# PROCEEDINGS

INTERNATIONAL WORKSHOP ON
RESEARCH STATUS AND PERSPECTIVES
IN LIQUID ROCKET COMBUSTION CHAMBER FLOW DYNAMICS

GDR Research Group Mascotte Bench
OH Emission (P = 60 bar) - (EM2C/CNRS-ONERA)

cnes

ONERA

DLR

CCT
Centres de Compétence Technique

19990719 063

DTIC QUALITY INSPECTED 4

PARIS France
May 27-28, 1999

REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 1999	3. REPORT TYPE AND DATES COVERED Conference Proceedings

4. TITLE AND SUBTITLE

International Workshop on Research Status of Perspectives in Liquid Rocket Chamber Dynamics

5. FUNDING NUMBERS

F61775-99-WF043

6. AUTHOR(S)

Conference Committee

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

ONERA
Direction deL'Energetique
B.P.72
Chatillon 92322
France

8. PERFORMING ORGANIZATION REPORT NUMBER

N/A

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

EOARD
PSC 802 BOX 14
FPO 09499-0200

10. SPONSORING/MONITORING AGENCY REPORT NUMBER

CSP 99-5043

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION/AVAILABILITY STATEMENT

Approved for public release; distribution is unlimited.

12b. DISTRIBUTION CODE

A

13. ABSTRACT (Maximum 200 words)

The Final Proceedings for International Workshop on Research Status of Perspectives in Liquid Rocket Chamber Dynamics, 27 May 1999 - 28 May 1999

This is an interdisciplinary conference. Topics will focus on liquid rocket combustion issues, including: Injection and Atomization (experimental and analysis aspects), Spray combustion in liquid rocket chambers, Experimental Methods and Diagnostics, Modeling and Analysis, Heat Transfer in combustion chamber, Liquid Rocket Combustion instability, Low Cost Technology

14. SUBJECT TERMS

EOARD, Combustion, Rocket Engines

15. NUMBER OF PAGES

575

16. PRICE CODE

N/A

17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
UNCLASSIFIED	UNCLASSIFIED	UNCLASSIFIED	UL

PROCEEDINGS

INTERNATIONAL WORKSHOP ON
RESEARCH STATUS AND PERSPECTIVES
IN LIQUID ROCKET COMBUSTION CHAMBER FLOW DYNAMICS

GDR Research Group Mascotte Bench
OH Emission (P = 60 bar) - (EM2C/CNRS-ONERA)

cnes

ONERA

DLR

CCT
Centres de Compétence Technique

PARIS France
May 27-28, 1999

Acknowledgments

Organizing Committee
International Workshop on Research Status and Perspectives
in Liquid Rocket Combustion Chamber Flow Dynamics

Objectives of the workshop

The workshop is aimed at gathering international experts in liquid rocket propulsion in order to :
- Provide an instantaneous picture of current international research activities in liquid rocket propulsion and planned efforts for the next few years.
- Identify fields of common interest and importance in liquid rocket combustion chamber flow dynamics research activity.
- Establish networks and enhance international scientific cooperation in the liquid rocket propulsion area.

Topics

- Injection and Atomization : Experimental and Analysis Aspects
- Spray Combustion in Liquid Rocket Combustion Chambers : Experimental Aspects and Diagnostics
- Spray Combustion in Liquid Rocket Combustion Chambers : Aspects of Modeling and Analysis
- Heat Transfer in Combustion Chambers
- Liquid Rocket Combustion Instability
- Low Cost Technology

Organizing Committee

France :   Paul Kuentzmann, Mohammed Habiballah (ONERA)
           Michel Pons, Patrick Vuillermoz, Eric Robert (CNES)
Germany : Wolfgang Koschel, Oskar Haidn (DLR)
USA :   Mitat Birkan (AFOSR), Jay Levine (Air Force Research Laboratory), Vigor Yang (Penn State University)

Local Committee

Fabienne Debruyère, Victor Burnley, Gérard Ordonneau, Yves Mauriot,
Mohammed Habiballah (ONERA)

Contents

Acknowledgments

Objectives of the workshop – Topics - Committees

The Status of the United States Air Force Liquid Propulsion Basic Research Program

International Workshop on Research Status and Perspectives in Liquid Rocket Combustion Chamber Flow Dynamics

27 May 1999

Mitat A. Birkan

Air Force Office of Scientific Research

PROPELLANT INJECTION

Heat Transfer

LIQUID-GAS SHEAR
Breakup Regimes

ATOMIZATION AND DROPLET FORMATION
Secondary Breakup, Coalescence

DROPLET HEATING,
VAPORIZATION AND DIFFUSION,
SPRAYS

LIQUID-LIQUID IMPINGEMENT
Fan or Sheet Formation

MIXING
Liquid Phase, Liquid-Gas,
Gas-Gas
Turbulence Effects

CHEMICAL REACTIONS
Liquid Phase, Gas Phase
Turbulence/Reaction Interactions

Transcritical Jets and Instability Control in Liquid Propellant Rocket Engines

HABIBALLAH(ONERA/France) CRYOGENIC COMBUSTION (MASCOTTE) (THEORY/EXP)

DROPLET COLLISION DYNAMICS AT TRANSCRITICAL CONDITIONS (THEORY/EXP) Law / PRINCETON

NONLINEAR ACTIVE CONTROL (THEORY/EXP) Culick / CALTECH

RAYLEIGH'S CRITERION BASED ACTIVE CONTROL (THEORY/EXP) Zinn / GEORGIA TECH

TRANSCRITICAL INTERFACE DYNAMICS IN TWO PHASE FORCED-CONVECTIVE ENVIRONMENTS (THEORY) Yang / PENNSTATE

MIXING CONTROLLED DYNAMIC CRITICALITY (EXP) Talley / AFRL

BOUNDARY ELEMENT SIMULATION OF JET ATOMIZATION (THEORY) Heister / PURDUE

MAYER (DLR/Germany) TRANSCRITICAL CRYOGENIC JETS AND SPRAYS (EXP)

BAZAROV(MAI/Russia NONLINEAR INJECTOR DYNAMICS (THEORY)

INSTABILITIES AND INJECTOR DYNAMICS(EXP) Santoro/PENNSTATE (EXP)

COMBUSTION INSTABILITIES IN SUB/SUPERCRITICAL TWO-PHASE FLOWS (THEORY) Williams / UCSD

3

Figure showing a plot of Measured ΔPc/Pc, % versus Frequency Ratio, $\omega 1T/\omega nat$.

Data points labeled: DRC, 5U Flat, 5U Baff, PFRT, FRT.

Annotations: Tangential Acoustic Wave; Jet Cross-Sections During Stages of Deformation.

Chamber Resonant Frequency, Hz

10^4 10^3 10^2

Air Force 0100 combustor

NASA LeRC research combustor

H-1 @ 200 klb thrust

H-1 @ 165klb thrust

1st stage engines of the Saturn 1B

1st stage engine of the Saturn V

F-1 flight engine

early F-1 engine model

Highest Predicted Instability Frequency

Stable region

Unstable region

10^{-5} 10^{-4} 10^{-3}

Injection Effect, seconds
(injector orifice diameter/injection velocity)

Liquid Rocket Engine Instability

Injector Orifice Dynamics

- Can effect combustion efficiency by as much as 5%.

- SSME Specific Impulse Error +/- 0.5 sec, $3M loss per launch.

AFRL empirical model
(Talley, AFRL/PRSA)

Small L/D

Large L/D

- **X-34 Fastrac engine Ox L/D = 2.6**

- Improved CFD required to resolve flow losses at short L/D.

6

Innovative Approach:
Pseudo-Density Formulation in 2-Phase Flows

Heister *et al.* (1998)

Cavitated Region

Kubota *et al.* (1992)

Cavitated Region

Fixed # Bubbles Per Unit Mass

$$\frac{D\rho}{Dt} = f(\rho, P, \vec{\upsilon})$$

- Permits Bubble Number Density to Continually Change

- Assumes Constant Number of Bubbles Per Unit Volume

- Integral Averaging of Rayleigh-Plesset Bubble Dynamics for 3D Codes

7

Pseudo-Density Code Accurately Predicts Unsteady Cavitating Slot Flow

Cavitation Length / Slot Length

* Henry: exp.
- - - Calculation

L_c/L vs ΔP(PSI)

Calculated Pseudo-Density Contours ($0.98 < \rho/\rho_l < 0.18$)

Theory:
Heister / Purdue
Sponsored by AFOSR
and Cummins Engine Co.

Experiments:
Henry & Collicott / Purdue
Sponsored by NSF and
Cummins Engine Co.

Elements of Model to Investigate Fully Coupled Dense Sprays Including Deforming Droplets

Droplet Atomization, Collisions, and Coalescence are all Modeled

Spray Attributes Evolve Naturally from Simulation

Steady-State Vaporization Theory of Interacting Droplets

$$\beta = \left(\frac{r_s}{r_b}\right)_0 \qquad \Delta = \frac{\ln\{1 + B_{interactive}\}}{\ln\{1 + B\}} \qquad \tau = t_{sd} / t$$

$$B_{interactive} = (Y_{Fb} - Y_{Fs}) / (Y_{Fs} - 1)$$

$$3\left(4 - d_s^{2}\right) - 2\beta\left(8 - d_s^{3}\right) = \left(12\Delta / \tau\right)$$

$$\tau_{interactive\ droplet\ lifetime} = \frac{\Delta}{1 - (4/3)\,\beta}$$

r_b

r_s

droplet

bubble

Unsteady Vaporization Theory of Interacting Droplets

Mass conservation:

$$\frac{d}{dt}\iiint \rho \, dV + \iint \rho(\vec{v}-\vec{w}).\vec{n}dA = 0$$

Momentum conservation:

$$\nabla p = 0$$

Energy conservation:

$$\frac{d}{dt}\iiint \rho e\, dV + \iint \rho(\vec{v}-\vec{w})e.\vec{n}dA = -\iint \vec{q}_e\,\vec{n}dA - \iint p\vec{v}.\vec{n}dA$$

Species conservation:

$$\frac{d}{dt}\iiint \rho Y_i\, dV + \iint \rho Y_i(\vec{v}-\vec{w}).\vec{n}dA = -\iint \vec{q}_i.\vec{n}dA$$

Soave-Redlich-Kwong equation of state:

$$p = \frac{\rho RT}{(W-b\rho)} + \frac{a\alpha\rho^2}{W(W+b\rho)}$$

Unsteady vs. Steady Models at Subcritical Pressures

Example:Heptane Droplet Vaporizing in 625 K Air at 5.72 atm

Initial droplet temperature = 443 K

Effect of Droplet Interaction on Heptane Vaporization in 1000 K Air and Hydrogen Environments

Effect of Droplet Interaction on Heptane Vaporization in 1000 K Air and Hydrogen Environments

Experimental Data vs Numerical Results

Heptane-Oxygen

p=30.3 atm
Do=500 mic.
Rb/Rd=100

★ Experimental
- - - T=1000 K
— T=1500 K
·-·- T=2500 K
·· ·· T=3500 K

$(d)^2$ (mm)^2

t (s)

Heptane / Oxygen

Initial Droplet Diameter: 500 micron

Calculated Regression Rate: 0.6 mm^2/sec

Measured Regression Rate: 1.58 mm^2/sec
(Clemons et al)

• **Experiments conducted with RP-1 in a Convective Combustion Environment**

Heptane-H2/O2

p=20 atm
Rb/Rd=100
Y H2=%2

★ Experimental
⋯⋯ T=1500 K
—·—· T=2500 K
⋯·⋯· T=3500 K

(d)² (mm)² vs t (s)

Heptane / Oxygen / Y_{H2}=2%

**Initial Droplet
Diameter: 245 micron**

**Calculated Regression
Rate: 0.8 mm²/sec**

**Measured Regression
Rate: 1.66 mm²/sec**
(Clemons et al)

•**Experiments conducted with RP-1 in a Convective Combustion Environment**

17

Droplet Lifetimes for Various Interacting Heptane Droplets in Various Gaseous Environments

p=20 atm , T=1000 K
Do=100 mic.
Rb/Rd=6

Heptane - Air

Heptane - Oxygen

Heptane - Oxygen - Hydrogen (%2)

Heptane - Oxygen - Hydrogen (%4)

Heptane - Hydrogen (%100)

$(d)^2 / (d_0)^2$

t (ms)

T=1000 K
Do=100 mic.
Rb/Rd=6

P=30 atm
P=20 atm

%2 H2

%4 H2

%2 H2

%4 H2

$(d)^2 / (d_0)^2$

t (ms)

0   10   20   30

1.0   0.8   0.6   0.4   0.2   0.0

Observation of Unstable Modes

Measured Pressure p_m is expressed as:

$$p_m(t) = \sum_{n=1}^{N}[a_n \sin(\omega_n t) + b_n \cos(\omega_n t)]$$

$$\begin{Bmatrix} \hat{a} \\ \hat{b} \end{Bmatrix} = \int_{t-2\pi/\hat{\omega}}^{t} p_m(\tau)\begin{Bmatrix} \sin \\ \cos \end{Bmatrix}\hat{\omega}\tau\, d\tau$$

$\hat{\omega}$

Determine corrected frequency

$\hat{a},\ \hat{b},\ \hat{\omega}$

fuel+oxidizer

secondary fuel

Pressure Transducer

Combustor

Observer

Actuator

Controller

21

Combustor

Primary Reactants Injection

Terfenol-D
Actuator

Control Signal
I(t)

Secondary Fuel Injection

Controlled Combustion
Heat Release

Pressure

p(t)

Observer

Controller

Transformation
to
Time Domain

Optical Window

Acoustic Energy Radiation
out of system (nozzle damping)

Unstable Combustor

Fuel

Oxidizer

Radiation
Measurement

Pressure
Measurement

ϕ

t

$P'(t)$

$Q'(t)$

Controlled $Q'(t)$

School of Aerospace Engineering

Oscillating Liquid Spray Combustion for Control of Combustion Instabilities

- **Objective:**

  Maximize the effectiveness of actuators that use liquid fuels to damp combustion instabilities

- **Goals of Controlled Combustion Process:**
  - Flame length much shorter than the acoustic wavelength.
  - Burn most of the fuel in a modulated form.
  - Release energy in a narrow phase domain.

Measured CH* Emission and Pintle Displacement at 170 Hz demonstrated excellent flame response.

A Schematic of the Investigated Combustor Setup

Oscillating Liquid Spray Combustion (continued)

Preliminary Results:

- High Effectiveness of the developed liquid fuel actuator demonstrated in the frequency range 150-800 Hz.

- The Amplitude and Phase of oscillations depend on the droplet size and velocity and are modified by variation of the control signal.

- Closed loop control of an unstable combustor was successfully demonstrated with the developed liquid fuel actuator.

Axial dependence of CH* Emissions Amplitude at 170 Hz

CH* Emission Amplitude (V) vs Distance from Flameholder (mm)

Legend: 20 % Duty, 35 % Duty, 50 % Duty, 65 % Duty, 80 % Duty

Axial dependence of CH* Emissions Phase at 170 Hz

Phase Angle (Degrees) vs Distance from Flameholder (mm)

Time Delay (ms): 5.88, 4.41, 2.94, 1.47, 0

Legend: 20 % Duty, 35 % Duty, 50 % Duty, 65 % Duty, 80 % Duty

Georgia Tech

AFOSR

Intrinsic Instabilities Identified for Diffusion Flames

- Relevant to Nonlinear Phenomena in Liquid-Propellant Rocket Instability
- Activation-Energy Asymptotics Applied to Derive Dispersion Relations
- Lewis-Number Effects are Important; Related to Cellular Flames
- Rate-Ratio Asymptotic Analyses are Needed in Future Work

Dispersion Relation

Physical Mechanism

TEN YEARS OF RESEARCH ON H_2-O_2 INJECTION

Vianney DUTHOIT
Michel RENE-CORAIL
Martin SION
Stéphan ZURBACH

SNECMA SEP Division,
Vernon, France

Roland BORGHI
Geoffrey SEARBY

IRPHE Laboratory
Marseilles, France

Patrick VUILLERMOZ
Michel PONS

CNES
Evry, France

snecma

TEN YEARS OF RESEARCH ON H_2-O_2 INJECTION

1. **Research Group**
   Organization
   Partners

2. **Research Themes**
   Atomization
   Single droplet
   Mixing
   Turbulent multiphase combustion

3. **Industrial interest**
   Phenomena comprehension
   Model elaboration

4. **Perspectives & lessons**

snecma

Division **SEP**

TEN YEARS OF RESEARCH ON H_2-O_2 INJECTION

- Organization -

1 "Research Group"

CNES
(State client)

→

SNECMA SEP Division
(industrial)

Research Program

→

"fictive" CNRS laboratory

ONERA
(Research partner)

CNRS
(Research partner)

SCIENTIFIC COMMITTEE involving all four partners deciding upon studies (Scientific / industrial relevance, continuation, evaluation).

snecma

Division SEP

TEN YEARS OF RESEARCH ON H_2-O_2 INJECTION

1 "Research Group"

- Partners -

CNES, Evry

SNECMA,
SEP Division, Vernon

CORIA, Rouen
Atomization & Combustion modeling,
LIF experiments

LCSR, Orléans
Single droplets experiments

LCD, Poitiers
Combustion studies
PDPA & Fiber optics atomization
experiments

IMFT, Toulouse
Turbulence studies

ONERA-CERT, Toulouse
Droplets chains experiments

LMM Jussieu, Paris
Liq/gas interface DVS

ENS, Paris
Theoretical studies

ONERA, Palaiseau
"Mascotte" GH_2 - LOX test facility
PDPA & CARS measurements

EM2C, Châtenay
Combustion modeling
LIF experiments

LPUB-LPM Dijon - Besançon
Spectroscopy

LEGI, Grenoble
Shear coaxial interactions
experimental studies

CRTBT, Grenoble
Cold Helium studies

IRPHE, Marseilles
Liq/gas interface behavior
unsteady multiphase flames

snecma

Division **SEP**

TEN YEARS OF RESEARCH ON H$_2$-O$_2$ INJECTION

2 "Research Themes"

Atomization

Mixing

Turbulent Multiphase combustion

Single droplets

H$_2$

O$_2$

H$_2$

snecma

Division SEP

TEN YEARS OF RESEARCH ON H_2-O_2 INJECTION

2 "Research Themes"

- Atomization -

Parameters of interest :

➤ **Liquid core length**

   Water-air experiments

   Fiber optics & ombroscopy measurements

   Laser sheet tomography & fluorescence

➤ **Resulting granulometry**

   PDPA measurements on H_2/O_2 10 bars

Dependency on momentum ratio

$$J = \frac{\delta_G U_G^2}{\delta_L U_L^2}$$

Dependency on Weber number

$$We = \frac{\delta_G U_G^2 D_L}{\tau}$$

snecma

2 "Research Themes" - Single droplets -

Parameters of interest :

➤ Thermomdynamical behavior of liquid gas interface at high p/pc ratio

➤ Droplet break-up type and length

No 'trivial' behavior (persistence or collapse) of liquid-gas interface

Result in We-Oh plane available for CFD models

snecma

TEN YEARS OF RESEARCH ON H_2-O_2 INJECTION

2 "Research Themes"

- Mixing -

Parameters of interest :

Mass fraction of propellants

Water-water experiments

High density gradients DNS

➢ Size of structures

Statistical maxwellian experiment analysis

High density gradient turbulence studies

Relevance of a turbulence based liquid-gas mixing approach : High density gradient turbulence model, liquid-gas surface density transport equations

snecma

2 "Research Themes"

— Turbulent multiphase combustion —

Température

Parameters of interest :

➤ Basic chemical kinetics and flame structure

➤ Interaction with liquid phase

   Influence of droplet size and supercritical conditions

   Adaptation of PdF shapes to liquid presence

   Adaptation of flame velocity evaluation

'simple' chemistry for H2/O2

'Thin'flame

Both families (flamelet & PdF) of models adapted

snecma

TEN YEARS OF RESEARCH ON H$_2$-O$_2$ INJECTION

3 Industrial interest

- Phenomena comprehension -

➤ **Confirmation of the key role of momentum ratio and LOX post diameter on liquid core (and flame) length (and efficiency).**

➤ **Flame anchoring very near LOX post lips**

➤ **Data on droplet sizes (=> inlet multiphase boundary conditions)**

➤ **Data on global flow structure (=> code calibration, thermal fluxes evaluation)**

➤ **Direct use for injector transfer function evaluation ("low frequency" instabilities)**

snecma

Division **SEP**

TEN YEARS OF RESEARCH ON H_2-O_2 INJECTION

3 Industrial interest

- Model elaboration and validation -

Atomization :

➤ "High-$\nabla\rho$" turbulence k-ε model

+ liquid-gas interface density transport equations

Closure laws   Criteria and delays for fragmentation and vaporization

Single LOX droplet studies (LCSR)

DNS high-$\nabla\rho$ (CORIA), liquid-gas interface (LMM)

Validation coaxial experimental setups :

Water-air + laser, fiber optics and ombroscopy (CORIA, LCD, LEGI)

Liquid-gaseous Helium + thermography (CRTBT)

Mascotte LOX-Hydrogen + laser tomography and PDPA (ONERA)

fiber optics (LCD)

Division **SEP**

snecma

TEN YEARS OF RESEARCH ON H_2-O_2 INJECTION

3 Industrial interest

Turbulent multiphase combustion :

➤ "PdF" based approach (CORIA)

➤ "Flamelet" based approach (EM2C)

Closure laws Two phase flame velocity Single droplet (LCSR)

Droplet chain (ONERA-CERT)

Counter-flow flame   EM2C

DNS

Validation base Metranol-air flame + statistical study (CORIA)

Mascotte LOX-H_2 flame + LIF OH (EM2C)

(1, 10, 60 bar)   LIF O_2 (CORIA)

CARS (ONERA)

snecma

38

3 Industrial

Mascotte test facility :

➢ LOX, 90 K,   40 ==> 400 g/s

➢ GH_2, 100 ==> 300 K,   5 ==> 70 g/s

➢ Test duration from 10 s (60 bar) to 20 s (1 bar)

Visualizations :
- OH Emission ,
- Laser Induced Fluorescence OH
- Laser Induced Fluorescence O2

Measurements :
■ PDPA
▲ CARS
● Fiber optics

FLTC 384/99

Division SEP

snecma

39

TEN YEARS OF RESEARCH ON H₂-O₂ INJECTION

3 Industrial interest

Simulation tool :

➤ Allow to accumulate research results usable for technology and hardware developments

⇨ **Types of calculations :**

	Cost		Complexity
	Manpower	CPU	
Feasibility studies to "explore" new code possibilities	High	Medium	High
Design studies allowing parametric investigation	Low	Low	Low
Simulation studies at the end of a design loop	High	High	Medium

Temperature field prediction of the Mascotte configuration at 1 bar

Temperature field prediction of the Mascotte configuration at 10 bar

snecma

40

TEN YEARS OF RESEARCH ON H_2-O_2 INJECTION

4 Perspectives & Lessons

➢ Model implementation to finalize

➢ Future research directions

- **Technological features**
  - swirl
  - recess
  - wide operating range
  - low frequency
  - high frequency

- **Combustion instabilities**

➢ Complementary between basic research / exp. validation / simulation tool

➢ Complementary between state / industrial / research partners :

long term commitment and financial involvement of everyone.

snecma

Comparative Study of Swirl-coaxial and Non-swirl-coaxial Injectors

Hiroshi TAMURA

National Aerospace Laboratory, KRC

1-Koganesawa, Kakuda, Miyagi 981-1522, Japan

email: tamura@kakuda-splab.go.jp

ABSTRACT

In connection with cost reduction and improvement of combustion efficiency of LOX/Hydrogen or LOX/Methane engines, employment of swirl-coaxial injectors seem to be wise, because with swirl-coaxial injectors, even employing large injection elements, which are easy to manufacture and thus can decrease production cost, high combustion efficiency may be expected. To establish the design methodology of swirl-coaxial injectors, a comparative study of swirl-coaxial injectors and shear-coaxial injectors has been conducted.[1,2] Steady state combustion characteristics were examined with multi-element injectors with a nominal thrust of 10 kN and a 14 kN, and a chamber pressure of 3.5 MPa. Combustion characteristics were evaluated in relation to chamber pressure distributions, wall temperature distributions, and ηc^*s.

The main findings on the steady state characteristics were as follows:

1) Shear-coaxial injectors require a longer chamber to complete vaporization as compared with those of swirl injectors; therefore, the ηc^* of shear-coaxial injectors is apt to be limited by vaporization efficiency. 2) Combustion with swirl injectors starts near the injector face and ends within a short chamber length. The ηc^* of swirl injectors is, therefore, apt to be limited by mixing efficiency. 3) Injection velocity of fuel affects secondary atomization of LOX spray. That is, the higher the fuel injection velocity, the finer the size of LOX droplets. Fine atomization promotes combustion near the injector face.

Because of the remarkable differences of steady state combustion characteristics, combustion stability characteristics are also expected to be significantly different from each other. Stability characteristics were examined by introducing a bomb disturbance during steady state combustion.[3] LOX/hydrogen and LOX/methane were used to see the effect of fuel density on the stability characteristics. Although all tests were judged to be stable, the differences of stability characteristics of shear-coaxial and swirl-coaxial injectors were evaluated based on amplitudes and frequencies of the induced pressure disturbances.

The main findings on the stability characteristics were as follows.

1) The magnitudes of the induced maximum pressure disturbances, P'max/Pc, decrease with an increase of injection velocity ratio, Vf/Vo, for both injector types. 2) The magnitudes of P'max/Pc with swirl-coaxial injectors were shown to be smaller than those with coaxial injectors at the same Vf/Vo. 3) The correlations between P'max/Pc and Vf/Vo were grouped in a single curve regardless of the difference of propellant combinations for coaxial injectors and for swirl-coaxial injectors, respectively. 4) A plausible reason for the observed trends is the interaction between the shock wave induced by a bomb and LOX droplets.

A cooperative study between NAL and DLR is now on going to see the combusting flame during unstable combustion. The rectangular chamber whose acoustic frequency is the same order with a typical large rocket engine will be designed. The chamber has 12 injection-elements with glass windows which allows optical observation. Bomb disturbance is planed to be introduced.

REFERENCE

[1] Sasaki, M. et al., "Comparative Study of Recessed and Non-recessed Swirl Coaxial Injectors," AIAA 97-2907, 1997.

[2]Tamura, H. et al., "LOX/LH2 Subscale Swirl Coaxial Injector Testing," AIAA 97-2906, 1997.

[3]Sasaki, M. et. al, "Experimental Study on Stability Characteristics of Non-swirl and Swirl Coaxial Injectors," AIAA 98-3438, 1998.

Comparative Study of Swirl-coaxial and Non-swirl-coaxial Injectors

Hiroshi TAMURA
National Aerospace Laboratory, KRC
1-Koganesawa, Kakuda, Miyagi 981-1522, Japan
email: tamura@kakuda-splab.go.jp

## Purpose of the Study and Method of Approach

Establishment of design methodology for swirl-coaxial injectors with large injection elements.

Steady state characteristics were evaluated in relation to chamber pressure distributions, wall temperature distributions, and ηc^*s with multi-element injectors with nominal thrusts of 14 kN and 10 kN and a chamber pressure of 3.5 MPa.

Stability characteristics were studied by introducing a bomb disturbance during steady state combustion. LOX/hydrogen and LOX/methane were used to see the effect of fuel density. Stability characteristics were evaluated based on amplitudes and frequencies of induced pressure disturbances.

Comparison of Steady State Combustion Characteristics

PARIS-France   May 27-28, 1999

a: Shear-coaxial injectors   b: Swirl-coaxial injectors

Fig. 1 Comparison of non-swirl and swirl injectors

a: Non-recessed swirl-coaxial   b: Recessed swirl-coaxial

Fig. 2 Comparison of recessed and non-recessed swirl-coaxial injectors

Swirl-coaxial injectors with a recessed LOX post showed a self-pulsation of the spray. To avoid instability related to this self-pulsation, recessed injectors with swirl-coaxial was not used.

PARIS-France   May 27-28, 1999


a: 14 kN injector   b: 14 kN chamber

c: 10 kN injector   d: 10 kN chamber

Fig. 3 Configuration of injector and chamber

a: Details of 14 kN injector   b: Details of 10 kN injector

Fig. 4   Injector configuration

| 14 kN INJECTOR					10 kN INJECTOR					
Name	B	C	D	LD	Name	H1	C1	H2	C2	C3	C4
Type	coax	→	→	→	Type	coax	→	swirl	→	→	→
do	2.4	→	→	→	do	2.14	→	1.26x6	→	→	→
de	4.0	→	→	→	de	5.3	→	→	→	→	→
R	.0	→	→	→	R	5.3	→	0	→	→	→
DFI	4.4	→	→	→	DFI	6.3	→	→	→	→	→
DFO	5.5	6.4	7.0	7.0	DFO	10.0	9.0	10.0	7.4	8.0	9.0
L1	51	→	→	67.5	L2	77	→	73	→	→	→
L2	15	→	→	51							

a: Shear-coaxial injectors   b: Swirl-coaxial injectors

(10 kN injectors)

Fig. 5 Comparison of axial pressure distribution

A pressure drop in a cylindrical section of the combustor is caused by the momentum pressure loss, thus pressure distribution indicates the progress of combustion.

a: Shear-coaxial injectors   b: Swirl-coaxial injectors

(10 kN injectors)

**Fig. 6 Comparison of L50s as a function of mixture ratio**

The length required for chamber pressure drop to the mean value of the chamber pressure, L50, is a measure for the required chamber length for complete combustion.

PARIS-France   May 27-28, 1999


a: Axial wall temperature distribution   b: c* efficiency ηc*

(10 kN chamber)

Fig. 7 Comparison of wall temperature distribution and ηc*

Comparison of swirl-coaxial and shear-coaxial injectors	
Shear-coaxial injectors	Swirl-coaxial injectors
Coarse LOX spray	Fine LOX spray
Vaporization limited	Mixing limited
Large Vf/Vo improves ηc^*	Small Vf/Vo improves ηc^*
Combustion starts far injector face	Combustion starts near injector face
Low heat load near injector face	High heat load near injector face
Require longer chamber	Shorter chamber is possible

PARIS-France   May 27-28, 1999

Comparison of Stability Characteristics

Fig. 8 Typical dynamic pressure trace

PARIS-France   May 27-28, 1999

Dynamic pressure trace   Pulse spectrum

a: Coaxial injector: H1, Pc=3.44 MPa, O/F=6.16, Vf/Vo=29.1, RDX= 2 grain

Dynamic pressure trace   Pulse spectrum

b: Swirl injector: H2, Pc=3.47 MPa, O/F=6.03, Vf/Vo=4.11, RDX= 2 grain

Fig. 9 Dynamic pressure trace and its pulse spectrum
(LOX/H2, 10 kN injectors)

Dynamic pressure trace   Pulse spectrum

a: Coaxial injector: C1, Pc=3.59 MPa, O/F=3.69, Vf/Vo=12.7, RDX= 2 grain

Dynamic pressure trace   Pulse spectrum

b: Swirl injector: C3, Pc=3.66 MPa, O/F=3.57, Vf/Vo=1.25, RDX= 2 grain

Fig. 10 Dynamic pressure trace and its pulse spectrum
(LOX/CH4, 10 kN injectors)

PARIS-France   May 27-28, 1999

a: 14 kN chamber   b: 10 kN chamber

Fig. 11 Induced maximum pressure, P'max/Pc,
vs Injection velocity ratio, Vf/Vo

51

a: Dynamic pressure trace   b: Eliminate low frequency components

c: Hilbert transformation   d: Obtain decay rates using log-scale

Fig. 12 Decay rate of induced pressure disturbance

PARIS-France   May 27-28, 1999

a: Decay rates of 1L-mode   b: Decay rates of 1T mode

Fig. 13 Correlation between decay rates of induced pressure disturbance and injection velocity ratio (LOX/CH4, coaxial injectors, 14 kN chamber)

Summary of stability rating test results

1) Induced pressure disturbances, P'max/Pc, decreases with an increase of injection velocity ratio, Vf/Vo.

2) The P'max/Pc with swirl-coaxial injectors are smaller than those with coaxial injectors at the same Vf/Vo.

3) The correlation between P'max/Pc and Vf/Vo are able to be grouped in a single curve regardless of the difference of propellant combinations for coaxial and for swirl-coaxial injectors, respectively.

4) Observed correlations indicate existence of the interaction between the shock wave induced by a bomb and LOX droplets. That is, the larger the LOX droplets, the more the sensitivity to the shock disturbance.

PARIS-France   May 27-28, 1999

Current program

A cooperative study between NAL and DLR is now on going. The purpose of the study is visualization of combusting flame during unstable combustion. The optically accessible rectangular chamber, its acoustic frequency is the same order to a typical large rocket engine, is designed. The chamber has 12-swirl and non-swirl coaxial injection elements. Bomb disturbance is plan to introduce.

W. Mayer and H. Tamura "Flow Visualization of Super-critical Propellant Injection in a Firing LOX/GH2 Rocket Engine," The Journal of Propulsion and Power, vol. 12 No. 5,   1996.

Our previous study on flow visualization in a LOX/H2 rocket chamber   (LOX/H2, Pc=4.5 MPa, Vo=30 m/s, Vf=300 m/s, do= 1mm)

53

EXPERIMENTAL INVESTIGATIONS OF CRYOGENIC SPRAYS IN COMBUSTION

by
Pierre GICQUEL, Lucien VINGERT
ONERA
29, Avenue de la Division Leclerc
92320 CHATILLON
France

ABSTRACT :
Three experimental investigations have been done on the cryogenic test bench MASCOTTE at ONERA Palaiseau center with the objective to study the LOX spray characteristics in combustion.
Informations concerning the breakup process at 0.1 and 1 MPa were obtained by the mean of a visualization technique. Quantitative and qualitative description of the spray were then obtained by the use of a Phase Doppler system.A map of droplets size and velocity has been realized. The influence of the momentum ratio J on the first atomization process has been also shown.
Recently, with the objective to analyse the local Weber number by the mean of discrimination liquid and gas velocity, a last experiment has been performed with a 2D LDV system.
All those results participate for a better understanding of atomization in cryogenic sprays in combustion.

NOTATION

J	momentum ratio (gas/liquid)	Vm	axial mean velocity
D_0	initial droplet diameter	m_G	gas mass flowrate
te	evaporation time	m_L	liquid mass flowrate
ts	residence time	MPa	pressure (in MPascal)
λ_{eff}	evaporation constant	V_L	liquid velocity
L	combustor length	V_G	gas velocity
Vg	droplet mean velocity	We	Weber number

INTRODUCTION
Cryogenic propellant combustion systems have been now applied successfully for many years in rocket engines (Ariane 1 to 5 , SSME, ...). However, to improve the performance of this type of combustion systems and get a good modelling of the combustion, we need a better understanding of the elementary mechanisms, in particular atomization and vaporization processes.
A lot of works has been performed last 10 years to study the behaviour of many sprays. All those studies were more often conducted with simulant fluids (water for the main off them). It is of course because it's more difficult to performed those studies on real fluids with real hot fire conditions.
To contribute answering those questions a cryogenic test bench, called MASCOTTE, was built and a test program was conducted under a consortium of laboratories and manufacturers associating ONERA, CNRS, CNES and SEP. The main objective was to provide a good description of atomization and vaporization processes under hot fire conditions and, by this way, to have a better understanding of this kind of combustion.
This article describes experiments performed during combustion tests mainly focused on the LOX droplets size analysis.
First, with the goal to provide preliminary informations on the fluid dynamics of the LOX core breaking process, a visualization technique, using a stroboscopic laser sheet associated with a high speeed camera (2000 frames/s), was used.
After those initial visualizations the main objective of this work consisted in measuring LOX droplets size and velocity on the axial and radial flow to get a good mapping of droplets size and velocity in the combustion

chamber. Two pressures have been perform, 0.1 and 1 MPa. A PDPA system with one component of velocity was used for those measurements.

The two experimental investigations (at 0.1 MPa and 1 MPa) give a good qualitative (by visualization) and quantitative (by Phase Doppler technique) description of the LOX spray in term of atomization and and vaporization process in hot fire conditions. At 0.1 MPa three different zones has been detected: near the post tip a first atomization zone, after a relative long ligaments zone and finally a well defined droplets spray.

A comparison between LOX droplets size and velocity at 0.1 and 1 MPa give us informations on the influence of the pressure on the atomization process.

The influence of the J number (momentum ratio) on the atomization has also been performed at 1 MPa.

A last characterization has been perform recently, for instance in cold flow conditions, with the objective to analyse the local Weber number by the mean of discrimination of liquid and gas velocity.

OPTICAL SETUP

Three optical configurations have been used during those experiments. On the picture of the figure 1 the PDPA setup is shown on the test bench. Like is well know today the PDPA is a size and velocity particles optical measurement system. The PDPA complete theory has been described and explained in details in reference [1].

The schematic drawing of figure 2 shows the optical configuration used for the visualization tests. This visualization has been performed by the mean of a stroboscopic laser sheet associated with a high speed camera. The laser sheet was formed by a stroboscopic copper laser beam (at $\lambda = 510.6$ nm) focused through a cylindrical and spherical lens. This sheet was about 70 mm wide and 1 mm thick near the chamber axis. The strobe frequency was 2 kHz and the pulse time duration about 40 ns. A high speed 16 mm movie camera (NAC E – 10) was used in association with black and white high speed sensibility movie film (500 ISO). This camera was used at 2000 frames/s and synchronised via an optical pick-up to the strobe frequency.

On the picture of figure 3 the optical 2D LDV system used recently for a 2D velocity analysis of both LOX and gas hydrogen is shown.

DROPLET SIZE AND VELOCITY RESULTS

The operating conditions are listed in the table 1. Those conditions were used for the two first campaings in combustion (drop size and visualisation).

Case	Pressure MPa	V_L m/s	m_G g/s	V_G m/s	J	M	We 10^5	Re 10^5
A	0.1	2.21	15.00	893	13.4	3.30	0.598	0.67
A-10	1	2.23	23.70	308	14.5	2.10	0.20	0.67
C	0.1	2.21	10.00	628	6.3	5.00	0.304	0.67
C-10	1	2.23	15.80	207	6.5	3.20	0.09	0.67

Table 1 : Operating conditions

For all cases the LOX mass flowrate was maintained constant at 50 g/s.

Results at 0.1 MPa [2, 3, 4]

The LOX spray evolution in the combustion chamber has been describe quantitatively and qualitatively. A map of the LOX droplet sizes and velocity has been done on all the length of the combustion chamber. One measurement point (on the axe) has been done also outside of the confining chamber and shows that droplets exist yet in this zone far from the front flame and cross it. Comparison between residence time (defined as : $t_s = L / Vg$), and evaporation time (defined as $t_e = (D_0)^2 / \lambda_{eff}$ by A. H. Lefebvre [5]) shows that at 0.1 MPa droplet size up to 200 μm was partially evaporated.

A comparison with computed empirical correlations [6, 7, 8] shows that the droplet size measurements are in the same order that results give by the empirical correlations. For more informations see the reference [4].

An « artistic drawing » of the qualitative description of the spray is shown on figure 4.

Results at 1 MPa

Like above, for the 0.1 MPa campaing, a qualitative and quantitative description of the spray has been done. Those complementary results have allowed to do a comparison, at the same cross section of the chamber, between 0.1 MPa and 1 MPa. The results at 1 MPa show a lower number density but droplet size (D_{10}, D_{32}) are bigger than at 0.1MPa (figure 5). The measurement validation rates are also better at 1 MPa. This shows that at high pressure all the small droplets are evaporated very quickly near the post tip of the injector and after only big structures and droplets are present in the spray.

56

A droplet size evolution versus J number has also demonstrated the importance of the momentum ratio for the first atomization process (figure 6).

VISUALIZATION RESULTS

Results at 0.1 MPa
During this first campaing only the zone near the injector has been analysed (from the injector post tip to 70 mm backward). A macro description of the breakup process has been done (figure 7) and has allowed to give an evolution, on 4 ms, of an attach ligament to simple droplets (spherical or not).

Results at 1 MPa
The aim of this test campaing at 1 MPa was to follow the LOX structure (if she exists) along the combustion chamber. Like a first result, a comparison with results at atmospheric pressure shows that the flame emission was clearly detectable at high pressure and not at 0.1 MPa. On figure 8 two pictures recorded during the test campaing are presented. First the phenomena were recorded without any filter to reject the luminous flame light (a). Here it is easily to see the LOX structure inside the flame. In a second configuration, a bandpass filter, centered at the wavelength of the laser beam, around 510 nm, was fitted in front of the camera lens. In this configuration only the scattered light of the liquid structure was visualized (b).
The analysis of the pictures at same axial positions confirms the PDPA results. The spray is denser at atmospheric pressure. Pictures far from the injector (X/d > 30) shows only big structures.

LDV TWO PHASES FLOW RESULTS
A last campaing, perform in 1999, has allowed to get a better description, in term of velocity, of a coaxial LOX stucture with an anulus gas flowrate. The 2D LDV measurements has been done, for instant, in none reactif flow (LOX and gas N2 and He).The main objective was to get the local Weber number by the mean of velocity discrimination between LOX droplets and gas. For gas velocity analysis a seeding system was added to to the gas distribution panel. The particles were chosen as zirconium oxide, with the objective to be used later in combustion tests.
A first theoretical analysis has been done by Onofri[9] to find the best optical configuration of the 2D LDV system. This analysis has given a numerical optimisation based on the diffusion of the two kind of particles (droplets and solid particles). For solid particles less than 1 µm, used for seeding the gas mass flowrate, and angular zone between 64° and 114° seem to be the best optical configuration.
For instance the first results show an important recirculation zone near the injector. An other important result shows that the seeding solid particles stay in the gas zone and never reach the two phases flow in the LOX spray. At the present time a software is on development with the objective to be able to analysed the raw signals and extract from the intensity levels of each particle the velocity of LOX droplets and seeding particles of the gas.

CONCLUSION
This paper has presented the main results got during a combustion test program performed on the ONERA cryogenic test bench MASCOTTE. Three experimental investigations were performed until today. Those investigations were mainly focused on the LOX droplet size and velocity analysis.The visualization technique give us first informations on the LOX structure and particularly the difference between tests at atmospheric pressure and 1 MPa. By the use of a PDPA measurement technique, a good mapping of droplet size and velocity around the LOX core has been obtained.
As main conclusions today we can say that we have got :
- a good qualitative (by visualization) and quantitative (by PDPA technique) description of the LOX sprays ;
- those results provide us informations on the atomization process under hot fire conditions, with a comparison between atmospheric pressure and 1 MPa ;
- the last step is yet under analysis, but would be able to help us to understand the local spray evolution by the knowledge of the local Weber number.

REFERENCES:

[1]   **W. D. Bachalo, M. J. Houser**, *Phase Doppler spray analyser for simultaneous measurements of drop size and velocity*, Optical Engineering, volume 23, N° 5, 1984.

[2]   **P. Gicquel, L. Vingert D. Lourme, L. Menoret**, Coaxial Injectors Atomization, Progress in Astronautics and Aeronautics, vol. 169, Chap.6, pp. 145-189, 1995.

[3]   **P. Gicquel, L. Vingert et E. Brisson**, *Caractérisation expérimentale d'un brouillard LOX-GH2 en combustion issu d'un injecteur coaxial*. Actes du 5 ième « Colloque du GDR Combustion dans les moteurs fusées »

[4]   **P.Gicquel, E. Brisson, L. Vingert**, Experimental investigation of a LOX spray under hot fire conditions. ICLASS 97, Seoul (Korea), August 18-22, 1997.

[5]   **A. H. Lefebvre,** *Atomization and Sprays*, Hemispher Press, NY, 1989

[6]   **S. Nukiyama and Y. Tanasawa**, *Experiments on the atomization of liquids in an air stream*, Trans. Soc. Mech. Eng. Jpn., vol. 5, N° 18, pp. 62-67, 1939.

[7]   **E.G. Lorenzetto and A.H. Lefebvre,** *Measurements of drops size on a plain jet airblast atomizer,* AIAA Journal, vol 2, N° 3, pp. 583-585, 1964.

[8]   **K. Y. Kim and W. R. Marchal** *Drop size distributions from pneumatic atomizers,* Journal of Am. Chem. Eng., vol 17, N° 3, pp. 575-584, 1971.

[9]   **F. Onofri**, *Optimisation numérique de la configuration expérimentale à adopter lors de la campagne de mesure des champs de vitesse particulaire/fluide du foyer LOX/GH2 « MASCOTTE »* Rapport d'étape CNRS du 3 sept. 1998

Fig 1. Optical PDPA arrangement on MASCOTTE test bench

Fig 2. Optical visualization setup

Fig 3. 2D LDV system optical arrangement

Fig 4. Qualitative description of the spray at 0.1MPa

Fig 5. D_{32} comparison between 0.1 MPa et 1 Mpa



Fig 6. D_{32} evolution versus momentum ratio J

Fig 7. Evolution of the breakup process during 4 ms

(a)   (b)

Fig 8. Visualization of flame and spray (a) and spray only with an additional green filter (b)

Quantitative Density Measurements in Supercritical LN2-Sprays Using Raman Scattering

M. Oschwald, A. Schik

Deutsches Zentrum für Luft- und Raumfahrt
Raumfahrtantriebe
Lampoldshausen

U.E. Mayer, W. Stricker

Deutsches Zentrum für Luft- und Raumfahrt
Institut für Verbrennungstechnik
Stuttgart

Motivation

conditions in a cryogenic high pressure rocket combustor:

Vulcaine-motor:

fuel:	GH2	
oxidizer:	LOX	

T≈100K   P≈10MPa

thermodynamic critical point of O_2:   **T_c=165.6K P_c=5.04MPa**

in the trans- and supercritical region real-gas behavior influences

- atomization and mixing
- heat and species transport

basic experiment:

coaxial injection of LN2 and H2 (optional): T_i=100K-140K P_T<6MPa
thermodynamic critical point of N2: T_c=126.2K P_c=3.4MPa

Laser diagnostics for **quantitative** investigation of the jet disintegration at conditions similar to rocket combustors:

thermodynamical state: $P_T/P_{C,LN2} \approx P_{cc}/P_{C,LOX}$

non-dimensional numbers: Re, We, J (LN2/GH2) $\approx$ Re, We, J (LOX/GH2)

idealized conditions: no combustion

DLR

Cryo-Injector Test Facility

coaxial-injector

LN_2 $\varnothing = 1.9mm$
H_2 $\varnothing_i = 2.4mm$
$\varnothing_o = 3.2mm$

injection of H2 is optional

T_{GH2}

T_{LN2}

injector

window

window

reservoir

DLR

Optical Diagnostics at High Pressure

strong molecular interaction → line broadening

strong gradients of the refractive index → laser beam steering

high signal intensities → non-linear effects

Spontaneous Raman-Scattering

species-specific

linear process, relative insensitive to molecular interaction

signal intensity profits from high densities

pulsed lasers:

$\approx 25 MW/cm^2$

2D

good temporal resolution

statistical characterization

risk of gas break down

non-linear effects

XeCl-excimer laser (351nm)

cw-lasers:

$\approx 10 kW/cm^2$

1D

temporal average

mean values

no gas break down, no non-linear effects

simple experimental set-up

Ar-ion laser (488nm)

Nitrogen: Thermophysical Properties   4MPa

Nitrogen: Thermophysical Properties　　4MPa

workshop May 27-28 1999.DOC

DLR

German Aerospace Center

Deutsches Zentrum für Luft- und Raumfahrt e.V.

test cases

	V_{N2} [m/s]	V_{H2} [m/s]	T_{N2} [K]	T_{H2} [K]	ρ_{N2} [kg/m³]	ρ_{N2}/ρ_{H2}	$Re_{N2}/1000$	$\rho v^2_{N2}/\rho v^2_{H2}$
A4	5		140		151		115	
B4	5		118		582		126	
C4	20		100		707		340	
D4	5	60	140	270	151	39	115	3.7
E4	5	120	118	270	582	151	126	3.8
F4	5	60	118	270	582	151	126	0.95

$P_T = 4 MPa \qquad P_T/P_c = 1.17$

1D-Raman Scattering

optical set-up

laser:
Ar^+, 488nm,
1.5 Watt

detector:
slow scan ICCD
integration "on chip"
1s

filter:
prisms and apertur;
OG550, Interference-filter
$T(488nm)<10^{-12}$
$T(551nm)=0.3$

$S/N \approx 40$ at 4MPa

aperture   lense

prisms

N2-jet

filters

ICCD-camera

Ar^+-laser

DLR

German Aerospace Center

Deutsches Zentrum für Luft- und Raumfahrt e.V.

4MPa

Nitrogen Free-Jet
row data

case A4
$T_{N2}=140K$
$n_{1,2}=1.025$

case C4
$T_{N2}=100K$
$n_{1,2}=1.157$

DLR

Nitrogen Free-Jet

radial density and temperature profiles

case A4/B4

case A4
x=2mm

case B4
x=16mm

German Aerospace Center

Deutsches Zentrum für Luft- und Raumfahrt e.V.

normalized temperature

normalized density

normalized density/temperature

= 1: injector conditions
= 0: tank conditions

German Aerospace Center

Deutsches Zentrum für Luft- und Raumfahrt e.V.

coaxial LN2/GH2-injection   case D4

radial density profiles for nitrogen (140K) und hydrogen

x=2mm

x=10mm

German Aerospace Center

Deutsches Zentrum für Luft- und Raumfahrt e.V.

4MPa

coaxial LN2/GH2-injection
maximal density

case **E4**: nitrogen (118K) / hydrogen

case **D4**: nitrogen (140K) / hydrogen

DLR

76

Experimental Arrangement

scattered light suppression by polarization or 2 species simultaneously

**Institute for Physical Chemistry of Combustion, Stuttgart
Division Space Propulsion, Lampoldshausen**

N$_2$ Densities and Temperatures

axial position 41.5 mm below injector; 60 bar, 20 m/s N$_2$ into N$_2$

single pulse

averaged image

**Institute for Physical Chemistry of Combustion, Stuttgart
Division Space Propulsion, Lampoldshausen**

DLR

um970401.doc

Deutsche Forschungsanstalt für Luft- und Raumfahrt e.V.

Simultaneous Detection of H_2 and N_2
distance from injector 35-50 mm; no stray light suppression

15 m/s LN_2
150 m/s H_2
into
40 bar GN_2

single pulse

averaged images

DLR

N_2

N_2

H_2

H_2

Institute for Physical Chemistry of Combustion, Stuttgart
Division Space Propulsion, Lampoldshausen

20 m/s LN$_2$ into 6 MPa GN$_2$:
Average N$_2$ Densities and Std. Deviation

average density at three downstream positions

standard deviation


Institute for Physical Chemistry of Combustion, Stuttgart
Division Space Propulsion, Lampoldshausen

um970413.doc

DLR

15 m/s LN₂ and 100 m/s H₂ into 6 MPa GN₂: Average N₂ Densities and Std. Deviation

## average density at three downstream positions

## standard deviation

Institute for Physical Chemistry of Combustion, Stuttgart
Division Space Propulsion, Lampoldshausen

um970421.doc

DLR

Deutsche Forschungsanstalt für Luft- und Raumfahrt e.V.

Comparison: Raman Imaging <-> Shadowgraphy
distance from injector 35-50 mm; no stray light suppression

5 m/s LN_2 into 40 bar GN_2 single pulse

20m/s LN_2 into 40 bar GN_2 single pulse

Raman

shadow

DLR

Institute for Physical Chemistry of Combustion, Stuttgart
Division Space Propulsion, Lampoldshausen

82

Summary

Spontaneous Raman Scattering

- cw-laser: no risk of interference due to gas break down and stimulated Raman scattering

- pulsed laser: with carefull adjustment of pulse energy and pulse length no interference due to gas break down and stimulated Raman scattering

- strong laser beam steering and elastic scattering in the near injector region due to gradients of the refractive index. Gradients increase with injection of H2.

- at both excitation wavelengths (488nm, 351nm) broadband background signal observed; source not finally identified

- **quantitative density and temperature measurements possible with cw-laser and pulsed laser**

workshop May 27-28 1999.DOC

DLR

Summary

Nitrogen Free-Jet

- different development of and temperature and density distribution
- strong influence of the thermodynamical state on the development of the temperature profiles
- colder (more dense) N_2-jet: slower disintegration

coaxial LN2/GH2-injection

- constant density on the first few x/D in the core flow observed for $T_{N2} < 130K$
- increased standard deviation in the boundary layer of the N_2-jet as compared to the free jet case
- increasing H_2–density downstreams the injector observed
- increasing T(N2) $\Rightarrow$ more efficient atomization
- increasing H_2-momentum flux $\Rightarrow$ more efficient atomization

84

Studies on the Break-up Regimes of LOx Droplets

Bruno Vieille, Christian Chauveau and Iskender Gökalp

Laboratoire de Combustion et Systèmes Réactifs

CNRS - Orléans

E-mail : vieille@cnrs-orleans.fr

Boris Gelfand, STCP, RAS, Moscou

Contents

- Introduction

- Experimental set-up and diagnostics

- Results
  - Aerodynamic field
  - Break-up regimes
  - Characteristic times

- Conclusions

Vulcain coaxial injector

Liquid - gas
interaction area

Formation of droplets
and ligaments

GH_2

Gaseous hydrogen

U = 650 m/s

Liquid Oxygen

U = 12

Gaseous hydrogen

87

Activités du L.C.S.R.

Expérimentale : en configuration monogoutte :

goutte primaire	initiation de la cassure	gouttes secondaires	fin de vaporisation

bag BU

trans. BU

shear BU

Temps d'initiation	regime de cassure	duree de cassure	temps (taux) de vaporisation des gouttes secondaires

temps total de cassure

nombre et taille des gouttes secondaires

Expérimentale : Spray inerte

Numérique : vaporisation / combustion goutte isolée

PARAMETRES INFLUANÇANTS

Temps d'initiation et régime de cassure :

- Reynolds
- Weber
- Ohnesorge
- pression (via rapport de densité gaz/goutte)

Duréé de la cassure (temps total – temps d'initiation) :

- Weber
- rapport de densités
  $\rightarrow$ indépendant de la pression

Nombre et taille des gouttes secondaires :

- Reynolds
- Weber
- pression
- D_0 (diamètre initial goutte primaire)

Temps de vaporisation :

- Reynolds turbulent $\dfrac{k^{1/2}d}{v_{gaz}}$
- Schmidt
- Shmidt turbulent $\dfrac{k^{1/2}L}{D_{12}}$
- Lewis
- Pression

Objectives

- To study the deformation and break-up regimes of liquid oxygen droplets subjected to aerodynamic shear forces under high pressure.

- To explore regimes in a very large range of the density ratio ($13 < \rho_l/\rho_g < 3500$) and of the droplet Weber and Reynolds numbers.

- To provide useful experimental data base to validate theoretical and numerical studies.

Droplet - jet interaction

Light source

Liquid oxygen droplets

Cryogenic injector

Flow

High speed camera

Experimental set-up

Cryogenic injector

High pressure chamber (P_{max} = 12 MPa)

Numerical high speed camera (45 000 im/s)

92

Diagnostics and image processing

- Visualisation by numerical high speed camera up to 9000 images / second.

- Images processing based on Visilog software.

93

- Two components laser Doppler anemometry and particle image velocimetry for the characterisation of the aerodynamic field.

Exploration area by video camera

Cryogenic injector

Visualisation window (9000 im/s)

Visualisation window (4500 im/s)

12 mm

5,25 mm

13,5 mm

6 mm

Flow pipe

Exploration area by PIV

Cryogenic injector

19 mm

30 mm

5,25 mm

13,5 mm

6 mm

Flow pipe

Conditions explored for the aerodynamic field characterisation

$$Re_{ec} = \frac{\rho_g U D}{\mu_g}, \quad D : \text{flow pipe diameter}$$

Gas	Technique	Pressure (MPa)	Re_{ec}
Dry air	LDA	0,1 - 4	10000 - 30000
Helium	LDA	1	10000
Dry air	PIV	0,2 - 8	3000 - 9000

Aerodynamic field characterisation

Speed (m/s)

0.1 0.3 0.5 0.8 0.8 1.0 1.2 1.4 1.8 1.7 1.9 2.1 2.3 2.5 2.8

Gas : Dry air, P = 0,5 MPa

Conditions explored

$$DR = \frac{\rho_l}{\rho_g} \;, \; We = \frac{\rho_g \, U^2 \, D}{\sigma} \;, \; Re = \frac{\rho_g \, U \, D}{\mu_g}$$

D : initial droplet diameter

| Liquid-gas couple	DR	We	Re
Ethanol / dry air	13 - 800	5 - 120	500 - 17000
Liquid oxygen / dry air	20 - 1030	2 - 850	600 - 7500
Liquid oxygen / helium	63 - 3500	1 - 180	320 - 3300

# Superposition of the aerodynamic field and droplet break-up images

Liquid oxygen / Helium couple
P = 0,2 MPa, We = 18, Re = 660

Surface tension measurement

Legend:
- ■ LOx / Helium
- ◆ LOx / Air
- --- LOx / Oxygen (theoretical)

Y-axis: Surface tension (N/m), ranging from 0 to 1.6E-2 (4E-3, 8E-3, 1.2E-2, 1.6E-2)

X-axis: Pressure (MPa), ranging from 0 to 8

Droplet deformation and break-up regimes

Flow

1 : No break-up regime
2 : Bag break-up regime
3 : Transitional break-up regime
4 : Shear break-up regime

Increasing Weber number

Images for the L0x / Dry air couple

P = 0,1 MPa, DR = 1200, We = 48, Re = 1800

Time between two images= 0,5 ms

Flow

Images for the LOx / Helium couple

P = 2 MPa, DR = 350, We = 19, Re = 1350

Time between two images = 0,5 ms

Flow

103

# (P, We) and (P, Re) maps of the droplet deformation and break-up regimes

LOx / Helium couple

Legend:
- ★ Shear Breakup
- ■ Transitional Breakup
- ● Bag Breakup
- ◆ No Breakup

Upper plot: Reynolds number, Re (vertical axis, 0 to 4000) vs Pressure (MPa) (horizontal axis, 0 to 8)

Lower plot: Weber number, We (vertical axis, 0 to 200) vs Pressure (MPa) (horizontal axis, 0 to 8)

New correlation for the regime transitions

105

Normalised break-up initiation time

- Break-up initiation time measurements with images processing.

- Normalisation by the characteristic time $T = (D/U)(\rho_l/\rho_g)^{1/2}$.

Legend:
- ◆ P = 0,2 MPa
- ✚ P = 0,5 MPa
- ▶ P = 1 MPa
- ■ P = 2 MPa
- ◀ P = 3 MPa
- ● P = 4 MPa
- ▼ P = 5 MPa
- ✕ P = 6 MPa
- ▲ P = 7 MPa
- ⊞ P = 8 MPa
- —— $T_{bu} = 0{,}75\, We^{-0.06}$

Normalised break-up initiation time

Weber number, We

Normalised break-up duration

Weber number, We

Normalised break-up duration

P = 0,2 MPa
P = 0,5 MPa
P = 1 MPa
P = 2 MPa
P = 3 MPa
P = 4 MPa
P = 5 MPa
P = 6 MPa
P = 7 MPa
P = 8 MPa
$D_{bu} = 0,3\ We^{0,5}$

**Nombre et taille des gouttes secondaires :**

- difficile à déterminer expérimentalement
- résultats des différents auteurs peu concordants

Quelques résultats au L.C.S.R., mais plage de paramètres restreinte

→ pas de corrélation, mais tabulation et interpolation possible

oxygène liquide / hélium (P = 0,5 MPa ; We = 137 ; Re = 2570 ; D₀ = 1,89 mm)

oxygène liquide / hélium (P = 0,5 MPa ; We = 78 ; Re = 1940 ; D₀ = 1,90 mm)

Conclusions (1)

- An experimental system has been developed to investigate droplet-jet interaction regimes under various velocity and pressure conditions.

- About the atomisation regimes, the Weber number seems to be the relevant parameter for their apparitions.

- The transitions between different regimes are correctly predicted by correlation based on density and viscosity ratio.

Conclusions (2)

- For the normalised break-up initiation time, a law based on Weber number and density ratio is underlined.

- For the normalised break-up total time, its evolution follows a law We ^{0,25}.

- The normalised break-up duration increases with We ^{0,5}.

110

Financial support

Centre National de la Recherche Scientifique (CNRS)

Centre National d'Etudes Spatiales (CNES)

SEP (Snecma Division)

French Research Group 'Combustion in the Rocket Engines'

Modeling of Supercritical Droplet and Spray Combustion

Vigor Yang

Propulsion Engineering Research Center

The Pennsylvania State University

University Park, Pennsylvania 16802, U.S.A.

phone: (814) 863-1502 fax: (814) 865-3389

email: vigor@psu.edu

Acknowledgment

- Air Force Office of Scientific Research
- NASA Marshall Space Flight Center
- Penn State Propulsion Engineering Research Center

Collaboration

- Air Force Research Laboratory
- NASA Lewis (Glenn) Research Center
- l'Office National d'Etudes et de Recherches Aérospatiales

- thermodynamics
- transport phenomena
- droplet vaporization, combustion, and dynamics
- spray combustion
- mixing and flame holding/spreading

ADVANCED AIRBREATHING AND ROCKET ENGINES

Subcritical Droplet Vaporization

Supercritical Droplet Gasification

T_c

- Transient Diffusion
- Thermodynamic Non-ideality
- Property Variation
- Ambient Gas Solubility

SUPERCRITICAL DROPLET COMBUSTION AND DYNAMICS

- Property evaluation techniques and constitutive relations

- Droplet vaporization, combustion, and dynamics in convective environments

- Dynamic responses of droplet vaporization and combustion to ambient flow oscillations

Thermophysical Properties and Constitutive Relations

- Equations of state (p-v-T)

- Thermodynamic properties (e, h, s)

- Transport properties (μ, λ, D)

EQUATIONS OF STATE

- ## Soave-Redlich-Kwong (SRK)

$$p = \frac{RT}{v-b} - \frac{a}{v(v+b)}$$

- ## Peng-Rubinson (PR)

$$p = \frac{RT}{v-b} - \frac{a}{v(v+b)+b(v-b)}$$

- ## Benedict-Webb-Rubin (BWR)

$$p = \sum_{n=1}^{9} a_n \rho^n + \sum_{n=10}^{15} a_n \rho^{2n-17} e^{-\gamma \rho^2}$$

Evaluation of Thermodynamic Properties

- sensible enthalpy : $h(\rho,T) = h^0(T) + \Delta h_{exc}(\rho,T)$

- internal energy : $u(\rho, T) = u^0(T) + \Delta u_{exc}(\rho, T)$

- specific heat : $C_p(\rho, T) = C_p^0(T) + \Delta C_{p_{exc}}(\rho, T)$

where

$h^0(T), u^0(T), C_p^0(T) = $ values in dilute $-$ gas limit

$\Delta h_{exc}, \Delta u_{exc}, \Delta C_{p_{exc}} = $ dense fluid corrections

Pressure-explicit type of EOS:

$$\Delta h_{exc} = \int_0^\rho \left[\frac{p}{\rho^2} - \frac{T}{\rho^2}\left(\frac{\partial p}{\partial T}\right)_\rho \right] d\rho + RT(Z - 1)$$

$$\Delta u_{exc} = \int_0^\rho \left[\frac{p}{\rho^2} - \frac{T}{\rho^2}\left(\frac{\partial p}{\partial T}\right)_\rho \right] d\rho$$

$$\Delta C_{p_{exc}} = -T\int_0^\rho \frac{1}{\rho^2}\left(\frac{\partial^2 p}{\partial T^2}\right) d\rho + \frac{T(\partial p / \partial T)_\rho^2}{\rho^2(\partial p / \partial \rho)_T} - R$$

Transport Properties of a Pure Substance

$$\lambda(\rho,T) = \lambda_0(T) + \Delta\lambda_{exc}(\rho,T) + \Delta\lambda_{crit}(\rho,T)$$

where λ_0 =   dilute gas limit

$\Delta\lambda_{exc}$ =   dense fluid correction

$\Delta\lambda_{crit}$ =   critical enhancement

THERMAL CONDUCTIVITY OF OXYGEN

SPECIFIC HEAT OF OXYGEN

# Correlation of Properties in terms of Density and Temperature

$$\lambda(\rho,T) = \lambda_0(T) + \Delta\lambda_{exc}(\rho,T) + \Delta\lambda_{crit}(\rho,T)$$

where λ_0 = dilute gas limit

$\Delta\lambda_{exc}$ = dense fluid correction

$\Delta\lambda_{crit}$ = critical enhancement

Critical Enhancement of Transport Properties

- Critical Region Proper : $|\Delta T^*| \leq 0.03,\quad |\Delta\rho^*| \leq 0.25$

$$\Delta T^* = (T - T_c)/T_c \quad\text{and}\quad \Delta\rho^* = (\rho - \rho_c)/\rho_c$$

- Extended Critical Region


- Critical Enhancement of Thermal Conductivity

PROPERTY EVALUATION FOR MIXTURES

- Extended Corresponding-State Principle

    - Density based scheme
      $$\eta_x(\rho,T) = \eta_0(\rho_0,T_0)F_\eta$$

    - BWR EOS for density at given pressure and temperature

    - Mapping function determined by
      - critical properties
      - Pitzer's acentric factor

    - Reference fluids based on methane or propane

Mass Diffusivity for Multicomponent Mixture

- Determine Binary Mass Diffusivity

    — Chapman-Enskog theory with Lennard-Jones
      intermolecular potential energy function

    — Corrected by the corresponding state approach
   of Takahashi

- Apply the mixing rule

$$D_{im} = (1 - X_i) / \sum_{\substack{j \neq i}}^{N} (X_j D_{ij}) , \quad i=1,.....N$$

Droplet Vaporization and Combustion in Quiescent Environments

- **Liquid Oxygen (LOX) Droplet Vaporization in Gaseous Hydrogen**

  $5 < P_\infty < 300$ atm
  $500 < T_\infty < 2500$ K
  $50 < D_0 < 300$ μm

- **Hydrocarbon Droplet Vaporization and Combustion in Air**

  $5 < P_\infty < 200$ atm
  $300 < T_\infty < 2500$ K
  $100 < D_0 < 1000$ μm

- **Unsymmetrical Dimethylhydrazine (UDMH) Droplet Vaporization and Decomposition Combustion**

  $1 < P_\infty < 180$ atm

THEORETICAL FORMULATION

- Complete Time-Dependent Conservation Equations for Both Gas and Liquid Phases

  - --- mass
  - --- momentum
  - --- energy
  - --- species concentration

- Finite-Rate Chemical Kinetics for Gas-Phase Reaction

- Matching of Droplet Behavior with Ambient Gases

  - --- Continuities of mass and energy
  - --- Phase equilibrium

VAPORIZATION OF LOX DROPLET IN
HYDROGEN FOR PRESSURES OF 5 - 250 atm

LOX
Droplet

r

R(t)

Hydrogen

P_∞ = 5 - 250 atm

T_∞ = 500 - 1500 K

T_l = 90 K

D_0 = 50 - 300 μm

CRITICAL PROPERTIES OF OXYGEN AND HYDROGEN

	T_c (K)	P_c (atm)	v_c (cm^3/g)	Z_c
OXYGEN	154.6	49.74	2.294	0.288
HYDROGEN	33.2	12.96	32.292	0.306

Time History of Droplet Surface Temperature

O$_2$ / H$_2$ System

- 100
- 50
- 200
- 300
- p = 10 atm

D$_0$ = 100 μm
T$_0$ = 90 K, T$_\infty$ = 1000 K

● Critical Mixing Point

Surface Temperature, K

Time, ms

Distribution of Mixture Specific Heat

O$_2$ / H$_2$ System

Time, ms
——— 1.0
- - - - 2.0
-·-·-· 3.0

D$_0$ = 100 μm
T$_0$ = 90 K
T$_\infty$ = 1000 K
p = 100 atm

Specific Heat C$_p$, kJ/kg/K

Reduced Radial Distance, r / R$_0$

Effect of Pressure on Droplet Lifetime

$500 < T_\infty < 2000\,K,\ 5 < p_\infty < 300\,atm$

- Enthalpy of vaporization decreases with pressure
  $\Rightarrow$ Enhancement of vaporization in subcritical regime

- Critical mixing temperature decreases with pressure
  + Gaseous thermal conductivity increases with pressure
  $\Rightarrow$ Enhancement of vaporization in supercritical regime

Correlation of Droplet Lifetime

- Processes dominated by thermal diffusion in supercritical regime

- Simplified analysis based on thermal diffusion equation in terms of

  - thermal diffusivity α
  - initial droplet radius squared R_0^2
  - transfer number $(T_\infty - T_c) / (T_\infty - T_o)$

- Correlation of reduced droplet lifetime

$$\tau \frac{\alpha_o^l}{R_o^2} = \left[0.0115 + 0.542 \left(1 - \frac{T_\infty - T_c}{T_\infty - T_o} \right) \right] f \left(\frac{\alpha_\infty}{\alpha_o^l} \right)$$

where $f \left(\dfrac{\alpha_\infty}{\alpha_o^l} \right) = 1 + 3.9 \left[1 - \exp \left(-0.035 \left(\dfrac{\alpha_\infty}{\alpha_o^l} - 1 \right) \right) \right]$

Effect of Thermal Diffusion on Droplet Lifetime
## (Critical Mixing Temperature)

Effect of Thermal Diffusion on Droplet Lifetime
(Critical Mixing Composition)

Species Composition in LOX/H$_2$/H$_2$O System

Temperature Distribution in LOX/H$_2$/H$_2$O System

# Effect of Pressure on Droplet Lifetime
(LOX/H_2/H_2O System)

Correlation of Droplet Lifetime
(LOX/H_2/H_2O System)

Effect of Pressure on Droplet Lifetime

$$400 < T_\infty < 2500\,K,\ 5 < p_\infty < 300\,atm$$

Subcritical Regime

- Low ambient temperature
  Molecular diffusion decreases with pressure
  $\Rightarrow$ Nitrogen composition decreases at the interface
  $\Rightarrow$ Surface temperature increases
  $\Rightarrow$ Temperature gradient decreases at the surface
  $\Rightarrow$ Droplet lifetime increases with pressure

- High ambient temperature
  Enthalpy of vaporization decreases with pressure
  $\Rightarrow$ Enhancement of vaporization with pressure

Supercritical Regime

- Mixture critical temperature decreases with pressure
  + Gaseous thermal conductivity increases with pressure
  $\Rightarrow$ Enhancement of vaporization in supercritical regime

Correlation of Droplet Lifetime

- High ambient temperature, $T_\infty > 1000\,K$
- Various initial droplet temperatures, $T_o = 300, 325, 350\,K$
- Reduced droplet lifetime correlated with pressure

$$\tau_r = \frac{\tau}{\tau_{p_{ref}=5\,atm}} = \exp\left[-a\left(p - p_{ref}\right) / p_{ref}\right]$$

where
    $a = 0.0161$ for n-heptane/air system
    $a = 0.01$ for n-decane/air system
- Average deviation < 2 %

Effect of Pressure on Vaporization Rate of UDMH Droplet

COMBUSTION OF n-PENTANE FUEL DROPLETS IN AIR FOR PRESSURES OF 5-140 atm

FLAME ZONE

FUEL →

← OXYGEN

$T_l = 300k$
$T_\infty = 1000k$
$D_o = 100\mu m$

CRITICAL PROPERTIES OF CONSTITUENT SPECIES

	n-C_5H_{12}	N_2	O_2	CO_2	H_2O
Critical Temp.(k)	469.6	126.2	154.6	304.2	647.3
Critical Pressure (atm)	33.3	33.5	49.8	72.8	217.6

Time-Variations of Droplet Surface Temperature

Time-Variations of Latent Heat of Vaporization

Effect of Pressure on Peak Flame Temperature

- Thermal diffusivity decreases almost linearly with pressure,

$$\alpha \sim \frac{1}{P} \quad \Rightarrow \quad \text{less heat transfer from the flame zone.}$$

- Mass diffusivity decreases relatively fast with pressure,

$$D < \frac{1}{P} \quad \Rightarrow \quad \text{much less fuel supply to the flame zone.}$$

- Lewis number increases with pressure,

$$Le \equiv \frac{\alpha}{D} \uparrow \quad \text{as} \quad P \uparrow$$

MILESTONE TIMES WITH DROPLET BURNING MECHANISMS

- **D_O = 100 μm**

- **D_O = 1000 μm**

--- At low pressures, gasification dominates.
--- At high pressures, transient gas-phase diffusion dominates.

DYNAMIC RESPONSES OF DROPLET VAPORIZATION AND COMBUSTION

TO AMBIENT FLOW OSCILLATIONS

- Pressure-Coupled Response

- Velocity-Coupled Response

Droplet Vaporization Response

$$R_p = \frac{\left[\left(-\dfrac{dM}{dt}\right)_{inst.} - \left(-\dfrac{dM}{dt}\right)_{s.s.}\right] \Big/ \left(-\dfrac{dM}{dt}\right)_{s.s.}}{(p'/\bar{p})}$$

P'
u'

- - - - - - - $\bar{P}'/\bar{P}$
———— $\bar{M}'/\bar{M}$

$\bar{P} = 50\ atm$ $P'=0.05\bar{P}$

TIME (msec)

frequency = 3000 Hz
• critical mixing point

P = 80 atm

50

20

$\dfrac{\dot{M}'/\bar{M}}{P'/\bar{P}}$

10

TIME (msec)

145

Magnitude of Droplet Vaporization Response

Phase Angle of Droplet Vaporization Response

Abnormal Variations of Thermophysical Properties at Critical Point Cause Sharp Amplication of Droplet Vaporization Response

$P = 80$ atm

--- pressure fluctuation, P'
— vaporization fluctuation, M'

● critical mixing point

Time (msec)

C_5H_{12} Droplet

R(t)

Air

r

$P_\infty = 10 - 80$ atm
$T_\infty = 1500$ K
$T_l = 300$ K
$D_0 = 100, 300$ μm

P'

● critical enhancement of thermal conductivity, $\Delta\lambda_{crit}$

Oxygen

$T = 160$ K
180
200
240
280

$\Delta\lambda_{crit}$, W/(m·K)

Density, g/cm³

● enthalpy of vaporization

N-PENTANE/NITROGEN SYSTEM

P=88 atm
P=80
P=72

B
A
C

Enthalpy of Vaporization (KJ/KG)

Temperature, K

147

Supercritical Droplet Vaporization in Convective Environments

THEORETICAL FORMULATION

- complete time-dependent conservation equations for the entire field
  - mass
  - momentum
  - energy
  - species concentration

- thermodynamic nonideality
  - interfacial thermodynamics
  - dense-fluid phenomena

- transient diffusion

- property variation

- finite-rate chemical kinetics

149

SUPERCRITICAL DROPLET GASIFICATION IN CONVECTIVE ENVIRONMENTS

- Droplet Gasification
- Momentum Transfer
- Droplet Dynamics

Key Parameters

- Reynolds number, $Re = \rho_\infty U_\infty D / \mu_\infty$
- Transfer number, $B = (Y_{FC} - Y_{F\infty})/(1 - Y_{FC})$
- Lewis number, $Le = \alpha/D$
- Ambient density, ρ_∞, (or ambient pressure)

LOX DROPLET VAPORIZATION IN SUPERCRITICAL HYDROGEN

- Temperature
- O₂ Concentration

LOX DROPLET VAPORIZATION IN SUPERCRITICAL HYDROGEN

- Temperature
- O_2 Concentration

LOX DROPLET VAPORIZATION IN SUPERCRITICAL HYDROGEN

- Temperature
- O_2 Concentration

153

FOUR DIFFERENT MODES OF DROPLET EVOLUTION

deformation(100 atm, 1.5 m/s ;t=610 μs)

breakup(100 atm, 15 m/s; t=170 μs)

spherical(100 atm, 0.2 m/s; t=610 μs)

stripping(100 atm, 5 m/s; t=170 μs)

Evolution of Critical Surface

LOX/H₂ System

p = 100 atm, U∞ = 2.5 m/s

t=0 μs   244 μs   389 μs   549 μs   604 μs   747 μs   918 μs   1488 μs

p = 100 atm, U∞ = 5 m/s

t=0 μs   110 μs   164 μs   189 μs   346 μs   417 μs   465 μs   633 μs

p = 100 atm, U∞ = 15 m/s

t=0 μs   49 μs   80 μs   110 μs   128 μs   146 μs   158 μs   170 μs

——— Critical Mixing Temperature   ----- Critical Mixing Composition

155

Evolution of Critical Surface

LOX/H$_2$ System

p = 100 atm, U$_\infty$ = 2.5 m/s

| t=0 µs | 244 µs | 389 µs | 549 µs | 604 µs | 747 µs | 918 µs | 1488 µs |

p = 200 atm, U$_\infty$ = 2.5 m/s

| t=0 µs | 228 µs | 342 µs | 457 µs | 550 µs | 642 µs | 688 µs | 1289 µs |

p = 400 atm, U$_\infty$ = 2.5 m/s

| t=0 µs | 120 µs | 186 µs | 249 µs | 326 µs | 419 µs | 485 µs | 777 µs |

——— Critical Mixing Temperature   - - - - -   Critical Mixing Composition

Supercritical LOX Droplet Vaporization in Convective Environments

LOX/H$_2$ System

p = 100 atm, U$_\infty$ = 2.5 m/s

t=0 μs   244 μs   389 μs   549 μs   604 μs   747 μs   918 μs   1488 μs

p = 100 atm, U$_\infty$ = 5 m/s

t=0 μs   110 μs   164 μs   189 μs   346 μs   417 μs   465 μs   633 μs

p = 100 atm, U$_\infty$ = 15 m/s

t=0 μs   49 μs   80 μs   110 μs   128 μs   146 μs   158 μs   170 μs

—— Critical Mixing Temperature   - - - - Critical Mixing Composition

Effects of Pressure and Velocity on Droplet Lifetime

- Atmospherical Conditions
  - Ranz and Marshall's correlation

$$\frac{\tau_f}{\tau_{f,\,Re=0}} \propto \frac{h_{Re=0}}{h} = \frac{1}{1+0.3Re^{1/2}Pr^{1/3}}$$

- Supercritical Conditions
  - LOX/hydrogen system

$$\frac{\tau_f}{\tau_{f,\,Re=0}} = \frac{1}{1+0.165634\,Re^{1.1}\,(p_{r,\,O_2})^{-0.88}}$$

LOX/H$_2$ System

p = 100 atm
200
400

$\dfrac{\tau}{\tau_{Re=0}}$

$1/(1+0.09*Re^{1.1}*(p/p_{ref})^{-0.88})$

LOX/H$_2$ System

p = 100 atm
200 atm
400 atm

τ_{life}, ms

Convective Velocity, m/s

- Effect of Ambient Pressure on
  - thermophysical properties
  - critical mixing state
  - convective heat transfer

- Effect of Ambient Velocity on
  - convective heat transfer

158

Droplet Drag Coefficient

- Hard Sphere (Putnum, 1963)

$$C_D^0 = \frac{24}{Re}[1+\frac{1}{6}Re^{2/3}]$$

- Subcritical Droplet Vaporization
  - Chiang et al. (1992)

$$C_D = \frac{C_D^0}{[1+B]^{0.2}} \quad with \quad B = \frac{C_p(T_\infty - T_s)}{\Delta h_v}$$

- Supercritical Droplet Vaporization
  - equivalent sphere model

$$C_D = \frac{C_D^0}{(1+aB_T)^b} \quad with \quad B_T = \left(\frac{T_\infty - T_s}{T_s - T_l}\right)$$

$$a = 0.05 \; ; \; b = 1.592(p_{r,O_2})^{-0.7}$$

- correction for droplet deformation

$$C_D = \frac{C_D^0 Re^{0.2}}{(1+aB_T)^b}$$

LOX/hydrogen system

Supercritical Droplet Combustion in Convective Environments

H_2-O_2 REACTION MECHANISMS

Eight Species Involved : H_2, O_2, H_2O, OH, O, H, HO_2, and H_2O_2

- ## Initiation Reaction

  $H_2 + M \rightarrow H + H + M$

  $H_2 + O_2 \rightarrow HO_2 + H$

- ## Chain Reaction Involving O, H, and OH

  $H + O_2 \rightarrow O + OH$

  $O + H_2 \rightarrow H + OH$

  $H_2 + OH \rightarrow H_2O + H$

  $O + H_2O \rightarrow OH + OH$

- ## Chain Termination Involving O, H, and OH

  $H + H + M \rightarrow H_2 + M$

  $O + O + M \rightarrow O_2 + M$

  $H + O + M \rightarrow OH + M$

  $H + OH + M \rightarrow H_2O + M$

- ## Reaction Involving HO_2

  $H + O_2 + M \rightarrow HO_2 + M$

  $HO_2 + H \rightarrow OH + OH$

  $HO_2 + H \rightarrow H_2O + O$

  $HO_2 + O \rightarrow O_2 + OH$

  $HO_2 + HO_2 \rightarrow H_2O_2 + O_2$

  $HO_2 + H_2 \rightarrow H_2O_2 + H$

- ## Reaction Involving H_2O_2

  $H_2O_2 + OH \rightarrow H_2O + HO_2$

  $H_2O_2 + H \rightarrow H_2O + OH$

  $H_2O_2 + H \rightarrow HO_2 + H_2$

  $H_2O_2 + M \rightarrow OH + OH + M$

LIMITING EXTREMES: 1) INERTIAL PROCESSES DOMINATE

- "Low" Heating Rates

  - dynamic forces and surface tension promote atomization and secondary break-up processes

  - heterogeneous spray field evolves continuously over wide range of thermodynamic regimes

  - spray flame surrounds oxygen jet with droplets burning in a variety of group combustion modes

LIQUID CORE

DENSE SPRAY

DILUTE SPRAY

FLAME FRONT

RECIRCULATION ZONES

H_2

O_2

H_2

LIMITING EXTREMES: 2) DIFFUSION PROCESSES DOMINATE

- "High" Heating Rates

  - diminished intermolecular forces promote diffusion processes prior to atomization

  - injected jet vaporizes forming continous fluid in presence of exceedingly large interfacial gradients

  - diffusion flame resides within annular post wake separating oxygen jet from outer hydrogen flow

DENSE FLUID CORE

GAS POCKETS

FLAME FRONT

RECIRCULATION ZONES

H_2 O_2 H_2

163

FILTERED CONSERVATION EQUATIONS

Mass:

$$\frac{\partial}{\partial t}(\theta\bar{\rho}) + \nabla \cdot (\theta\bar{\rho}\tilde{\mathbf{u}}) = \dot{\rho}_s$$

Momentum:

$$\frac{\partial}{\partial t}(\theta\bar{\rho}\tilde{\mathbf{u}}) + \nabla \cdot [\theta(\bar{\rho}\tilde{\mathbf{u}}\tilde{\mathbf{u}} + \bar{p}\mathbf{I})] = \nabla \cdot (\theta\bar{\tau}) - \nabla \cdot (\theta\mathbf{T}) + \dot{\mathbf{F}}_s$$

Energy:

$$\frac{\partial}{\partial t}(\theta\bar{\rho}\tilde{e}_t) + \nabla \cdot [\theta(\bar{\rho}\tilde{e}_t + \bar{p})\tilde{\mathbf{u}}] = \nabla \cdot (\theta\overline{\mathbf{q}_e}) + \nabla \cdot (\theta\bar{\tau} \cdot \tilde{\mathbf{u}})$$
$$- \nabla \cdot (\theta\mathbf{Q}) - \nabla \cdot (\theta\mathbf{T} \cdot \tilde{\mathbf{u}})$$
$$- \nabla \cdot \left[\theta\frac{1}{2}tr(\mathbf{T}\overline{\mathbf{u}''})\right] + \nabla \cdot \left[\theta(\overline{\tau \cdot \mathbf{u}''})\right] + \dot{Q}_s$$

Species:

$$\frac{\partial}{\partial t}(\theta\bar{\rho}\tilde{Y}_i) + \nabla \cdot (\theta\bar{\rho}\tilde{Y}_i\tilde{\mathbf{u}}) = \nabla \cdot (\theta\overline{\mathbf{q}_i}) - \nabla \cdot (\theta S_i) + \theta\bar{\omega}_i + \dot{\omega}_{s,i} \qquad i = 1,\ldots,N$$

164

CLOSURE REQUIREMENTS

Thermodynamic and Transport Properties:
$$Z, \; C_p, \; \mu, \; \lambda, \; \mathcal{D}_{im}$$

Subgrid-Scale Turbulence Interactions:
$$\mathbf{T}, \; \mathbf{Q}, \; S_i$$

Subgrid-Scale Particulate Interactions:
$$\theta, \; \dot{\rho}_s, \; \dot{\mathbf{F}}_s, \; \dot{Q}_s, \; \dot{\omega}_{s,i}$$

Chemical Kinetics:
$$\bar{\dot{\omega}}_i$$

EXTENDED CORRESPONDING STATES PRINCIPLE

● Expresses generalization that equilibrium properties which depend on intermolecular forces are related to critical properties in universal manner

● Basic assumptions:

1) Configurational properties of mixture can be equated to those of a hypothetical pure fluid

$$\eta_m(\rho, T, X_1, \ldots, X_N) = \eta_x(\rho, T)$$

2) Properties of the hypothetical fluid obey classical two parameter corresponding states formalism

$$\eta_x(\rho, T) = \eta_o F_\eta(W_o, W_x, \hbar_x, f_x)$$

3) Reference fluid density and temperature obey extended equilibrium corresponding states principle

$$\rho_o = \rho \hbar_x \qquad T_o = T / f_x$$

HIGH-PRESSURE SPRAY FIELD DYNAMICS

$U_1 = 200$ m/s $(M_1 = 0.084)$

$\delta_o = 1$ mm

$u(y)$

$U_2 = 50$ m/s $(M_2 = 0.021)$

$T_{H_2} = 1000$ K
$T_{O_2} = 100$ K

δ

50 mm

200 mm

GRID DISTRIBUTION

120x75

BASELINE FLOW CHARACTERISTICS

Pressure, $-0.2336 \leq (p-p_{ref})/p_{ref} \leq 0.1415\%$, $\Delta = 0.02\%$

Vorticity, $0 \leq \omega/\omega_{ref} \leq 100\%$, $\Delta = 10\%$, $\omega_{ref} = -74 \times 30^3\ s^{-1}$

BASELINE FLOW CHARACTERISTICS

u-Velocity, -20 ≤ u ≤ 250 m/s, Δ = 10 m/s

v-Velocity, -75 ≤ v ≤ 75 m/s, Δ = 10 m/s

Velocity Vectors

BASELINE FLOW CHARACTERISTICS

Viscosity Ratio

$p = 1$ atm, $0 \leq \nu_t/\nu_l \leq 0.2704$

$p = 100$ atm, $0 \leq \nu_t/\nu_l \leq 37.80$, $\Delta = 5$

$p = 400$ atm, $0 \leq \nu_t/\nu_l \leq 156.3$, $\Delta = 5$

1 atm, O/F = 4

Spray Distribution, 2576 Parcels, 6.3×10^4 Particles

Mass Fraction, $0.8132 \leq Y_{H2} \leq 1$, $\Delta = 0.05$

Viscosity Ratio, $0 \leq \nu_t/\nu_l \leq 0.2947$

Vorticity, $0 \leq \omega/\omega_{ref} \leq 100\%$, $\Delta = 10\%$, $\omega_{ref} = -74 \times 10^3 \text{ s}^{-1}$

100 atm, O/F = 4

Spray Distribution, 2680 Parcels, 2.8×10^6 Particles

Mass Fraction, $0.4032 \leq Y_{H2} \leq 1$, $\Delta = 0.05$

Viscosity Ratio, $0 \leq \nu_t/\nu_l \leq 35.52$, $\Delta = 5$

Vorticity, $0 \leq \omega/\omega_{ref} \leq 100\%$, $\Delta = 10\%$, $\omega_{ref} = -74 \times 10^3 \ s^{-1}$

400 atm, O/F = 4

Spray Distribution, 1363 Parcels, 5.1×10^6 Particles

Mass Fraction, $0.2102 \leq Y_{H2} \leq 1$, $\Delta = 0.05$

Viscosity Ratio, $0 \leq \nu_t/\nu_l \leq 195.0$, $\Delta = 5$

Vorticity, $0 \leq \omega/\omega_{ref} \leq 100\%$, $\Delta = 10\%$, $\omega_{ref} = -74 \times 10^3 \text{ s}^{-1}$

1 atm

100 atm

SHEAR COAXIAL UNI-ELEMENT INJECTOR

Table 5: Inlet conditions employed for the analysis of high-pressure hydrogen-oxygen mixing and combustion processes. Subscript 1 denotes the hydrogen stream, subscript 2 denotes the oxygen stream.

|	1	2	3	4	5	6
p [atm]	100	100	100	100	100	100
T_1 [K]	150	150	150	300	300	300
T_2 [K]	100	100	100	300	300	300
T_2/T_1	0.6667	0.6667	0.6667	1	1	1
ρ_1 [kg/m^3]	15.37	15.37	15.37	7.752	7.752	7.752
ρ_2 [kg/m^3]	1118	1118	1118	134.7	134.7	134.7
ρ_2/ρ_1	72.75	72.75	72.75	17.37	17.37	17.37
U_1 [m/s]	500	250	125	250	125	62.5
U_2 [m/s]	30	30	30	30	30	30
U_2/U_1	0.06	0.12	0.24	0.12	0.24	0.48
$\rho_2 U_2/\rho_1 U_1$	4.365	8.730	17.46	2.084	4.169	8.338
$\rho_2 U_2^2/\rho_1 U_1^2$	0.2619	1.048	4.190	0.2501	1.001	4.002
M_1	0.4828	0.2414	0.1207	0.1786	0.08931	0.04465
M_2	0.04572	0.04572	0.04572	0.09203	0.09203	0.09203
Re_{δ_1}	1424000	715700	359400	243200	121900	60990
Re_{δ_2}	245000	245000	245000	201700	201700	201700
Pr_1	0.7842	0.7842	0.7842	0.6913	0.6913	0.6913
Pr_2	1.917	1.917	1.917	0.7832	0.7832	0.7832
Sc_1	1.560	1.560	1.560	1.365	1.365	1.365
Sc_2	89.09	89.09	89.09	0.2207	0.2207	0.2207
Le_1	1.964	1.964	1.964	1.975	1.975	1.975
Le_2	46.48	46.48	46.48	0.2817	0.2817	0.2817

$Re_\delta \equiv U_e \delta/\nu$ where U_e represents the edge velocity and δ the channel half width.

Figure 19: Contours of density, temperature, velocity, and vorticity in the near-field region of the splitter plate for inlet condition 3 in Table 5.

178

Figure 20: Contours of H_2, O_2, H_2O, and OH mass fraction in the near-field region of the splitter plate for inlet condition 3 in Table 5.

Figure 21: Contours of density, temperature, velocity, and vorticity in the near-field region of the splitter plate for inlet condition 5 in Table 5.

Figure 22: Contours of H_2, O_2, H_2O, and OH mass fraction in the near-field region of the splitter plate for inlet condition 5 in Table 5.

PLANAR COAXIAL TRI-ELEMENT ARRAY

Cryogenic Combustion Modelling

B. Barbeau, F. Lacas, G. Rymer and S. Candel

Labo EM2C du CNRS et de l'ECP, Grande Voie des Vignes,
F-92295 Châtenay Malabry, France

INTRODUCTION :

- Simulation conditions

- Numerical solver

- Combustion model

- Spray model

- Computational domain

- Results

Laboratoire E.M2.C.

NUMERICAL METHOD : KIVA3

General

- Finite volume (ALE), basic equations in integral form
- Structured mesh with hexaedric cells

Spray

- Statistical Eulerian Lagrangian method
- Vaporizing droplets, Turbulent movement
- No collision, No breakup

Combustion model

- Coherent Flame Model

Laboratoire E.M2.C.

CENTRALE

185

SPRAY MODEL : KIVA3 adapted models

- 1 droplet is representative of n droplets of identical size, velocity and temperature.

- Droplets turbulent movement : t_k characteristic turbulent correlation time, Δt timestep

- If $\frac{\Delta t}{t_k} < 1$ then $\mathbf{v_d} = \mathbf{v_d} + \mathbf{v_d}'$

- If $\frac{\Delta t}{t_k} > 1$ then $\mathbf{v_d} = \mathbf{v_d} + \mathbf{v_d}'$ and $\mathbf{x_d} = \mathbf{x_d} + \mathbf{x_d}'$

Laboratoire E.M2.C.

SPRAY MODEL : KIVA3 adapted models

- Vaporization law : Wet Bulb Temperature model

$$\dot{r} = \frac{-\rho D(\widetilde{T})}{2\rho_{Lox}r} B\mathrm{Sh_d}$$

- with $B = \dfrac{Y_{O_2}^* - \widetilde{Y}_{O_2}}{1 - Y_{O_2}^*}$

- and $\mathrm{Sh_d} = (2 + 0.6\mathrm{Re_d}^{0.5}\mathrm{Sc_d}^{1/3})\dfrac{\log(1+B)}{B}$

- $Y_{O_2}^*$ is the gaseous oxygen mass fraction at droplet surface.

Laboratoire E.M2.C.

COMBUSTION MODEL : Coherent Flame Model

Mean reaction rate $\overline{\dot{\omega}}_c$ is given by $\overline{\dot{\omega}}_c = -\bar{\rho} S_d \widetilde{\Sigma}$, where $\widetilde{\Sigma}$ is discribed by the following transport equation

$$\frac{\partial \widetilde{\Sigma}}{\partial t} + \nabla \cdot \widetilde{\mathbf{u}} \widetilde{\Sigma} = \nabla \cdot \frac{\nu_\Sigma}{\sigma_\Sigma} \nabla \widetilde{\Sigma} + \mathrm{E_S} \widetilde{\Sigma} - \beta \left(\frac{S_d}{\widetilde{Y}_{H_2}} + s \frac{S_d}{\widetilde{Y}_{O_2}} \right) \widetilde{\Sigma}^2$$

$\mathrm{E_S}$ is the turbulent strain rate

$$\mathrm{E_S} = \alpha \frac{\widetilde{\epsilon}}{\widetilde{k}} \text{ and } \Phi = s Y_{H_2^0} / Y_{O_2^0}$$

and S_d oxygen consumption velocity is given by

$$S_d = Y_{o\infty} \left(\frac{D \mathrm{E_S}}{2\pi} \right)^{1/2} \frac{\Phi + 1}{\Phi} \exp \left(\mathrm{erf}^{-1} \left(\left(\frac{\Phi - 1}{\Phi + 1} \right)^2 \right) \right)$$

Laboratoire E.M2.C.

COMPUTATIONAL DOMAIN : Configuration and mesh

Without recess

size : 2.5 × 9 cm

mesh : 13 × 45

Laboratoire E.M2.C.

COMPUTATIONAL DOMAIN : Configuration and mesh

With recess

size : 2.5×9 cm; recess = D_{LOx}

mesh : 13×45

Laboratoire E.M2.C.

SIMULATION CONDITIONS: general inflow conditions

And for all simulation points :

Species	Variable	Value
H_2	Temperature (K)	300
	Density (kg/m^3)	0.8
O_2	Temperature (K)	80
	Density (kg/m^3)	1170
	Pressure (bars)	10

Laboratoire E.M2.C.

CENTRALE

SIMULATION CONDITIONS : 4 different inflow conditions

General propellant inflow conditions (with and without recess)

Species	Variable	Point A	Point C
H_2	Velocity (m/s)	308	207
LOx	Velocity (m/s)	2.23	2.23
	$We.10^{-3}$	28.2	12.6
	$Re_{Lox}.10^{-3}$	67	67
	J	14.5	6.5

Laboratoire E.M2.C.

COMPARISON WITH EXPERIMENT : LIF/simulation

Without recess

- Locate flame's maximum expansion rate (x_d)

- Compare x_d with experimental trends of the flame

Laboratoire E.M2.C.

CENTRALE

COMPARISON WITH EXPERIMENT : LIF/simulation

Without recess

	x_d (comp)	x_d (exp)
Point A	4.6	1.0
Point C	6.6	3.0

Point A

Point C

Laboratoire E.M2.C.

Point A
Consumption rate (g.cm^{-3}.s^{-1})

Flame Surface Density

Temperature

CENTRALE

Point A
Water mass fraction

Oxygen mass fraction

Hydrogen mass fraction

Point A

Radial velocity (cm.s^{-1})

axial velocity (cm/s)

Point A without recess

Point C without recess

Point A with recess

Point C with recess

Résultats numériques : Taux de réaction.

Point A sans retrait

Point A avec retrait

Point C sans retrait

Point C avec retrait

Laboratoire E.M2.C.

CENTRAI F

RESULTS : Point A, without recess

- Droplets velocities
- Droplets positions

Droplets velocity (m/s), max=127.0061

Droplets radius (μ m)

Laboratoire E.M2.C.

COMPARISON WITH EXPERIMENT : PDA/simulation

Point A without recess

Sauter Diameter (microns)

Pt A X/d=16 R/d=0

Mean diameter=83

Sauter Diameter (microns)

Pt A X/d=4 R/d=0

Mean diameter=26

$x/d = 4$

Measured SMD : 59.9 μm

$x/d = 16$

Measured SMD : 102.8 μm

Laboratoire E.M2.C.

COMPARISON WITH EXPERIMENT : PDA/simulation

Point C without recess

Sauter Diameter (microns)

Pt C X/d=4 R/d=0

Mean diameter=42

Sauter diameter (microns)

Pdf(d)

$x/d = 4$

Measured SMD : 73.4 μm

Sauter Diameter (microns)

Pt C X/d=16 R/d=0

Mean diameter=105

Sauter diameter (microns)

Pdf(d)

$x/d = 16$

Measured SMD : 103.5 μm

Laboratoire E. M. C.

COMPARISON WITH EXPERIMENT : PDA/simulation

Point A without recess

$x/d = 4$
Mean Velocity $26.2 \ ms^{-1}$

$x/d = 16$
Mean Velocity $8.6 \ ms^{-1}$

Laboratoire E.M2.C.

CENTRALE

Point C without recess

Axial Velocity (m/s)

Pt C X/d=4 R/d=0.0

Mean velocity=9

Pdf(v)

Axial Velocity (m/s)

Axial Velocity (m/s)

Pt C X/d=16 R/d=0.0

Mean velocity=28

Pdf(v)

Axial Velocity (m/s)

$x/d = 4$

Mean Velocity $16.8\ ms^{-1}$

$x/d = 16$

Mean Velocity $8.3\ ms^{-1}$

Laboratoire E.M2.C.

DISCUSSION : reaction rate, spray

Good agreements :

- Flame shape

- Flame shape's dependence with momentum ratio

- Droplets sizes

Problems :

- Flame stabilization

- Atomization

Comparison Simulation/Experiment needs postprocessing of computation results

205

Laboratoire E.M2.C.

CENTRALE

Thin Film Dynamics

and the

Physics of Atomization

Dirk Meinköhn

Deutsches Zentrum für Luft- und Raumfahrt DLR

D-74239 Hardthausen

e-mail: dirk.meinkoehn@dlr.de

General Remarks

- liquid propellants: **combustion**

    - gasification

    - mixing processes

    - combustion: efficiency

    - motor operations: stability

- **spray states:** intermediate, important

- feedback loop:

atomization	spray combustion

- atomization problematics: no comprehensive model available

- atomization → hydrodynamic process

    - liquid membranes/ligaments: flow processes

    - liquid edges: formation/dynamics

    - droplet detachment: neck formation/pinching/rupture

- **asymptotic descriptions**

Atomization Processes

- forcing process:

    - nozzle flow $\rightarrow$ jet
    - air assist/electrostatic/ultrasonic/ ...
    - generation of liquid membranes/filaments

- decomposition of membranes/filaments

    - droplets/spray formation

- investigation: **applications oriented**/empirical approach

    - forcing process: technicalities/devices
    - spray properties: empirical
    - feed-back from downstream combustion: neglected

- investigation: **physics orientated**/predictive approach

    - liquid flow processes in membranes/filaments: 2-d/1-d
    - interaction with 3-d environment:
        * **formation/dynamics of liquid edges**
        * **criticality** ($\rightarrow$ static equilibrium of liquid edges)
        * **propagation of perturbations** in liquid membranes
        * **rupture/necking/pinching**
        * **feedback processes**

- **deductive approach $\rightarrow$ predictive approach**

147. **Kelvin-Helmholtz waves on a thin liquid sheet.** Water is ejected downward in the form of a thinning sheet from a fan-spray nozzle that is vibrated sinusoidally normal to the plane of the sheet at a frequency giving wave instability. A side view shows the initial exponential growth predicted by two-dimensional theory and the development of a complex wave form as the amplitude increases. The stream of drops along the axis at the bottom is seen in the plan view to result from collapse of the rims of the sheet. *Crapper, Dombrowski, Jepson & Pyott 1973*

droplet detachment: role of liquid edges

Daimler-Benz Aerospace

Raumfahrt-Infrastruktur

DLR

sep
société
européenne de propulsion

Third French-German Colloquium on

Research on Liquid Rocket Propulsion

example: formation of ⟶ • Kelvin - Helmholtz
a liquid edge   instability

Topics :

- Heat Transfer
- Diagnostics
- Modelling
- Atomisation

5-6 June 1997

Marseilles (France)

3-D Simulation of liquid-gas shear layer. S Zaleski & J.Li

Rapp. Final de Synthèse
1995, URA CNRS 22

prepared by the
CNES SEP DASA DLR joint programme group
organised by the CNRS (IRPHE) in partnership with
the Université de la Méditerrannée and the city of Marseilles

149. Breakup of a liquid sheet. Studies of drop formation in sprays show that the production of filaments generally constitutes an intermediate stage. Controlled filament formation should therefore provide a means of regulating the size of drops. One approach is to subject the nozzle to forced vibrations. This photograph shows a flat laminar sheet of water issuing from a fan-spray nozzle that is oscillated axially at resonant frequency. *Photograph by N. Dombrowski*

liquid edges and droplet detachment

M. Carvalho (1997 ICLASS - Florence)

$U_L = 4.3$ m/s

$U_L = 6.4$ m/s

$U_1 = U_2 = 20$ m/s

$U_1 = U_2 = 0$

$U_1 = U_2 = 20$ m/s

holes:
edge formation

213

Physical Characterization

- flow processes → **hydrodynamics**

  1. liquid membranes/filaments: deformation → propagation of pressure perturbations
  2. propagation of existing free edges
  3. rupture processes for membranes/filaments
  4. formation of free edges

- **long wave theory:**

  > reference wave length λ large → **reduction in dimensionality**

  ** 2-d membranes / 1-d filaments **

- characteristic dimensions: cm , sec , g

- characteristic variables

(relative) flow velocity	u	$[cm/sec]$
characteristic length	h	$[cm]$
density	ρ	$[g/cm^3]$
kinematic viscosity	ν	$[cm^2/sec]$
surface tension	σ	$[g/sec^2]$

- characteristic groups

  Reynolds $\quad Re = uh/\nu$

  Capillary $\quad Ca = u\rho\nu/\sigma$

  Weber $\quad We = \sigma/h\rho u^2 = \dfrac{1}{Re\,Ca}$

  Ohnesorge $\quad Oh = \nu\sqrt{\rho/\sigma h} = \dfrac{\sqrt{We}}{Re} = \sqrt{\dfrac{Ca}{Re}}$

  Bond $\quad Bo = \rho g h^2/\sigma$

Hydrodynamic Models

- Navier-Stokes equations $\rightarrow$ **continuum-theoretic**

$$\nabla \cdot \vec{\upsilon} = 0 \quad , \quad \rho = const$$

$$\partial_t \vec{\upsilon} + (\vec{\upsilon} \cdot \nabla)\vec{\upsilon} = \frac{1}{\rho}\nabla p + \nu(\nabla \cdot \nabla)\vec{\upsilon}$$

- **thin** liquid membranes/ligaments

$$p = \sigma \kappa$$

- 2 limit cases (no gravity):

case 1: | Weber-number hydrodynamics |

- no viscosity/no dissipation
- propagation/dynamics:
    * pressure perturbations
    * free edges

case 2: | Ohnesorge-number hydrodynamics |

- viscosity important/strong dissipation
- rupture processes:
    * continuum-theoretic asymptotics
    * needle's-eye-role of microphysics

Weber Number Hydrodynamics

- **static criticality**: drag force D = surface tension force T

$$D = \frac{1}{2}c_D \frac{\pi d_{crit}^2}{4} \rho_{air} u^2 = T = \pi \sigma d_{crit}$$

(hand-drawn diagram: $\Delta p = \frac{4}{d}$, with cylinder of diameter d, velocity u, angle α, forces D and T)

- typical estimate: **diameter of maximal drop** d_{max}

$$d_{max} \simeq d_{crit} = \frac{8\sigma}{\rho_{air} u^2} \frac{1}{c_D} = \left(\frac{8}{c_D} d_0\right) We \qquad \text{reference diameter } d_0$$

- **dynamics**: propagation of perturbations

$\gtrsim d$

antisymmetric wave

(hand-drawn wavy diagram with axes z, x)

- velocity $\vec{v} = \{u, v\} = -\nabla \Phi \quad \rightarrow \quad$ velocity potential Φ

- wave equation (Taylor):

$$\rho \partial_{tt}^2 \Phi = \sigma \partial_z \left(\partial_{xx}^2 \Phi\right)\Big|_{z=\pm d/2}$$

- antisymmetric waves:

$$u = a w_{as} \kappa \sinh(\kappa z) \cos(\kappa[x - w_{as}t])$$

$$v = a w_{as} \kappa \cosh(\kappa z) cos(\kappa[x - w_{as}t])$$

- wave speed $w_{as} \rightarrow$ **dispersion relation**

$$w_{as}^2 = \frac{2\sigma}{\rho d}\{(\kappa d/2) \coth(\kappa d/2)\}$$

- case $\kappa d \ll 1$: $\quad w_{as}^2 = \frac{2\sigma}{\rho d} \quad \rightarrow$ **long wave approx.: nondispersive**

Geometric Acoustics: Rays

- antisymmetric waves: nondispersive $\rightarrow$ hyperbolic

- stationary perturbations: influence spreading along rays (compare: Mach lines)

$$\boxed{sin^2(\alpha) = w_{as}^2/u^2 = \frac{2\sigma}{\rho du^2} = We}$$

- example (Taylor): impinging jet $\rightarrow$ radially expanding free sheet

-2.0 < X < 2.0
-2.0 < Y < 2.0
Z = 0.00

- solution method: ray tracing $\rightarrow$ **eikonal method**

$$\boxed{sin^2(\alpha) = \frac{2\sigma}{\rho du^2} = \frac{4\pi\sigma}{\rho Qu} r = r/R}$$

$$\longrightarrow \quad We = r/R$$

parameter $R = \frac{\rho Q u}{4\pi\sigma}$

kinematic mass flux $Q = 2\pi r du = const$

flow velocity $u = const$

Liquid Sheets: Edge Dynamics

- edge retraction

$$\Delta p = \frac{2}{h}\sigma = \cdot$$

cylindrical edge

- cylindrical edge:

    - retraction velocity $= v$

    - tension force (per unit length of edge):
    $$T = \int_0^\pi (h/2)\,\mathrm{d}\alpha\; 2\sigma/h)\sin(\alpha) = 2\sigma$$

    - mass (per unit length of edge): $\mathrm{d}M = \rho h \mathrm{d}x \;\rightarrow\; M = \rho h x$

- edge dynamics: $T = 2\sigma = \frac{d}{dt}\left(M\frac{dx}{dt}\right) = (\rho h/2)\frac{d^2 x^2}{dt^2}$

- solution: $x/\tau \equiv v = \sqrt{\dfrac{2\sigma}{\rho h}} = w_{as}$

- stationary edge $\nrightarrow$ **geometric acoustics**

$$\boxed{\text{liquid edge} = \text{acoustic ray}} \quad \rightarrow \quad \boxed{\sin^2(\alpha) = v^2/u^2 = w_{as}^2/u^2 = We}$$

- **conclusion:**

    1. importance of Weber number for edge dynamics

    2. analogy Weber number with Mach number (gas dynamics)

    3. ray tracing, method of characteristics

Droplet Detachment: Necking/Pinching Phenomenon

- acoustic theory: inertia, surface tension, no viscosity

  characteristic time: $\boxed{t_{ref} = h^3 \rho / \sigma \ll 1}$

- droplet separation: necking/pinching

  - large curvature $\kappa \sim 1/h$, large surface tension forces
  - well-posedness: dissipation/viscosity necessary
  - Ohnesorge hydrodynamics

- modelling: full Navier-Stokes + continuity $\rightarrow$

  $\boxed{\textbf{inertia + surface tension + viscosity}}$

  viscous time scale: $\boxed{t_{vis} = h^2/\nu}$

- (Keller/Miksis 1983, Eggers/Dupont 1994) pinching $\rightarrow$
  asymptotic phenomenon

  - long wave approximation
  - large neck curvature $\rightarrow$ boundary values negligible $\rightarrow$ **self-similar solution**
  - new scales for length and time: surface tension as well as viscosity

$$
\begin{aligned}
\ell_{neck} &= \nu^2 \rho / \sigma = h \, Oh^2 \\
t_{neck} &= \nu^3 \rho^2 / \sigma^2 = \frac{h^2}{\nu} Oh^4 = t_{vis} Oh^4 \\
Oh^2 &= \frac{\nu^2 \rho}{h \sigma}
\end{aligned}
$$

1   2   3   4   5   6

7   8   9   10   11   12

13   14   15   16   17   18

19   20   21   22   23   24

Fig.7 from :
M. Rein , JFM 306 (1996) 145

$t = -6.7\mu s$

$t = -4.0\mu s$

$t = -1.3\mu s$

$t = 1.3\mu s$

$t = 4.0\mu s$

$t = 73\mu s$

Fig. 3. Separation of the droplet from the liquid jet of radius $r_j = 98.5$ μm. Time is given relative to the moment of the jet breakup. Liquid medium of relatively low viscosity (MIXD). The width of one frame corresponds to 1 mm

FIGURE 2. Simulation of a drop of water suspended from a circular orifice of radius $r_0 = 0.26$ cm. This gives parameter values $l_c/r_0 = 0.992$ and $l_v/r_0 = 4.89 \times 10^{-6}$. compare table 1. The time distance between profiles is $0.4(r_0^3 \rho/\gamma)^{\frac{1}{2}}$. starting from a point where the drop is already falling. We also superimpose a profile at the snap-off and the corresponding experimental picture from Peregrine *et al.* (1990). There is no adjustable parameter in the comparison. To enhance contrast, we erased the background in the original photograph.

Conclusions

- physics of atomization:
    - deformation processes/instability of liquid membranes/ligaments:
      Weber number hydrodynamics, acoustics $\rightarrow$ **hyperbolic PDE**
    - pinching/rupture of liquid membranes/ligaments:
      Ohnesorge number hydrodynamics $\rightarrow$ **parabolic PDE**
    - post-rupture processes: edge dynamics/secondary rupturing/satellite droplets

- modelling efforts:
    - no comprehensive, all-encompassing model available as yet
    - available: partial models covering asymptotic aspects
    - interaction/coupling with external acoustics: partially possible

- goal: physical characterization of atomization
    - process duration
    - droplet size distribution
    - fully coupled with external acoustics $\rightarrow$ **elliptic PDE**

- compare: state-of-the-art in phase transition modelling
    - no closed comprehensive model
    - two asymptotic partial models:
        * nucleation
        * late-stage ripening/Ostwald ripening

Computation of Spray Combustion using PDF-equation approach

P. Durand[1] , M. Gorokhovski[1], R. Borghi[2]

1 : UMR 6614-CNRS

CORIA / Université et INSA de Rouen

FR-76821 Mont-Saint-Aignan Cedex

2 : UMR 6594-CNRS

IRPHE / Université Aix Marseille

FR-13451 Marseille Cedex

•Resulting "spray flame" is controlled by the turbulent scalar mixing and the turbulent dispersion of droplets.

fast reaction, thin spray

gaseous flame, no drops

slow reaction, dense spray

Laser Mie scattering of the reacting spray. The green and blue colors correspond to the droplet scattering and the flame emission respectively. (Stepowski et al., 1992)

•The random positions and properties of evaporating droplets intervene in the turbulent micro-mixing in the gas mixture.

•It modifies the probability distribution of temperature and concentrations and eventually the mean local rate of chemical reactions.

•Models of turbulent gaseous flames that accounts for turbulence-chemistry interaction are often based on the PDF-equation method. The objective here is to extend the PDF-equation approach to the spray combustion.

226

PDF-Equation Approach in Multicontinua Formulation:
Example for vapor and liquid mass fractions

Vapor mass fraction signal

Liquid mass fraction signal

Results in joint PDF $P(\hat{Y}_v, \hat{Y}_L)$

Conditional ($Y_L = 0$) vapor mass fraction signal

Results in conditional PDF:
$$P(\hat{Y}_v, \hat{Y}_L) = f(\hat{Y}_v) * \delta(\hat{Y}_L - 0)$$

From the stochastic differential equation to the PDF-equation

$\Rightarrow$ unconditional PDF $P(\hat{Y}_v)$

- Fluctuations (Y_i, T) in the gas are caused by the random velocity field and by the random rate of vaporization/condensation. The set of all events constitutes a sample space.

- Instantaneous continuity for the vapor mass fraction :

$$\rho\frac{\partial Y_v}{\partial t} + \rho\vec{V} \cdot \nabla Y_v = \nabla\left(D\rho\nabla Y_v\right) + \rho\dot{\omega}_{lg}\left(1 - Y_v\right) + \rho\dot{\omega}_{chem}$$

- Instantaneous continuity for the gas mixture density :

$$\frac{\partial \rho}{\partial t} + \nabla \cdot \left(\rho\vec{V}\right) = \rho\dot{\omega}_{lg}$$

- Vaporization rate : $\dot{\omega}_{lg} = \rho_v V_{vap,s}.\Sigma;$

  $\rightarrow \Sigma = |\nabla Y_v|\,\delta(Y_v - Y_{vs})$ - instantaneous interface per unit volume
  $V_{vap,s}$ - vapor velocity relatively to the displacement of interface
  $\dot{\omega}_{lg} = 0$ if $V_{vap,s} = 0$ (or $Y_v \neq Y_{vs}$)

  $\rightarrow \dot{\omega}_{chem}$ - chemical reaction rate

228

- Unconditional PDF balance equation :

$$\frac{\partial}{\partial t}\left(\langle\rho|Y_v=\hat{Y}_v\rangle P(\hat{Y}_v)\right) + \nabla\left[\langle\rho\vec{V}|Y_v=\hat{Y}_v\rangle P(\hat{Y}_v)\right] = \langle\rho\dot{\omega}_{lg}|Y_v=\hat{Y}_v\rangle P(\hat{Y}_v)$$

evolution in the phase space
$$\left\{\begin{array}{l} -\dfrac{\partial}{\partial\hat{Y}_v}\left[\langle\nabla\left(\rho D\nabla Y_v\right)|Y_v=\hat{Y}_v\rangle P(\hat{Y}_v)\right] \\[2mm] -\dfrac{\partial}{\partial\hat{Y}_v}\left[P(\hat{Y}_v)\langle\rho\dot{\omega}_{lg}|Y_v=\hat{Y}_v\rangle\left(1-\hat{Y}_v\right)\right] \\[2mm] -\dfrac{\partial}{\partial\hat{Y}_v}\left[P(\hat{Y}_v)\langle\rho\omega_{chem}|Y_v=\hat{Y}_v\rangle\right] \end{array}\right.$$

- Integration over all spectrum of $\hat{Y}_v$ leads to the averaged continuity equation :

$$\frac{\partial\overline{\rho}}{\partial t} + \nabla\cdot\left(\overline{\rho\vec{V}}\right) = \overline{\rho\omega_{lg}}$$

- Vaporization/condensation rate is explicitly available from Lagrangian tracking of the droplets

- Non-linear chemical reaction term is presented in exact form

Unconditional joint PDF-equation for gas mixture
(gaseous species and gas enthalpy) :

$$\frac{\partial}{\partial t}\langle\rho\rangle P\left(\hat{Y}_1,...,\hat{Y}_M,\hat{h}\right) + \nabla\left[\langle\rho\vec{V}\rangle P\left(\hat{Y}_1,...,\hat{Y}_M,\hat{h}\right)\right] = \langle\rho\dot{\omega}_{lg}\rangle P\left(\hat{Y}_1,...,\hat{Y}_M,\hat{h}\right)$$

$$- \sum_{i=1}^{M}\frac{\partial}{\partial\hat{Y}_i}\left[\left(\langle\nabla\left(\rho D\nabla Y_i\right)\rangle - \langle\rho\dot{\omega}_{lg}\rangle Y_i + \langle\rho\dot{\omega}_{lg}\rangle\delta_{iv}\right) P\left(\hat{Y}_1,...,\hat{Y}_M,\hat{h}\right)\right]$$

$$- \frac{\partial}{\partial\hat{h}}\left[\left(\langle\nabla\left(\rho D\nabla h\right)\rangle + \langle\rho\dot{q}_{lg}\rangle\right) P\left(\hat{Y}_1,...,\hat{Y}_M,\hat{h}\right)\right]$$

$$- \sum_{i=1}^{M}\frac{\partial}{\partial\hat{Y}_i}\langle\rho\omega_{chem}\rangle P\left(\hat{Y}_1,...,\hat{Y}_M,\hat{h}\right)$$

- Enthalpy source (or sink) due to the droplets $\dot{q}_{lg}$ is explicitly available from Lagrangian tracking of the droplets ; $\dot{q}_{lg} = 0$ if the heat exchange at the interface = latent heat

- Alongside with the CFD, the modeling of PDF-equation supplies each cell with the probability distributions in order to calculate the mean combustion rate

Micro-mixing modeling

"turbulent" part of micro-mixing

$$\eta \approx l_{tur}\, Re^{-3/4}$$

random rearrangement of steady-state laminar vapor sheet

"quasi-laminar" part of mixing

$\hat{y}_{v\eta}$ $\hat{y}_{vs}$ $\hat{y}_{v\eta}$

$\vec{U}_d$ r_0

random sampling from:

$$P(\hat{y}_{vs} \geq \hat{y}_v \geq \hat{y}_{v\eta}) \approx (\nabla \hat{y}_v)^{-1} \approx \hat{y}_v^{-1}$$

Spalding solution

for evaporating drop: $\nabla y_v = \dfrac{\dot{w}_{ig}(\hat{y}_v - 1)}{4\pi r_0^2\, \rho D}$

Curl pairwise interaction

$P(\hat{y}_v)$

$\hat{y}_{v\eta}$ $\hat{y}_{vs}$

Laminar and turbulent parts in the mixing

At what conditions entirely turbulent mixing occurs?

For stagnant droplet:

$$t_{evap} \propto \frac{d_0^2}{8D} \cdot \frac{\rho_{liq}}{\rho_{gas}}; \qquad t_{tur} \propto \frac{k}{\varepsilon};$$

$$\frac{t_{evap}}{t_{tur}} \propto \frac{d_0^2}{8\eta^2} \cdot \frac{\rho_{liq}}{\rho_{gas}} \cdot \frac{V_\eta}{k} \propto \quad \cdots \cdots \left| \frac{V_\eta}{\Delta U} \propto \mathrm{Re}^{-1/4} \right| \cdots \cdots \propto \frac{1}{8\,\mathrm{Re}^{1/2}} \cdot \left(\frac{d_0}{\eta} \right)^2 \cdot \frac{\rho_{liq}}{\rho_{gas}}$$

$$\left(\frac{\eta}{d_0} \right)^2 \propto \frac{1}{8\,\mathrm{Re}^{1/2}} \cdot \frac{\rho_{liq}}{\rho_{gas}} \cdot \frac{t_{tur}}{t_{evap}}; \quad d_0 > \eta \quad \Rightarrow \quad \text{mixing is turbulent.}$$

For mobile droplet:

$$\left| u_d - u_{gas} \right| > V_\eta \quad \Rightarrow \quad \text{mixing is turbulent.}$$

232

SCHEMATIC

micromixing

CURL

$N^* = N \cdot \dfrac{\tau_y}{\tau_t}$

evaporation

N particles

Y_v, h

$Y_{vs}, h_s = h_s(Y_{vs}, T_s)$

$+$

$N_{inj} \cdot \dfrac{\overline{Y}_v^{n+b} - \overline{Y}_v^{n}}{\overline{Y}_v^{n+1} - Y_{vs}} \cdot N$

$$\dfrac{\displaystyle\int_{Y_{vs}}^{Y_v} P(\hat{Y}_v)\, d\hat{Y}_v}{\displaystyle\int_{Y_{vs}}^{Y_{vn}} P(\hat{Y}_v)\, d\hat{Y}_v} = rnd \in [0,1] \quad \Rightarrow \quad \hat{Y}_v = \hat{Y}_{vn}\left(\dfrac{\hat{Y}_{vs}}{\hat{Y}_{vn}}\right)^{rnd}$$

MONTE CARLO MODELING
OF JOINT PDF-EQUATION

- transport

- vaporization

- micromixing

- chemistry in each
  statistical particle

KIVA II :

A COMPUTER PROGRAM
FOR THE TRANSIENT
CHEMICALLY REACTIVE
FLOWS WITH
EVAPORATING SPRAYS

instantaneous positions
of spray droplets

spray droplet evaporation
and energy terms

Courant and Fourier numbers
to model the transport of PDF

mean combustion rate

Simulation of convective transport

Donnor/acceptor scheme :

$$P_a = P_a + \frac{\delta V_\alpha}{V} P_d$$

→ Exchange of Nc_α statistical particles

→ $Nc_\alpha = int\,[N.C_\alpha]$ where C_α is an effective Courant number

Simulation of diffusive transport

$$\vec{A}_\alpha = \varphi_\alpha(\vec{r} - \vec{r}_\alpha)$$

$$(\nu_T \cdot \vec{\nabla P.A})_\alpha$$

donor

acceptor

Nd_α

$$P_a = P_a(1 - F_\alpha) + F_\alpha P_d$$

→ Exchange of Nd_α statistical particles

→ $Nd_\alpha = int[N.F_\alpha]$ where F_α is an effective Fourier number

# Spray in the constant volume bomb. (inert case)

PDF distribution computed

Experimental and numerical inlet setup

Experiment

Modeling

liquid methanol

air

3.4 mm
2.4 mm
1.8 mm

3.4 mm

-20 -10 0 10 20

Computations of temperature and vapor distributions
using Eddy-Break-Up combustion model (middle) and PDF approach (right)

Probability distributions
of vapor mass fraction
and temperature in two
different locations

PDF

EBU

Experimental pattern of
OH emission

V = 110 m/s Q_{CH_3OH} = 1g/s

Computed results

Stepowski et al, 1994:

OH planar laser-induced fluorescence images of the reacting spray. Images represent two snapshots taken for $V_{coflow} = 110 m/s$

mean combustion rate	mixing controlled zone $t_{mix} > (t_{vap}; t_{chem})$

Stepowski et al., 1994:
Experimental lift-off
location versus air coflow
velocities

Computed probable zone of stabilized
combustion for three coflow velocities

$U_{cof} = 70$ m/s $U_{cof} = 110$ m/s $U_{cof} = 150$ m/s

ROCKET INJECTOR CHALLENGES:
Performance, Stability and Reliability at Low Cost

R. J. Santoro

Propulsion Engineering Research Center
and
Department of Mechanical and Nuclear Engineering
The Pennsylvania State University

INTERNATIONAL WORKSHOP ON
RESEARCH STATUS AND PERSPECTIVES
IN LIQUID ROCKET COMBUSTION CHAMBER FLOW DYNAMICS

May 27-28, 1999
PARIS - France

PENNSTATE

ACKNOWLEDGMENTS

PENNSTATE

OVERVIEW

- Rocket Injector Design Criteria
  - ⇒ Propellant Combination
  - ⇒ Performance, Stability and Reliability Aspects
  - ⇒ Low Cost
- Focused Application-oriented Injector Research at Penn State
  - ⇒ LOX-rich Preburner - LOX/GH$_2$ Propellants
  - ⇒ Orbital Maneuvering System (OMS) Upgrade - LOX/Ethanol Propellants
  - ⇒ Gas/Gas Injector Technology - GO$_2$/GH$_2$ Propellants
- Injector Flowfield Research at Penn State
  - ⇒ Dynamics of Impinging Jet Injectors
  - ⇒ Chamber Mach Number Effects on Injector Flowfield - GO$_2$/GH$_2$ and LOX/GH$_2$ Propellants
- Summary/Future Plans

PENNSTATE

ROCKET INJECTOR DESIGN

Application Defines Propellants/Injector Design

LOX/GH$_2$		**PROPELLANTS**		LOX/H$_2$O$_2$
• SSME		• LOX/GH$_2$		• Upper Stage Engine
• X-33		• GO$_2$/GH$_2$		
• LOX Rich Preburner		• LOX/Ethanol		LOX/RP-1
		• LOX/RP-1		• X-34
		• LOX/H$_2$O$_2$		

GO$_2$/GH$_2$	LOX/Ethanol
• Full Flow Engine Cycle	• OMS
• RBCC Rocket	• RCS

PENNSTATE

ROCKET INJECTOR DESIGN

Injectors Depend on Shear and/or Flow Impingement for Mixing and/or Atomization

Shear Coaxial Injector

Swirl

Swirl Coaxial Injector

Generic Injector Types

Impinging Injector

PERFORMANCE

- Combustion Efficiency Is Typically High, Particularly, for H_2/O_2 Systems (99%).
    - Performance Gains Through Compact Combustors
    - Increased Lifetime
- Combustion Performance - Instability Trade-off Critical for Liquid-liquid Systems Such As LOX/RP-1.
- Route to Improved Performance Is Advance Design Methodologies That Are CFD Model Based.
    - Gas/Gas Injector Studies Have Been Pursued As a First Step

INJECTOR RESEARCH AT PENN STATE

• <u>Focused Application-oriented Injector Research at Penn State</u>

⇒ Gas/Gas Injector Technology - GO_2/GH_2 Propellants
→ Shear Coaxial Injector
→ Swirl Coaxial Injector
→ Impinging Injector

⇒ LOX-rich Preburner - LOX/GH_2 Propellants
→ Swirl Coaxial Injector

⇒ Orbital Maneuvering System (OMS) Upgrade - LOX/Ethanol Propellants
→ Pintle Injector
→ Bi-centrifugal Coaxial Swirl Injector

PENNSTATE

GAS/GAS INJECTOR TECHNOLOGY

Motivation

• Data Base on Gas/Gas Combustion for Rocket Application Is Limited To Studies of Global Characteristics

  – Aerojet Report (1973)

• Gas/Gas Injector Design Requires a Data Base On Local Phenomena

  – Mixing and Combustion Characteristics

  – Injector Face and Wall Heat Transfer Issues

• Laser-based Diagnostic Techniques and CFD Models Have Matured, and Can Be Used As Design Tools for Next-generation Technology (RLV) Development

PENNSTATE

GAS/GAS INJECTOR TECHNOLOGY

FLOW CONDITIONS

GH_2 Mass Flow Rate	1.9×10^{-2} kg/s (4.2×10^{-2} lbm/s)
GO_2 Mass Flow Rate	0.11 kg/s (0.25 lbm/s)
GO_2/GH_2 Mass Flow Ratio	6.0
Inlet Gas Temperature	300 K
Chamber Pressure	6.9 MPa (1000 psia)

PENNSTATE

GAS/GAS INJECTOR TECHNOLOGY

Injectors Tested
- **Swirl Coaxial Injectors**
  $\Rightarrow$ **60°, 75° and 90° GO_2 Swirl**
- **Shear Coaxial Injectors**
  $\Rightarrow$ **H_2/O_2 Velocity Ratios of 4, 6, 7 and 8**
- **O-F-O and F-O-F Triplet Injectors**
  $\Rightarrow$ *Excessive Heat Transfer Noted at*
  Lower Pressure Experiments
  (Not Tested at 1000 psia)

Injector Posts for 60°, 75° and 90° GO_2 Swirl

PENNSTATE

GAS/GAS INJECTOR TECHNOLOGY

Raman Species Measurements for 60° Swirl Injector

O/F=6

H₂ Instantaneous

H₂ Average of 8 Realizations

H₂O Instantaneous

H₂O Average of 11 Realizations

P_c=993 psia; x=3.5 in.

X=89 mm

Near-Complete Mixing and Combustion Within 90 mm

PENNSTATE

GAS/GAS INJECTOR TECHNOLOGY

Injector Face Temperature for Swirl Injectors

O/F=6

PENNSTATE

GAS/GAS INJECTOR TECHNOLOGY

O/F=6   X=127 mm

H₂/O₂ Velocity Ratio=8.0   H₂/O₂ Velocity Ratio=6.8

H₂/O₂ Velocity Ratio=5.9   H₂/O₂ Velocity Ratio=3.9

PENNSTATE

GAS/GAS INJECTOR TECHNOLOGY

Summary

<u>Swirl Coaxial Injector</u>
- Mixing and Combustion Is Extremely Fast
- Heat Release Achieved Within a Short Distance
- Face Temperature Increases With Swirl Angle
- Use of Swirl Coaxial Injector Will Require Effective Face Cooling Strategies

<u>Shear Coaxial Injector</u>
- Mixing and Combustion Is Slower Than Swirl Coaxial Injector
- Mixing and Combustion Increases With GH₂ to GO₂ Velocity Ratio

PENNSTATE

LOX-RICH PREBURNER

Motivation

- Improve Understanding of LOX/GH$_2$ Combustion at LOX-rich Conditions
- Conduct Detailed Study of Swirl Coaxial Injector Performance
- Data Base to Validate/improve Computational Combustion Tools

---

LOX-RICH PREBURNER

TEST CONDITIONS

CASE	LO$_2$ Flowrate (lb$_m$/s)	GH$_2$ Flowrate (lb$_m$/s)	(O/F)$_{mass}$	T$_{adiabatic}$ K	P$_{chamber}$ psia	c* Efficiency	LO$_2$ Velocity ft/s	GH$_2$ Velocity ft/s
A	0.2	0.004	50	1806	300	0.6	110	110
B	0.2	0.005	40	2114	333	0.8	110	140
C	0.2	0.008	25	2724	337	0.9	110	224

LOX-RICH PREBURNER

TEST CELL

INSTRUMENT CELL

RAMAN SETUP

Personal Computer
Gate/Pulse Generator
Data Acquisition System

105 mm
Nikkor Lens
f/#=1.8

f=0.75 m
Focusing Lens

ICCD

Holographic
Imaging
Spectrograph
f/#=1.8

Beam
Stop

Laser
Window

Imaging
Mirror

IR
Filter

Q-Switched Nd:YAG

Rocket

PENNSTATE

LOX-RICH PREBURNER

X=127 mm, X/d=37 (X=axial distance, d=LOX post ID)

PENNSTATE

LOX-RICH PREBURNER

X=127 mm, X/d=37 (X=axial distance, d=LOX post ID)

PENNSTATE

LOX-RICH PREBURNER

Summary

- Single Shot Linewise Multi-species Raman Images Of LOX/GH$_2$ Rocket Combustion Obtained For Oxidizer-rich Conditions
- Resultant Temperature And Major Species Profiles Yield Expected Values
- Swirl Coaxial Injector Mixedness Is Further Evaluated

PENNSTATE

252

OMS UPGRADE

Motivation

- NASA Is Investigating the Feasibility of a Non-toxic OMS/RCS Upgrade for the Space Shuttle to Eliminate the Safety and Cost Issues Associated With Hypergolic Propellants
- <u>Broad Objectives</u>

  To Provide NASA and Contractors With an Objective Base From Which Future Injector Design Decisions Can Be Made for OMS and Future HEDS Applications
- <u>Specific Objectives</u>

  To Measure and Analyze Detailed Combustion Characteristics of *LOX/Ethanol* Propellant Combinations at Representative Thrust Chamber Conditions for Various Candidate Injectors

PENNSTATE

OMS UPGRADE

BI-CENTRIFUGAL SWIRLER

PINTLE INJECTOR TIP

PENNSTATE

OMS UPGRADE

OMS Engine Design
Thrust: 27 kN (6000 lbf)
Isp: 326 sec
Mixture Ratio: 1.7
Propellant Flowrate: 8.3 kg/s (18.4 lbm/s)
     -Oxygen: 5.26 kg/s (11.6 lbm/s)
     -Ethanol: 3.08 kg/s (6.8 lbm/s)

Sub-Scale Engine Design
1/60 of Full Scale-mass flowrate
Mixture Ratio: 1.7

Propellant Flowrate: 0.14 kg/s (0.307 lbm/s)
     -Oxygen: 0.088 kg/s (0.193 lbm/s)
     -Ethanol: 0.052 kg/s (0.114 lbm/s)

Case #	1	2	3	4	5	6
P_c (MPa)	1.10	1.10	1.10	2.07	2.07	2.07
O/F	2.0	1.7	1.4	2.0	1.7	1.4
LOX flowrate (kg/s)	0.095	0.088	0.082	0.177	0.163	0.155
ethanol flowrate (kg/s)	0.048	0.052	0.059	0.088	0.096	0.111
GN2 flowrate (kg/s)	0.014	0.014	0.014	0.014	0.014	0.014
Nozzle Diameter (mm)	16.51	16.51	16.51	16.51	16.51	16.51

PENNSTATE

OMS UPGRADE

- **Over 100 LOX/Ethanol Tests Were Conducted on Pintle Injectors**

PENNSTATE

OMS UPGRADE

BI-CENTRIFUGAL NEAR INJECTOR FLOWFIELD

2M injector, Case 2 ← Flow 2M injector, Case 6

Outer LOX flow is separated from inner ethanol cone by layer of vaporized oxygen

---

OMS UPGRADE

MODIFIED BI-CENTRIFUGAL INJECTOR WITH LARGE RECESS
•2M w/large recess face plate exhibits good mixing and combustion over
wide range of operating conditions and is insensitive to LOX quality

Case 3 ← Flow Case 4

OMS UPGRADE

PERFORMANCE OF BI-CENTRIFUGAL INJECTOR

Plot: C* Efficiency (%) versus LOX Quality (P_c/P_v at T_3)

Legend:
- ○ 1 M (90 inj/fire plate) low P
- ● 1 M (90 inj/fire plate) high P
- □ 2 M (60 inj/fire plate) low P
- ■ 2 M (60 inj/fire plate) high P
- ⊙ 2 low P
- △ 2 Delta (narrow gap) low P
- ▲ 2 Delta (narrow gap) high P
- ⊡ 2 M w/big recess low P
- ▣ 2 M w/big recess high P
- ◇ 2 O (open w/big recess) low P
- ◆ 2 O (open w/big recess) high P
- ● 3 Delta A high P
- ▽ 3 B (reverse scheme) low P
- ▼ 3 B (reverse scheme) high P

PENNSTATE

OMS UPGRADE

Summary

PINTLE INJECTOR

- Pintle Injector Designed for OMS Conditions Operated in a Stable Manner
- For Pintle Injector, c* Efficiency Increase With O/F

BI-CENTRIFUGAL SWIRLER

- Marginal LOX Quality Influenced Combustion Efficiency for All Injector Configurations
- Shadowgraph Imaging Was Instrumental in Assessing Flow Phenomena Which Caused Lower Than Expected Performance
- Use of Recess Is Reasonable Solution to Spray Cone Separation Problem:
  - Recess Insensitive to LOX Quality (of Significance to OMS Upgrade), Stable Under All Conditions Tested, LOX Cooling of Injector Face Effective Here

PENNSTATE

INJECTOR RESEARCH AT PENN STATE

<u>Injector Flowfield Research at Penn State</u>

$\Rightarrow$ Dynamics of Impinging Jet Injectors
  $\rightarrow$ Like-on-like Impinging Injectors

$\Rightarrow$ Chamber Mach Number Effects on Injector Flowfield - GO_2/GH_2 and
  LOX/GH_2 Propellants
  $\rightarrow$ Shear Coaxial Injectors

PENNSTATE

DYNAMICS OF IMPINGING JET INJECTORS

Motivation

- Determine Conditions Under Which Impinging Jet Injector
  Periodic Atomization Can Cause Combustion Instabilities

    $\Rightarrow$ Longitudinal Mode Excitation for GO_2/ethanol Propellants in
    Model Rocket Chamber

    $\Rightarrow$ Electromechanical Drivers Controlling Individual Ethanol Jets
    (*of Impinging Jet Injector*)

PENNSTATE

DYNAMICS OF IMPINGING JET INJECTORS

- Ethanol Impinging Jet Injector
  (Individual Electromechanical Drivers
- Annular Flow of GO_2

PENNSTATE

DYNAMICS OF IMPINGING JET INJECTORS

ELECTROMECHANICALLY DRIVEN
INJECTOR ASSEMBLY

IMPINGING INJECTOR JETS
PERTURBED OUT-OF-PHASE
AT 2500 Hz

PENNSTATE

258

DYNAMICS OF IMPINGING JET INJECTORS


DYNAMICS OF IMPINGING JET INJECTORS

DYNAMICS OF IMPINGING JET INJECTORS

Summary

- Successful Demonstration of Combustion Instability by Periodic Atomization for Impinging Jet Injector
- Technique Has Potential As Active Control of Combustion Instability

---

CHAMBER MACH # EFFECT STUDIES

Motivation

- Document Effect of Chamber Mach # on Mixing and Combustion Characteristics of Shear Coaxial Injector for Both GO_2/GH_2 and LOX/GH_2 (*Currently in Progress*) Propellants

- Obtain Data Base for CFD Code Validation

CHAMBER MACH # EFFECT STUDIES

- GO_2/GH_2 Study Injector
- O/F =4 GO_2/GH_2 Combustion
- Background Air/GH_2 Flow
- 1200 K Background Flow
- Chamber Pressure $\approx$ 1.3 MPa
  (190 psia)
- Chamber Mach # Varied
  $\Rightarrow$ for M# of $\approx$0, 0.1, 0.2, 0.3

FLOW

50.8 mm

Air Holes
GO_2/GH_2 Shear Coaxial Injector
GH_2 Swirlers

PENNSTATE

CHAMBER MACH # EFFECT STUDIES

## Flow Conditions

Case	Chamber Mach Number	O_2 mass flow rate (lbm/s)	Main H_2 mass flow rate (lbm/s)	Air mass flow rate (lbm/s)	Background H_2 mass flow rate (lbm/s)
1	0.1	0.093	0.024	0.730	0.007
2	0.2	0.093	0.024	1.887	0.016
3	0.3	0.093	0.024	3.197	0.030

Case	O/F Main	O/F Background	O/F total
1	3.818	111.4	26.7
2	3.818	115.4	48.8
3	3.818	107.2	60.8

PENNSTATE

CHAMBER MACH # EFFECT STUDIES

Focused Laser Beam Passes
Vertically Through Rocket
Chamber

50mm Lens

ICCD Camera   Imaging Spectrograph

CHAMBER MACH # EFFECT STUDIES

P_c=1.3 MPa
X=51 mm
X/d=6.5
X=*Axial Distance*
d=*GO_2 Post ID*

M# ≈ 0

M# ≈ 0.1

M# ≈ 0.2

M# ≈ 0.3

262

M# ≈ 0

M# ≈ 0.1

M# ≈ 0.2

M# ≈ 0.3

P_c=1.3 MPa
X=51 mm
X/d=6.5
X=*Axial Distance*
d=*GO_2 Post ID*

PENNSTATE

CHAMBER MACH # EFFECT STUDIES

M# ≈ 0

M# ≈ 0.1

M# ≈ 0.2

M# ≈ 0.3

P_c=1.3 MPa
X=127 mm
X/d=16.2
X=*Axial Distance*
d=*GO_2 Post ID*

PENNSTATE

CHAMBER MACH # EFFECT STUDIES

P_c=1.3 MPa
X=127 mm
X/d=16.2
X=*Axial Distance*
d=*GO_2 Post ID*

M# ≈ 0

M# ≈ 0.1

M# ≈ 0.2

M# ≈ 0.3

CHAMBER MACH # EFFECT STUDIES

SHADOWGRAPH IMAGE OF LOX IN COMBUSTION ZONE
- LOX/GH_2 O/F=4 For Shear Coaxial Injector
- Chamber Pressure = 1.38 MPa (200 psia)
- Chamber Mach# = 0.2 (Air/GH_2 Combustion; 1280 K)

32 mm

74 mm

CHAMBER MACH # EFFECT STUDIES

Summary

• Initial Experiments for a GO$_2$/GH$_2$ Shear Coaxial Injector Involving Raman Spectroscopy Indicate That Chamber Mach # Increases Mixing
• Experiments Are Currently Underway for a LOX/GH$_2$ Shear Coaxial Injector

PENNSTATE

Summary/Future Work

• Broad Rocket Propulsion Interests Are Driving Diverse Studies of Injector Types and Propellant Combinations.
• Current Interest in Low Cost Access to Space Is Currently Focusing Research On Propellants That Provide Operations Advantages and Robust Injector/Chamber Concepts That Increase Lifetime.
• Advanced Concepts Such As Rocket Based Combined Cycle and Pulse Detonation Engines Are Also Competing Increasing Interest.
• Future Research Efforts At Penn State's Cryogenic Combustion Laboratory Reflect These Developments.

PENNSTATE

Recent Studies on Preburner Injector Characteristics

for the Hydrogen-Oxygen Engine

J.Wang,   S.Q.Cheng,   L.Z.Song,   P.X.Hu

11th Research Institute of China Aerospace Corporation

Abstract In order to develop the technology for high performance hydrogen-oxygen staged combustion rocket engine, four kinds of preburner injector have been studied theoretically and experimentally. By using the Phase Doppler Particle Analyzer(PDPA), the spray characteristics of these injectors are investigated, through varying liquid-to-air pressure drop ratio, liquid mass flow, and back pressure in the high pressure rig. Fire tests have also been completed for demonstration. The spray performance, gas temperature distribution, combustion stability and ignition performance for different injector configurations are revealed.

1. Introduction

The preburner is a key component for the staged combustion cycle engine, owing to it's higher pressure and flowrate than that of the gas generator cycle engine. It's combustion performance and stability, gas temperature distribution at exit are closely related to it's injector configurations. In order to develop high performance preburner injector, recently we studied four kinds of injector configurations theoretically and experimentally.

Four kinds of injector configurations are depicted in fig.1-3. The coaxial injector with swirler of liquid oxygen in centre can get high performance and commonly used in china Hydrogen Oxygen Rocket Engine, The coaxial injector with straight stream of liquid oxygen in centre use the successful experiences of the SSME/LE-7 preburner injectors and it has a well-earned reputation for it's reliable operation and processing; The bi-coaxial injector is a new kind of injector configuration we designed specially. It's hydrogen sleeve consist of two segments, hydrogen and oxygen burn at near stoichiometric mixture ratio in the first segment. In the second segment, is injected the remainder of hydrogen which mix and cool the stream exited from first segment. Turbulent diffusion combustion is transformed into premixture combustion for this injector, so that it's combustion rate increases. It's spray and mixture performance are as same as that of the shear coaxial injector.

Preburner injector unit is made of injector face plate, central ignition port and four injector, as shown in Fig.4. The ignition port diameter is 16mm. Four injectors with same configuration are equally located at a circle of diameter 32mm.Four injector configurations, namely A,B,C,D are used respectively in their injector elements for testing.

we employed the Phase Doppler Analyzer(PDPA) to study spray droplet size and flowrate distribution for different injector configuration, using air and water as imitation agents, varying liquid-to-air injector pressure drop ratio, liquid mass flowrate and back pressure in the high pressure rig. Theoretical approach is to calculate the atomization combustion model which consider gaseous phase, droplet phase, turbulence and combustion effects. Changing the measured spray data into inlet conditions of the imitation calculation, we can get the spray combustion efficiency and gas temperature distribution and other parameters for the four kinds of injector configuration. The injector elements are also undertaken fire testings, it's chamber pressure ranges 6.85-7.73 MPa, it's mixture ratio ranges o.639-0.845. Combustion efficiency, gas temperature distribution and vibration are measured .

Fig.1 Swirl coaxial injector(A)

Fig.2 Shear coaxial injector(B)

$$L=\begin{cases}17mm\\27mm\end{cases}$$

Fig.3 bi-coaxial injector

Injector arrangement

Fig.4   injector unit

2. Test Facilities

Injector spray testing goes on in the high pressure rig, as shown in Fig. 5. Normal pressure in the rig is 3.5 MPa, it's internal diameter 320mm, highness 1200mm. There are four windows on it's flank, inserted with plate glass of thickness 25mm and diameter 100mm, used for PDPA light emission, receive and monitor. Safety valve and pressure gauge are mounted on the upper cover, the regulator on bottom is used to keep chamber pressure.

Fire test system for preburner injector, in Fig.6, consist of hydrogen flow lines, liquid oxygen flow lines, nitrogen pressurization system, nitrogen cutoff system and measurement system. The venturi orifice and sonic nozzle are respectively set on liquid oxygen flow line and gaseous hydrogen flow line. The measured data include propellant flowrate, inlet injector pressure, gas average pressure and fluctuation pressure, vibrations corresponding to axial, radial, tangential direction at injector element head. Three temperature gauges are mounted on exhaust duct to measure gas temperature distribution.

Fig.5 spray measurement system   Fig.6 fire testing system

3. Theoretical Model

the spray combustion model in [4] is adopted for theoretical calculation. The model consider gas phases combustion, as well as droplet behavior in gas phases and their interaction. These processes are coupled each other, so that the calculation of the spray combustion model should be done by solving equation system of gas phase equation, droplet equation, combustion and turbulence equation.

3.1 Gas Phase Governing Equations

We can get the gas phase governing equations concerning the continuity, momentum, energy and composition in the following average form:

$$\frac{\partial \bar{\rho}}{\partial t} + \frac{\partial}{\partial x_j} | \overline{\rho u_j} | = S_{pm}$$

$$\frac{\partial}{\partial t}(\overline{\rho u_j}) + \frac{\partial}{\partial x_j}(\overline{\rho u_i u_j}) + \frac{\partial}{\partial x_j}(\overline{\rho u'_i u'_j}) = -\frac{\partial \bar{p}}{\partial x_j} + \frac{\partial \bar{\tau}_{ij}}{\partial x_j} + \overline{\rho F_j} + S_{pui}$$

$$\frac{\partial}{\partial t}(\overline{\rho H}) + \frac{\partial}{\partial x_j}(\overline{\rho u_j H} + \overline{\rho u' H'}) = \frac{\partial \bar{p}}{\partial t} + \frac{\partial}{\partial x_j}(\frac{\mu}{Pr}\frac{\partial \bar{H}}{\partial x_j}) +$$

$$\frac{\partial}{\partial x_j}(\bar{\tau}_{ij}\bar{u}_i - \mu \bar{u}_i \frac{\partial \bar{u}_i}{\partial x_j}) + \frac{\partial \bar{q}_{ij}}{\partial x_j} + S_{pH}$$

269

$$\left\{ \frac{\partial}{\partial t}(\bar{\rho}\bar{Y}_s) + \frac{\partial}{\partial x_j}(\bar{\rho}\bar{Y}_s\bar{u}_j) + \overline{\rho\bar{Y}'_s u'_j}) = \frac{\partial}{\partial x_j}(\bar{\rho}D_s \frac{\partial \bar{Y}_s}{\partial x_j}) - \bar{W}_s + S_{YS} \right. \tag{1}$$

Turbulence model employs κ - ε equations, namely

$$\left\{ \begin{array}{l} \frac{\partial}{\partial t}(\bar{\rho}k) + \frac{\partial}{\partial x_j}(\overline{\rho u_j}k) = \frac{\partial}{\partial x_j}[\Gamma_k \frac{\partial k}{\partial x_j}] + G_k - \bar{\rho}\varepsilon \\[3mm] \frac{\partial}{\partial t}(\bar{\rho}\varepsilon) + \frac{\partial}{\partial x_j}(\overline{\rho u_j}\varepsilon) = \frac{\partial}{\partial x_j}[\Gamma_\varepsilon \frac{\partial \varepsilon}{\partial x_j}] + C_1 \frac{\varepsilon}{k}G_k - C_2 \frac{\bar{\rho}}{k}\varepsilon^2 \end{array} \right. \tag{2}$$

Assuming that stress is proportional to average strain, the expression of Reynold's strain is as following:

$$- \bar{\rho}\,\overline{u'_i u'_j} = \mu_i [\frac{\partial \bar{u}_j}{\partial x_i} + \frac{\partial \bar{u}_i}{\partial x_j}] - \frac{2}{3}\rho k \delta_{ij} \tag{3}$$

3.2 Droplet Governing Equations

Considering turbulence diffusion effects, droplet movement equation is written as:

$$\left\{ \begin{array}{l} \dot{m}_d \frac{dU_d}{dt} = C_D \frac{A_d}{2} \frac{\mu Re}{D} [U - (U_d + U_{diff})] \\[3mm] \dot{m}_d \frac{dV_d}{dt} = C_D \frac{A_d}{2} \frac{\mu Re}{D} [V - (V_d + V_{diff})] + \dot{m}_d \frac{W_d^2}{r} \\[3mm] \dot{m}_d \frac{dW_d}{dt} = C_D \frac{A_d}{2} \frac{\mu Re}{D} [W - W_d] + \dot{m}_d \frac{V_d W_d}{r} \end{array} \right. \tag{4}$$

When droplet collide with wall, the droplet rebounds with same axial velocity and opposite radial velocity. It's trajectory equation is :

$$\frac{dx_d}{dt} = U_d, \quad \frac{dr_d}{dt} = V_d, \quad r\frac{d\theta}{dt} = W_d \tag{5}$$

3.3 Droplet Vaporization Model

Droplet vaporization rate can be calculated by following formula:

$$\dot{m}_{v.s} = \frac{2\pi r_l \rho_g D_g N_{um}}{AB}\ln[\frac{1 - Y_{v.\infty}}{Y_{v.s}}] \tag{6}$$

here $\quad A = 1 + \dfrac{4\pi r_l^2 \rho_{us}}{\dot{m}_{v.s}}\dfrac{\partial r_l}{\partial t}$, $B = 1 + \dfrac{\rho_{e.s}}{\rho_{v.s}}(1 - \dfrac{1}{A})$

The droplet radius variation can be written as the following:

$$\frac{dr_l}{dt} = -\frac{\dot{m}_{v.s}}{\pi D^2 \rho_l} - \frac{D}{6\rho_l}\frac{d\rho_l}{dt} \qquad (7)$$

Droplet energy equation is:

$$\frac{dT_l}{dt} = \frac{3\lambda_g N_{uT} Z_1}{2C_{pl}r_{l\rho_l}^2}\left[\frac{T_g - T_l}{e^{Z_1}-1} - \frac{\triangle Hv}{Z_2}\right] \qquad (8)$$

here $Z_1 = \dfrac{\dot{m}_{vs}Z_2}{\pi D\lambda_g N_{uT}}$, $Z_2 = AC_{pv} + (A-1)C_{pe}\dfrac{\rho_{ls}}{\rho_{e.s}}$

3.4 Combustion Model

We use Spalding's EBU model to imitate droplet combustion, assuming that turbulent combustion zone consist of large quantity of flammable gas messes and burned gas messes. Chemical reaction take place at interfaces between messes. Chemical reaction rate depends on flammable gas messes break rate which is directly proportional to turbulence fluctuation energy decay rate.

$$\begin{cases} R_{f.g} = -\min[\mid R_f \mid, \mid R_g \mid] \\[2mm] R_f = -AM_f(\dfrac{\rho_{yf}}{M_f})^\alpha (\dfrac{pY_{ox}}{M_{ox}})^\beta \exp(-E/RT) \\[2mm] R_g = -C_k\rho_g^{0.5}\dfrac{\varepsilon}{k} \end{cases} \qquad (9)$$

here Ck=1.07; A stands for reaction constant;

4. Results and Discussion

4.1 Spray Measurement

The spray is measured downstream at a section of 110 mm distance from nozzle exit. At different radius ,we measure droplet density Nd, average volume diameter D30,average area diameter D20 ,then calculate average droplet diameter D32 by following formula:

$$D_{32} = \frac{\int_0^R N_d(r)D_{30}(r)dr}{\int_0^R N_d(r)D_{20}(r)dr} \qquad (10)$$

Varying gas/liquid injector pressure drop ratio, back pressure in high pressure rig and liquid flowrate, we can obtain the relation between D32 and $\triangle$PG / $\triangle$PG ,PB ,m L, as seen in Fig.7-9. The Fig. 10 show liquid flowrate distribution v.s radius. It can be seen that it's average spray droplet diameter is smallest for centrifugal coaxial injector;

For shear coaxial injector and bi-coaxial injector, their spray droplet diameters are closely; For bi-coaxial injector, when it's oxygen post recess increases, it's average spray droplet diameter will decreases. For all four injector configurations, their average spray droplet diameters will decrease when injector pressure drop ratio increase, and their average spray droplet diameters will increase when back pressure and liquid flowrate increase. Fig.10 show that for shear coaxial injector and bi-coaxial injector, their flowrate distribution concentrate on spray centre; for swirl coaxial injector, it's flowrate distribution is well distributed, that benefits mixture ratio dustribution.


Fig.7 gas/liquid injector pressure drop ratio effects on D32


Fig.8 back pressure effects on D32

Fig.9 flowrate effects on D32



Fig.10 flowrate distribution

4.2 Theoretical Calculation

Cartesian coordinates grid system are used for theoretical calculation. We will change the non-regular physical plane into regular rectangular plane for calculating. The grids distribution is made exponentially. In order to ensure calculation

convergence and accuracy, we make denser grids at near injector face and convergent section, where there are great variation in chemical reaction and flow conditions.


Fig.11 Calculation domain and grid plane

We make the equations(1) and (2) discretization. The liquid phase governing equations (4) and (5) are coupled with gas phase governing equations through diffusion velocities. We can directly integrate the liquid phase governing equations ,while assuming that gas phase field is known. The time interval required for droplet movement from position k to k+1 is decided by following expression:

$$\Delta t_k = min\left\{\frac{\Delta \xi}{\overline{U}_{d.k}} \cdot \frac{\Delta \eta_k}{\overline{V}_{d.k}}\right\} \tag{11}$$

here U_{dk} , V_{dk} denote droplet axial and radial velocities at position k. The SIMPLE was used to solve the equation system. The pressure field is indirectly given by continuity equation, so that we can put the pressure field into momentum equation to get velocity field. As soon as the velocity field meets continuity requirements, the calculation will goes to the end, otherwise the calculation repeats after revising pressure field again. In calculation, we assume that all flux at symmetric axis are equated to zero, the wall is adiabatic , fixed and can't be penetrated, and there is sonic velocity at preburner exit. The flow conditions are greatly coupled with throat choke conditions. The inlet parameters are:

   liquid flowrate 0.0885 kg/s; liquid oxygen temperature 90K; gaseous hydrogen temperature 300K.

   Mixture ratio variation can be realized by changing gaseous hydrogen flowrate. For centrifugal injector, liquid oxygen tangential velocity should be given. For bi- coaxial injector, gaseous hydrogen velocity at different entrance is given to corresponding entrance grids.

   Initial spray droplet size is obtained by spray testing data. Dividing the measured droplet size into 10 groups, inputing diameter and mass percentage of each group, the calculation begin and the results will display on plane.

   For four kinds of preburner injector, the pictures are almost same. Now we take straight coaxial injector as example to explain the results. Velocity vector field is depicted in Fig.12. It show that there is a recirculation zone near injector face.Fig.13 show temperature field, it imply that there is great temperature variation in the range of 30-70mm downstream injector face, where exists strong combustion reaction. Liquid oxygen droplets injecting from injector move forward along it's trajectory,

owing to their vaporization, around them exist strong combustion zones. The oxygen vapor immediately reacts with gaseous hydrogen before it's sufficient diffusion, so that exists higher local mixture ratio. The highest temperature can reach about 3000K.The chemical reaction basically stops in excess of 70mm downstream injector face. Gas temperature gradually become closely and the final temperature is about 1000K. At different axial distance, the temperature variation relations with radius are depicted in Fig.14. The temperature near injector face (X<26.5mm) is under 800K, that imply combustion don't take place. The combustion begins until the distance is in excess of 26.5mm and stops about at X=78.9.The low temperature zones near injector face are produced by recirculation. After combustion begin, exists initial temperature peak in radial direction about at Y=5mm, then the peak move gradually toward the centre. In excess of X=79.9mm, gas temperatures are almost equal. Radial distribution of axial velocities is shown in Fig.15.It imply that recirculation zones exist at 0-43mm axial distance and the flow finally become stable accompanying with the end of combustion. Fig.16 show that radial velocities in combustion zone are relatively higher, owing to turbulence mixture and then they decrease gradually. The radial velocities are almost equal to zero before the convergent section(X=173.9). That means diffusion and mixture are very weak, the flow is in equilibrium.


Fig.12   velocity vector field


Fig.13   isothermal field

Fig.14 gas temperature radial distribution at different sections

Fig.15 radial distribution of axial velocity at different sections

Fig.16 radial distribution of radial velocity at different sections

4.3 Fire Testing Results

Six fire testings for preburner have been finished. The testing measured data are summarized in table 1.

Table 1 testing data

mode	YR01	YR02	YR03	YRO4	YR06$_I$	YR06$_{II}$
preburner pressure Pf, MPa	7.400	7.585	7.489	7.080	7,732	6.848
OX flow Gy, kg/s	0.370	0.376	0.375	0.369	0.367	0.322

H2 flow Gr, kg/s	0.438	0.448	0.461	0.461	0.497	0.470
mixture ratio, r	0.845	0.838	0.813	0.799	0.738	0.673
characteristic velocity C, m/s	2435	2475	2408	2269	2308	2272
gas temperature Tf1 , K	1151	1121	/	/	1003	900
gas temperature Tf2, K	1163	1123	1091	1058	953	866
gas temperature Tf3, K	1134	1103	1056	1054	989	896
theoretical temperature Tf_{Th} ,K	1118	1108	1082	1072	1044	954
biggest temperature difference ΔT_f,K	28.98	20.09	35.6	4.2	50.23	34.73

A. Combustion Efficiency.

It can be calculated by the following:

$$\eta c = C^*_{ex}/C^*_{th} \qquad C^*_{ex} = P_f At/G_\Sigma \qquad (12)$$

here C^*_{ex} is experimental characteristic velocity;
   C^*_{th} is theoretical characteristic velocity, corrected by supply
   gas hydrogen temperature
   At is throat area of exhaust duct

The other measured data are all close to 100%, this is owing to having bigger hardware volume. Theoretical calculation show that the propellant combustion goes on to the end in 100mm downstream injector face. combustion efficiencies greater than 100% result in the measurement error. Comparing four preburner configurations, we found that option D has higher combustion efficiency and lower for B.

B. Gas Temperature Distribution

Gas temperatures are measured at different locations in a same exhaust duct section. The increase rate of measured temperature with mixture ratio is more rapid than that of theoretical calculation. Comparison of the temperature difference show that the gas temperature is well distributed for D , $\Delta Tf = 20.09$, and it's temperature distribution is poor for B, $\Delta Tf = 50.23$.

C. Vibration

Vibration gauges were mounted at the head cover of injector elements in axial, radial and tangential directions. The measured vibration data are given in table 2, the

peak frequency and it's amplitude are given in table 3. Comparing their vibration data of different injector configurations , there is lower vibration for D, it's complex vibration is 325.4 m/s^2, and it's component vibration is 36.8 m/s^2 (3025 Hz). The option B has higher vibration, it's complex vibration is 686 m/s^, component vibration is 196.4(5575 Hz). The measured gas pressure fluctuation show that there is no combustion instability, the peak to peak pressure fluctuation is less than 4% of rated chamber pressure.

Table 2   mechanical   vibration

parameter name	YR01	YR02	YR03	YR04	YR06
option	C	D	A	B	B
axial acceleration a_1, m/s^2	306.3	261.7	514.5	196	356.7
radial acceleration a_2, m /s^2	414.5	279.6	676.2	686	541
tangential acceleration a_3,m/s^2	232	325	/	174	278

Table 3   mechanical   vibration

parameter name		YR01	YR02	YR03	YR04	YR06
axial frequency	Hz	6375	3025	3425	7825	5650
axial amplitude	m/s^2	12.6	36.8	38.9	32	63.8
radial frequency	Hz	6975	8975	3450	5675	5575
radial amplitude	m/s^2	47.2	33.4	59	47.7	196.4
tangential frequency	Hz	4275	7950	3450	3200	5575
tangential amplitude	m/s^2	15.1	22.4	59	18	36.4

D. Ignition Performance

We employ pyrotechnic ignitor AN8100-00B which has 150mm flame length and about four second burning duration. Pressure peaks occur at about 0.6 s. After liquid oxygen and gaseous hydrogen inject into preburner, the chamber pressure rapidly increases up to peak value. there is a time interval between hydrogen entering time and ignition time, which were given in table 4. The ignition performance is closely related to the time interval, and the shorter interval means well ignition performance. The data show that option A has shorter time interval and it is longest for option B. this may be related to mixture ratio distribution (Fig.10). For swirl coaxial injector, oxygen injection flow has strong transversal penetrability into hydrogen, so that it can improve mixture ratio distribution and ignition performance.

Table 4   Ignition delay

parameters name	YR01	YRO2	YR03	YR04	YR06
option	C	D	A	B	B
hydrogen enter time, s	0.4	0.4	0.7	0.4	0.4
ignition time , s	1.6	1.6	1.6	1.8	1.8
time interval, s	1.2	1.2	0.9	1.4	1.4

5.Concluding Remarks

A. Gas/liquid coaxial injector spray droplet diameters decrease with the increase of gas/liquid injector pressure drop and increase with the increase of liquid flowrate and back pressure.

B. Average spray droplet diameter for swirl coaxial injector is smaller than that of shear coaxial injector. It has good transversal penetrability and ignition performance.

C. The bi-coaxial injector (option D) has the advantage of high combustion efficiency and stability, uniform temperature distribution but it needs to further improve it's ignition performance.

D. For gas/liquid coaxial injectors, there are recirculation zones in the range of 0-43mm downstream injector face, and the combustion occurs in range of 30-70mm from injector face.

Reference

1. Sankar S .V,   Zhu J.Y, Bachalo W.D. Experimental studies on the behavior of coaxial rocket injector spray. Areome Tric, Sunnyvale, CA, U.S.A. 1994
2. Lefebvre A.H. Atomization and spray   Hemisphere Pub. XO, 1989
3. Yost M.C. Preburner of staged combustion rocket engine, NASA CR-135356
4 Z.G.Wang   Combustion Processes imitation calculation for liquid rocket engine, National Defence Science and Technology University, China, 1995.

ONERA

Numerical simulation of reactive flow within the MASCOTTE combustor

Mani POUROUCHOTTAMANE ←

Victor BURNLEY

Francis DUPOIRIEUX

Guillaume DEUCHST

Isabelle DUBOIS

Pascale GILBANK

Department of Fundamental and Applied Energetics (DEFA) - ONERA

279

The MASCOTTE combustor

Mascotte operating domain (V03 version)

Gaseous hydrogen mass flow rate : 5 to 75 g/s

Gaseous hydrogen temperature : 298 K or cooled down to 100 K

Liquid oxygen mass flow rate : 40 to 400 g/s

Liquid oxygen temperature : 85 K

Pressure in the combustion chamber : 1 to 100 bars

flame

vizualisation

LOx droplets

secondary atomization

primary atomization zone

GH2

LOx

ONERA

The CFD code MSD2.2

- calculation code of DEFA - ONERA

- version : 2.2 (released in March 1999)

- current applications : propulsion (liquid, solid, airbreathing)

  turbomachinery

  aerothermics

ONERA

Specifications of MSD 2.2

- finite difference finite volume

- structured mesh : fixed or deforming

- multidomain

- multispecies

- schemes : explicit and implicit

- multigrid : V , W and F cycles

- turbulence : $k - \epsilon$, $k - l$, RNG

- combustion : various models

- dispersed two-phase flow : Eulerian (DE), Lagrangian (DLS)

ONERA

Calculation of MASCOTTE

stochastic Eulerian-Lagrangian approach

mean flow field

Calculation DLS
lagrangian tracing of particles

Calculation MSD
eulerian integration of fluid flow

source terms (interfacial transfer)

ONERA

283

Equations for the Lagrangian tracing of particles

$$\frac{d\vec{X}_p}{dt} = \vec{V}_p$$

$$m\frac{d\vec{V}_p}{dt} = \vec{F}$$

$$\frac{dm}{dt} = \omega_{vap}$$

$$m\frac{dh}{dt} = \phi$$

with :

$$\vec{F} = \frac{\pi}{8}D_p^2 C_D \mid \vec{U}_G - \vec{V}_p \mid (\vec{U}_G - \vec{V}_p)$$

$$\omega_{vap} = 2\pi\rho D_p D \ln(1 + B_M)$$

$$\phi = \pi D \, Nu \, \lambda (T - Ts) - \omega_{vap} \, L_{vap}$$

ONERA

Equations solved by MSD

$$\frac{\partial}{\partial t}\begin{pmatrix}\rho \\ \rho\vec{U} \\ \rho H \\ \rho Y_\alpha \\ \rho k \\ \rho\varepsilon\end{pmatrix} + \vec{\nabla}\cdot\begin{pmatrix}\rho\vec{U} \\ \rho\vec{U}\vec{U}+P\mathcal{I} \\ \rho H\vec{U} \\ \rho Y_\alpha\vec{U} \\ \rho k\vec{U} \\ \rho\varepsilon\vec{U}\end{pmatrix} + \overrightarrow{FLUX}_{viscous} = \begin{pmatrix}S_\rho + \mathbf{\Gamma} \\ S_{\rho\vec{U}} + \vec{\mathbf{I}} \\ S_{\rho H} + \mathbf{\Pi} \\ S_{\rho Y_\alpha} + (\mathbf{\Gamma}) \\ S_{\rho k} + .. \\ S_{\rho\varepsilon} + ..\end{pmatrix}$$

In bold : interfacial exchange terms between phases (→ given by DLS)

ONERA

Dispersion validation

The Snyder & Lumley experiment

- Air mean velocity : 6.55 m/s
- Mesh length : 2.54 cm
- Particle diameter : 87 µm
- Particle density : 1000 kg/m3

MASCOTTE simulation at 1 bar

Calculation GRID - MASCOTTE (A-1)

(41 x 41)

MASCOTTE simulation at 1 Bar (A-1)

EBUP = 2500

GH2 mass flow rate : 15 g/s
LOX mass flow rate : 50 g/s
diameter of particles : 50 microns
injection velocity : 20 m/s
5 injection points

k-e model
C1 = 1.44
C2 = 1.92

C1 = 1.2
C2 = 2.3

ONERA

MASCOTTE simulation at 1 Bar (A-1)

GH2 mass flow rate : 15 g/s
LOX mass flow rate : 50 g/s
EBUP = 2500
k-e model
C1 = 1.44
C2 = 1.92

turbulence rate

C1 = 1.2
C2 = 2.3

Taux"e [turb

1
0.965517
0.931034
0.896552
0.862069
0.827586
0.793103
0.758621
0.724138
0.689655
0.655172
0.62069
0.586207
0.551724
0.517241
0.482759
0.448276
0.413793
0.37931
0.344828
0.310345
0.275862
0.241379
0.206897
0.172414
0.137931
0.103448
0.0689655
0.0344828
0

X

Y

0.1
0.09
0.08
0.07
0.06
0.05
0.04
0.03
0.02
0.01
0
-0.01
-0.02

0.1
0.2
0.3

ONERA

MASCOTTE simulation at 1 Bar (A-1)

GH2 mass flow rate : 15 g/s
LOX mass flow rate : 50 g/s
EBUP = 2500
k-e model
C1 = 1.44
*C2 = 1.92*

*liquid volume fraction*

C1 = 1.2
C2 = 2.3

ONERA

MASCOTTE simulation at 1 Bar (A-1)

GH2 mass flow rate : 15 g/s
LOX mass flow rate : 50 g/s
k-e model

EBUP = 2500

EBUP = 32

ONERA

## MASCOTTE simulation at 1 Bar (A-1)

GH2 mass flow rate : 15 g/s
LOX mass flow rate : 50 g/s
k-e model
C1 = 1.2
C2 = 2.3

EBUP = 2500

Temperature
4273.41
4133.55
3993.7
3853.84
3713.98
3574.13
3434.27
3294.41
3154.56
3014.7
2874.84
2734.98
2595.13
2455.27
2315.41
2175.56
2035.7
1895.84
1755.99
1616.13
1476.27
1336.42
1196.56
1056.7
916.846
776.989
637.133
497.276
357.419
217.562

EBUP = 32

Temperature
4101.83
3972.56
3843.28
3714.01
3584.73
3455.46
3326.19
3196.91
3067.64
2938.36
2809.09
2679.81
2550.54
2421.27
2291.99
2162.72
2033.44
1904.17
1774.9
1645.62
1516.35
1387.07
1257.8
1128.53
999.251
869.977
740.703
611.429
482.155
352.881

ONERA

MASCOTTE simulation at 1 Bar (A-1)

EBUP = 32

k-e model (standard)
C1 = 1.44
C2 = 1.92

C1 = 1.2
C2 = 2.3

ONERA

MASCOTTE simulation at 1 Bar (A-1)

EBUP = 32

k-e model (standard)
C1 = 1.44
C2 = 1.92

C1 = 1.2
C2 = 2.3

ONERA

MASCOTTE simulation at 1 Bar (A-1)

EBUP = 32

k-e model (standard)
C1 = 1.44
C2 = 1.92

C1 = 1.2
C2 = 2.3

MASCOTTE simulation at 1 Bar (A-1)

EBUP = 32.

k-e model (standard)
C1 = 1.44
C2 = 1.92

C1 = 1.2
C2 = 2.3

MASCOTTE simulation at 1 Bar (A-1)

EBUP = 32

k-e model (standard)
C1 = 1.44
C2 = 1.92

C1 = 1.2
C2 = 2.3

ONERA

298

ONERA

# MASCOTTE simulation at 10 bars

MASCOTTE simulation at 10 bars (A-10)

GH2 mass flow rate : 23.7 g/s
LOx mass flow rate : 50 g/s
EBUP = 2500
k-e model
C1 = 1.44
C2 = 1.92

C1 = 1.2
C2 = 2.3

Temperature

| 4400 |
| 3980 |
| 3560 |
| 3140 |
| 2720 |
| 2300 |
| 1880 |
| 1460 |
| 1040 |
| 620 |
| 200 |

MASCOTTE simulation at 10 bars (A-10)

GH2 mass flow rate : 23.7 g/s
LOx mass flow rate : 50 g/s
EBUP = 2500
k-e model
C1 = 1.44
C2 = 1.92

liquid volume fraction

C1 = 1.2
C2 = 2.3

ONERA

MASCOTTE simulation at 10 bars (A-10)

GH2 mass flow rate : 23.7 g/s
LOx mass flow rate : 50 g/s
5 injection points
k-e model
EBUP = 2500

Temperature

4400
3980
3560
3140
2720
2300
1880
1460
1040
620
200

EBUP = 32

Temperature

4400
3980
3560
3140
2720
2300
1880
1460
1040
620
200

ONERA

Preliminary Results

- validation of the functioning of DLS (Lagrangian solver)

- results qualitatively in good agreement with experiments

- high sensitivity to turbulence

303

Work in progress

- Introduction of source terms for the equations of k and ε

- Introduction of the volume fraction of liquid in the equations

in prediction of :

    – calculation of dense regions of the two-phase flow (near the core)

    – Eulerian modeling of the the flow

ONERA

Conservation equations for the continuous phase

$$\frac{\partial}{\partial t}(\alpha\rho) + \frac{\partial}{\partial x_j}(\alpha\rho U_j) = \Gamma$$

$$\frac{\partial}{\partial t}(\alpha\rho U_i) + \frac{\partial}{\partial x_j}(\alpha\rho U_i U_j) = -\alpha\frac{\partial P}{\partial x_i} + \frac{\partial}{\partial x_j}(\alpha T_{ij} - <\rho\chi u_i'' u_j''>) + \mathbf{F_i} + \mathbf{I_i}$$

$$\frac{\partial}{\partial t}(\alpha\rho E) + \frac{\partial}{\partial x_j}(\alpha\rho H U_j) = -P\frac{\partial\alpha}{\partial t} - \frac{\partial}{\partial x_j}(\alpha Q_j + <\rho\chi h'' u_j''>) + \mathbf{S} + \mathbf{\Pi}$$

In bold : interfacial exchange terms between phases (→ modeled)

Work done : introduction of α in MSD

ONERA

Introduction of α in MSD : 1D validation

H2
$\rho U = 5.$
$T = 280$

p =97800

α : volume fraction of gas

ONERA

temperature

axial velocity

- analytical solution
- 50 cells. MSD
- 100 cells. MSD
- 200 cells. MSD

alpha. rho

alpha. P

Work to be done

- improvement of thermodynamics $\rightarrow$ better prediction of temperature

- improvement of turbulence by evaluating source terms for κ and ε $\rightarrow$ right length of flame

- other developments :

  – introduction of volume fraction of phases

  – secondary break-up and coalescence

  – evaporation at high pressure (above critical pressure of LOx)

- Eulerian modeling : two-fluid model ?

ONERA

Basic Research in Liquid Rocket Combustion at the Air Force Research Laboratory

**Doug Talley
Propulsion Sciences
and Advanced
Concepts Division**

27-28 May 1999

Required Injector Characteristics

- Complete combustion in the shortest possible length
  - Main injectors: performance *vs* weight tradeoffs
  - Preburners/GG's: downstream component interactions, eg, turbine blades, etc
- Acoustically stable
  - Chamber modes
  - Feed system coupling
- Chamber/wall compatibility
  - Heat transfer/cooling
  - Oxygen blanching

- Minimize pressure drop
- Throttling
- Ignitable; minimum ignition transients
- Cost, weight
- The "ilities:"
  - Reliability
  - Maintainability
  - Manufacturability
  - Durability
  - Operability

Facilities currently supporting basic research

Single element cold flow pressure facility

- All facilities designed to provide optical access at pressures to 2000 psi (136 atm).

Supercritical pressure facility

Subscale hot fire facility

Single element cold flow pressure facility

Gas simulants	$N_2(g)$, He(g)
Liquid simulant	$H_2O(l)$, others
Window Purge gas	$N_2(g)$, He(g)
N_2 mass flow rate	.20 lbm/s (.09 Kg/s)
He mass flow rate	.20 lbm/s (.09 Kg/s)
H_2O mass flow rate	4.0 lbm/s (1.8 Kg/s)
Max. test art. press.	2000 psi (136 atm)
Max. Fuel sim. press.	3000 psi. (204 atm)
Max. Ox sim. press.	3000 psi. (204 atm)

Windowed test chamber with 5.5" (14 cm) of axial injector travel and a linear translating injector stage with 5" (13 cm) total radial travel inside chamber.

Ability to simulate manifold cross velocities to 30 ft/s (9.1 m/s).

27 tube traversable mechanical patternator

Phase Doppler, Malvern, other diagnostics

Subscale hot fire facility

Fuel	H2(g), CH4(g)
Oxidizer	O2(g)
Purge gas	N2(g), He(g)
H2 mass flow rate	.15 lbm/s (.07 Kg/s)
CH4 mass flow rate	.25 lbm/s (.11 Kg/s)
O2 mass flow rate	1.0 lbm/s (.45 Kg/s)
N2 mass flow rate	.5 lbm/s (.23 Kg/s)
Water flow rate	16 lbm/s (7 Kg/s)
Max. system press.	2640 psi. (179 atm)

128 ch, 200 kbs scanning A/D
16 ch, 2 MHz per ch A/D, independently controlled
Central laser/optics room

Installing in 1999
. 2000 psi liquid hydrocarbon capability

2000
LOX capability

Gas/gas hardware

Supercritical pressure facility

Chamber	Stainless
Optical access	2 facing sapphire 13 cm dia windows
	2 facing slot-shaped quartz (12 x 1.3 cm)
Max chamb. press.	2000 psi (136 atm)
Chamb. temp.	473 K
Injected fluid	O2, N2, HC, and mixtures
Ambient fluid	N2, He, and mixtures
Injected mass flow rate	400 mg/s
Cryogenic cooler	85 K
Mass flow meters	up to 10,000 SLPM

━━ Air Force Research Laboratory ━━━━━

Pressure Capability Matches More Scaling Parameters

Atmospheric Pressure
Geometry Scaling=1.0
Velocity Ratio O/F=.084
Ma=0.25

Pc=416 psig
Geometry Scaling=1.0
Velocity Ratio O/F=.084
Ma=0.25
Momentum Ratio O/F=.079
Density Ratio O/F=29.2

AFRL/NASA study
Shear

Cox 1988

AFRL 1997

- **H2/O2 fuel preburner coax injector tests demonstrate reduced effectiveness of swirl on macro-scale mixing at pressure.**

Dense Spray Diagnostics

Strakey, et. al., ILASS Americas '98

- Goal - Extend existing diagnostic techniques into the dense spray regime where $N > 10^5$ cc^{-1}.
- The combination of a small probe volume and a flow splitter resulted in a dramatic improvement in PDPA volume flux measurements in a dense spray.

Area of Particle Imaged onto Receiver

Light Rays from Laser Beams

Receiver Lens

Legend:
- Conventional Probe / No Splitter
- Conventional Probe / With Splitter
- Small Probe / With Splitter
- Patternator

Flux(cc/s/cm 2) vs Radial Position (mm)

Two Sheet Correction for Laser Sheet Extinction

Talley, et. al., AIAA 96-0469

Two-sheet optics

- Flat Mirror
- Collimating Lens (Acrylic)
- Cylindrical Lens
- Beam Steering Device
- Beam Splitter

20 deg viewing angle corrected for perspective

Camera response*

$$G = KI\rho$$

Along a ray,

$$\frac{dG_l}{G_l} = \frac{dI_l}{I_l} + \frac{d\rho}{\rho}$$

$$\frac{dG_r}{G_r} = \frac{dI_r}{I_r} + \frac{d\rho}{\rho}$$

Beer's law scattering is the same in both directions at any dx. Thus

Adding,

$$\frac{dG_l}{G_l} + \frac{dG_r}{G_r} = 2\frac{d\rho}{\rho}$$

Independent of laser sheet intensity.

*G is gray level, I is laser sheet intensity, ρ is spray mass density, and K is a constant

Effect of Crossflow on Orifice Discharge Coefficients

Strakey, et. al., Atomization and Sprays, vol. 9, no. 1, 1998

D=1.19 mm, L/D=10, P_1=.69 MPa

Evolution of Mixing Layers in Transition from a Subcritical to a Supercritical State

Acknowledgements:
Bruce Chehroudi
Roger Woodward
Ed Coy

Overall Objectives

Determine the impact of thermodynamic state relative to the critical point on the transport and mixing of droplets, jets, and sprays

Issues

- Vanishing surface tension and heat of vaporization
- Equivalent gas/liquid densities
- Enhansed gas/liquid solubility
- Mixing induced critical point variations

PRESSURE VESSEL / DROPLET GENERATOR INTERFACE

Pressure Vessel Schematic

Raman Measurements

EXPERIMENTAL SET-UP

Low Reynolds Number N2 Jets

Woodward and Talley, AIAA 96-0468

into:

| N2 | N2 | N2 | N2/He, MR=3.9 |
| Pr=0.83 | Pr=1.03 | Pr=2.03 | Pr=2.03 |

Raman images of LN2 jet at 69 atm into (a) gaseous nitrogen and (b) helium

(a)　　　　　(b)

Transcritical Injection of LOX Droplets

Mayer et. al., J. Propulsion and Power, vol. 14, no. 5, 1998

Ambient: N2 @ 970 psig, 290K. O2 Injector Temperature: 177K.
Drops formed in chilled helium, nitrogen flowing across stream.
Sequence corresponds to increasing distance downstream.

N_2 into N_2

Back-illuminated images. Chamber is at a fixed supercritical temperature of 300 K but varying sub- to supercritical pressures ($P_{critical}$ = 3.39 MPa). Re = 25,000 to 75,000. Injection velocity: 10-15 m/s. Froud number = 40,000 to 110,000. Injectant temperature = 99 to 120 K.

PRESSURE DEPENDENT MIXING LAYER STRUCTURE

Nitrogen/nitrogen system (P_{cr} = 3.39 MPa, T_{cr} = 126 K)

T_{inj} = 128 K, T_{amb} = 300 K, mass flow = 350 mg/s

Pr=0.91   Pr=1.22   Pr=2.71

| *Low Pres.* *Subcritical* Droplets | *Mod. Pres.* *Supercritical* Ligaments | *High Pres.* *Supercritical* Gas layers |

— Air Force Research Laboratory —

Sub- and Super-critical Mixing Layer Physics

Chehroudi et. al., AIAA 99-0206, AIAA 99-2489

——— Steady Diesel-Type Spray L/D=4	- - - - Steady Diesel-Type Spray L/D=85	○ N2 jet into N2 L/D=200 (*)
◇ N2 jet into N2 Darkcore (*)	◆ Cold He jet into N2; L/D=200 (*)	■ Cold N2 jet into He; L/D=200 (*)
✖ Brown & Roshko (He/N2)	△ O2 jet into N2; L/D=200 (*)	□ O2 jet into N2; Darkcore (*)
- - - - Theory (Papamoschou&Roshko)		

319

Characteristic Times

- Characteristic bulge formation time (τ_b) at the jet interface (Tseng et al.): $(\rho_l L^3/\sigma)^{1/2}$; ρ_l , L, σ are liquid density, characteristic dimension of turbulent eddy, and surface tension, respectively.

- Characteristic time for gasification (τ_g) (D-square law): D^2/K; D and K are drop diameter and vaporization constant.

- A Hypothesis: If these two characteristic times (calculated for appropriate length scales) are comparable then an interface bulge may not be separated as an unattached entity (onset of the gas-jet behavior at supercritical condition)

Similar equation format for different cases

- Theoretical isothermal liquid spray growth rate (θ_s) based on Orr-Sommerfeld equation and stability analysis to find the wavelength of the most unstable interface wave:
  $\theta_s \cong 0.27 [0 + (\rho_g/\rho_l)^{0.5}]$

- Papamoschou/Rashko theory for incompressible variable-density gaseous mixing layer/jet:
  $\theta_{P/R} \cong 0.17 [1 + (\rho_g/\rho_l)^{0.5}]$

- Dimotakis theory for incompressible variable-density gaseous mixing layer/jet:
  $\theta_D \cong 0.212 [0.59 + (\rho_g/\rho_l)^{0.5}]$

- ALL HAVE THE SQUARE ROOT OF DENSITY RATIO AND THE SAME EQUATION FORMAT

Correlation

Based of the information of the previous slide the following correlation is proposed for both sub- and supercritical measured growth rates:

$$\theta_{Ch} \cong 0.27 \left[\left(\tau_b/(\tau_b + \tau_g) \right) + (\rho_g/\rho_i)^{0.5} \right] \qquad \text{N2 into N2}$$

$$\theta_{Ch} \cong 0.27 \left[\left(\tau_b/(\tau_b + \tau_g) \right) + \left\{ (\rho_g/\rho_i) - 0.8(\rho_g/\rho_i) \right\}^{0.5} \right] \qquad \text{N2 into He}$$

Note:

- For isothermal liquid case: $\tau_g \gg \tau_b$ and $\tau_g \rightarrow \infty$. It then collapses to the isothermal spray case.
- For subcritical the $(\tau_b/(\tau_b + \tau_g))$ is calculated until it reaches 0.5. After that it is maintained constant at 0.5 for supercritical jet. The transition point is found to be approximately when $(\tau_b/(\tau_b + \tau_g)) \cong 0.5$.
- Only a horizontal axis variable transformation is needed to fit with the N_2-into-He experimental growth rate data.

Empirical Correlation Results

Fractal Dimension vs Reduced Pressure

Chehroudi et. al., AIAA 99-2489

Summary and Conclusions

- Structural differences in cryogenic jets have been observed below and above the thermodynamic critical point.
- Liquid-Jet like appearance occurs up to near the critical point, similar to second wind-induced liquid jet breakup regime.
- Gas-jet like appearance occurs above the critical point. No drops are observed.
  - Supercritical spreading rate measurements agree quantitatively with incompressible variable density mixing layer experiments and theory.
  - Supercritical fractal dimensions agree quantitatively with gas jet measurements.
- New and existing mixing layer growth rate experiments and theory have for the first time been consolidated into a single plot as a function of density ratio, where the density ratio spans three orders of magnitude.
- A physical mechanism and correlation have been proposed to describe the transition from spray to gas jet behavior.

Instantaneous Images of Sub- and Supercritical Impinging Jets

N_2 into N_2
($P_{critical}$ = 3.39 MPa; T_c = 126.2 K)
(P_{ch} = 5.5, 4.2, 3.5, 2.8, 2.5, 2.1, 1.5, 0.8 MPa; from upper left to lower right)
(Re=25,000 to 70,000; injection velocity:10-15 m/s)

Instantaneous Images of Sub- and Supercritical Impinging Jets

N2 into N2
(Pcritical = 3.39 MPa; Tc = 126.2 K)
(Pch = 5.5, 4.2, 3.5, 2.8, 2.5, 2.1, 1.5, 0.8 MPa; from upper left to lower right)
(Re=25,000 to 70,000; injection velocity:10-15 m/s)

Opportunities for Future Research

1990's at AFRL
- High pressures, "steady."
- Gas/gas injection

Future: 1990's topics remain relevant. Add:
- Injector/chamber interactions
- Transients
  - Organized
  - Un-organized
- Revolutionary cycles
  - Pulsed detonation propulsion
  - Combined cycle

THE STRUCTURE OF CRYOGENIC JET FLAMES INFERRED FROM EXPERIMENTS

A. Tripathi,[*], M. Juniper,[†], P. Scouflaire,[‡]
D. Durox,[§], C. Rolon,[%], S. Candel,[¶]
EM2C Laboratory, CNRS, Ecole Centrale Paris
F-92295 Châtenay-Malabry, France
L. Vingert,[°] and M. Habiballah,[◁]
ONERA, 91120 Palaiseau, France

Abstract

This article reports new experimental results on cryogenic jet flames formed by a coaxial injector. This element fed with liquid oxygen and gaseous hydrogen is placed in a square combustion chamber equipped with quartz windows. The flame is studied with a set of optical methods : light emission from OH radicals and from H_2O molecules, laser induced fluorescence of OH, elastic scattering from the liquid oxygen jet, shadowgraphy. These techniques are used to examine flame spreading near the injection plane. The instantaneous flame location was previously described with simultaneous light elastic scattering images and laser induced fluorescence of OH. More recently, the mean flame structure was extracted from average emission images treated with Abel's transform. This numerical transformation provides the local volumetric light emission of the species being imaged. Previous studies concerned radiation from OH radicals. New measurements have been carried out by imaging a band of wavelengths which characterizes H_2O radiation. The transformed images of OH yield a structure which is indicative of the location of reaction while the transformed images of H_2O radiation portray the distribution of products or temperature in the flame. This combined imaging provides further information on the flame structure. Additional clues on

the flow near the injector are provided by shadowgraph images. Systematic experiments have been carried out by varying the operating parameters and the chamber pressure. Effects of LOX tube recess have also been examined at various pressures and for a set of operating conditions. The data provide a unified picture of the flame in the vicinity of the injection plane. Results may be used to describe effects of pressure and analyze the modification in the flame pattern induced by recess. The experimental investigation serves as a basis for modeling efforts described in a companion paper and in a previous article cited in reference.

This work was carried-out with support from CNES, SEP, ONERA and CNRS.

Figure 1: Cryogenic combustion facility

1   Experimental Facility

The experimental facility, called Mascotte, shown in Figure 1, is situated at ONERA, Palaiseau. It consists of a coaxial injector in which an annulus of hydrogen at high velocity is injected around a jet of liquid oxygen at low velocity. The dimensions of the injector are in the same range as those used in the Vulcain rocket motor of Ariane 5. A pressure of 60 bar can be maintained

Figure 2: Low pressure injector   High pressure injector

within the chamber, which is square. The first few centimetres of the flame can be examined through quartz windows on each side of the chamber.

Cold flow studies have shown the importance of the momentum ratio, defined as $J = \rho_g u_g^2 / \rho_l u_l^2$, in determining jet break-up mechanism. This parameter is kept constant on changing pressure, which requires a reduction of the hydrogen flow cross-section at high pressure. The injector geometries are shown in Figure 2.

Our laboratory has carried out five series of experiments on Mascotte, the details of which are summarised in Table (1). Versions VO1 and VO2 of the combustion facility permitted pressures up to 10 bar. At these pressures, the flame position was determined using planar laser-induced fluorescence. The liquid surface position was found simultaneously by observing the elastic scattering of the laser sheet. It is known that LIF and elastic scattering are less effective at high pressure, as well as being technically complicated. It is more suitable to use visualisation techniques based on emission and shadowgraphy. These techniques are simpler, but quite effective.

2   Experiments at 1, 5 and 10 bar

A diagram of the apparatus used for planar laser-induced fluorescence is shown in Figure 3. The laser sheet excites OH radicals in the $Q_1(6)$ band, which decay emitting a photon at a different wavelength. The emission intensity is found to be almost independent of temperature in a range between 1500 and 3000K. The signal then mainly depends on the concentration of hydroxyl (OH) radicals. These radicals are an intermediate in the global reaction of H_2 with O_2 and regions of high level of OH mark the flame front. Filters exclude all but the fluorescence wavelength and thus the flame position is recorded by an intensified CCD camera. Simultanously, a second CCD camera records the scattering of the laser sheet by the liquid surface.

Version of rig	Dates	Pressure	Visualisation technique
VO1 VO2	3 series of tests	1,5,10 bar	Laser-induced fluorescence Elastic scattering OH emission
VO3	June 1998 March 1999	10,60 bar	OH emission H2O emission Spectroscopy Shadowgraphy

Table 1: Experiments on MASCOTTE by Laboratoire EM2C

Figure 3: Set-up for simultaneous Planar Laser-induced Fluorescence and Elastic Scattering imaging

Figure 4: Schematic diagram of the flame between 1 and 10 bar, below the critical pressure of oxygen

This gives the position of the jet and droplets.

The flame front [1] in red, is not seen in the top half of the images because very little of the laser sheet passes undisturbed through the jet. The bottom half shows that the flame front is highly wrinkled. Scattering from the liquid surface is shown in blue. Further from the injector, the intensity is lower, which is due to the fact that the droplets are smaller. Also the thicker droplet cloud masks the sheet of droplets which are illuminated by the laser. The scattered signal is outside the dynamic range of the CCD camera.

Some important points can be made about the flame shape. The flame starts at the oxygen injector lip and then burns extremely close to the liquid jet. The liquid jet breaks up into a dense cloud of droplets. The inter droplet distance divided by the droplet diameter is estimated to be around $b/d = 6$. Because the cloud is so dense, external group combustion takes place and the flame surrounds but does not penetrate the cloud. A schematic diagram of the flame shape between 1 and 10 bar is shown in Figure 4.

3 Application of The Abel Inversion

Given the reduced signal level of PLIF at high pressures, other techniques were considered. One of these is the Abel inversion of natural emission images. The spectrum of the flame shows that is it possible to isolate the natural emission of OH^* and H_2O^* radicals, as shown in Figure 5.

The Abel inversion is frequently used to obtain the radial intensity distribution of an axisymmetric object from a projection on a plane placed on

---

[1]Colour images can be found in Candel et al: "Experimental investigation of shear coaxial cryogenic jet flames," *Journal of Propulsion and Power*, Vol. 14 , 1998, pp. 826-834

Figure 5: Spectrum of the flame at 10 bar a) $300 < \lambda < 400 nm$; UV region
b) $500 < \lambda < 700 nm$; green-red region

Figure 6: Principle of the Abel inversion, the radial structure is deduced
from the projected distribution

Figure 7: Instantaneous image of the OH* emission of a turbulent flame, 10 bar, $J = 14.5$

Figure 8: Averaged images of a turbulent flame. This gives the OH* Intensity × Residence fraction summed along the line of sight. 10 bar, $J = 14.5$

the side. The principle is shown in Figure 6. The axisymmetric distribution is assumed to be made up of a series of co-centric rings. To calculate the contribution of an inside ring, the contribution of the rings outside it is subtracted from the cumulative image along the line of sight. Working from the outside to the inside, this enables the contribution from each ring to be determined. Around the axis, the process is particularly sensitive to noise.

Care is required when applying the Abel transform to a non-axisymmetric turbulent flame, as indicated in Figure 7. Averaging over several images gives an axisymmetric field: intensity × residence fraction, which is summed over the line of sight, as in Figure 8. The residence fraction corresponds to the fraction of the time that the flame spends at a particular point, on average. The Abel inversion can be applied to this field, giving a slice through the injector plane of the intensity of OH* radical natural emission × residence fraction, Figure 9. This can be compared with the average of the PLIF

331

Figure 9: The Abel inversion of the averaged images. This gives a slice of the OH* Intensity × the Residence fraction. 10 bar, $J = 14.5$

images, which gives a slice of the intensity of OH radical stimulated emission × residence fraction, as in Figure 10. This indicates a slightly wider high intensity region than that found in the Abel-inverted images. However, this is to be expected because the PLIF images show all OH radicals, wheras the Abel-inverted images show only the excited OH* radicals. The OH* radical has a short lifetime compared with characteristic flow times and will not be seen away from the flame front. However, it is likely that a small quantity of OH radicals will exist in the high temperature regions around the flame. The corresponding intensity of these radicals on the PLIF images will be small but the residence fraction will be high. This accounts for the thick flame zone on the averaged PLIF images.

To compare the averaged images more exactly it is necessary to make the reasonable assumption that the regions where OH concentration is high correspond to the regions of OH*. Thus when the low intensity regions of the PLIF images are removed and the images averaged, the result should be similar to the intensity of OH* × Residence fraction. The comparison turns out to be excellent. Figure 11 shows the positions of maximum intensity for the Abel inverted images and for the average of the PLIF images.

Whenever the Abel inversion is used, it should be remembered that the slices are of emission intensity × residence fraction, rather than just intensity. The highest values are usually seen near the injector, where the residence fraction is high. The Abel-inverted images give a good idea of the change in the average flame shape when injection conditions are altered. It should also be noted that the Abel inversion assumes that no light is absorbed or deflected by the flame.

The Abel-inverted images of OH* and H_2O^* radical emission are shown in Figures 12 and 13. To a first approximation, the intensity of OH* emission

Figure 10: Averaged PLIF images. This gives a slice of the OH Intensity ×
the Residence fraction

Figure 11: Position of maximum intensity of the Abel-inverted emission images compared with that of the average PLIF images

is a function of the reaction rate and the intensity of the thermally excited reaction product H_2O^* is a function of temperature. From these images, taken with an oxygen tube recess of $1 \times d_{LOx}$, it can be seen that the maximum H_2O^* emission is somewhat further downstream than the maximum OH^* emission, as would be expected.

Figure 12: OH^* Intensity $\times$ Residence fraction at 10 bar in a slice through the axial plane

Figure 13: H_2O^* Intensity $\times$ Residence fraction at 10 bar in a slice through the axial plane

4 Supercritical effects

The critical point of oxygen is 50.8 bar, 155K. The Pressure-Temperature phase equilibrium diagram is shown in Figure 14. Conditions achieved in Mascotte version VO1, VO3 and in the Vulcain motor are also shown in this figure. The important point is that the oxygen will have no definite phase

Figure 14: Pressure-Temperature diagram for oxygen, with the operating points of Mascotte versions VO1, VO3 and the Vulcain rocket motor

boundary in VO3 and in Vulcain, unlike the low pressure VO1. This is likely to lead to differences in jet and droplet break-up, since surface tension is a factor at low pressure. Above the critical pressure, two gases of very different density mix.

Studies by Delplanque and Sirignano indicate that the oxygen jet will have a dense, liquid-like core, where the temperature is low. Towards the edge of the jet, where the temperature is higher, the oxygen will be supercritical. There will be very high temperature and density gradients in this region, but no discontinuous surface. Around the critical point, small temperature variations lead to large density variations. The fluid becomes almost opaque to incident light.

5 Experiments at 60 bar

The apparatus for flame and jet visualisation at high pressure is shown in Figure 15. The techniques used are listed below:

- Spectroscopy: The spectrum of the flame at 60 bar was obtained over the course of the campaign. It showed that OH* radical emission is well isolated by the filters.

- Images of OH* radical emission

335

Figure 15: Experimental set-up used in the high pressure tests

Figure 16: OH* radical emission at low pressure ($P \approx 30$bar)

- Shadowgraphy: In order to eliminate as much of the flame's natural emission as possible, the ICCD camera had a very short exposure time (300ns) and was synchronised with the spark lamp. In addition, after passing through the chamber, the light was focussed through an iris. This cut out a large proportion of the flame's natural emission. Finally, the light was filtered to remove as much natural emission as possible, while passing the wavelength in which the spark was most intense, between 420 and 500 nm.

Some close-up images of the near-injector region were also taken.

The far-field results are shown in Figures 16 to 19. During each run the pressure took 30 seconds to build up to 60 bar and then was stable for 7 seconds. Thus images at low pressure were obtained, but it should be stressed that the conditions were not steady and do not correspond to those of version

Figure 17: OH* radical emission at 60 bar

Figure 18: Shadowgraphy at low pressure ($P \approx 30$bar)

Figure 19: Shadowgraphy at 60 bar

Figure 20: Emission above 400nm at low pressure, near injector

VO1 and VO2 of Mascotte. It is clear from the shadowgraphy images that the shape of the oxygen jet is different at high pressure. Droplets are no longer visible and it is more clumpy and stringy. Emission is more intense at high pressure and, compared with the stable images at 1,5 and 10 bar from version VO1 and VO2, the flame expands less rapidly.

The near-field emission images are shown in Figures 20 and 21. The flame is stabilised just behind the oxygen injector lip. This effect has also been noted by Mayer and Tamura on the cryogenic combustion facility in Japan, on which the diameter of the oxygen jet is smaller and the oxygen lip proportionally much larger, figure (22). The near-field shadowgraphy images require some explanation. Typical samples are shown in Figures 23 and 24. Where the light from the spark lamp has been deflected only slightly, a shadowgraphy effect can be seen, characterised by a light and a dark band. Where the light has been deflected more, it is not captured by the lens and a schlieren effect can be seen. This is simply a dark region. A shadowgraphy effect can be seen at the outside edge of the hydrogen jet and in some parts of the gaseous phase in the low pressure image. The 60 bar image is almost entirely determined by schlieren effects. Light is deflected by refractive index gradients perpendicular to the ray direction. Refractive index gradients will be large at the edge of the oxygen jet and at the edges of the flame. If the flame is very close to the oxygen jet, the two will be indistinguishable.

The images show the expansion of the hydrogen annulus, the wake of the oxygen tube lip, the position of the oxygen jet (or the inner edge of the flame) and the outer edge of the flame. An image taken by Mayer and Tamura is

Figure 21: Emission above 400nm at 60 bar, near injector

Figure 22: OH* radical emission at 45 bar from Mayer and Tamura, *Journal of Propulsion and Power* Vol 12, 1996

Figure 23: Shadowgraphy at low pressure ($P \approx 30$ bar), near injector

Figure 24: Shadowgraphy at 60 bar, near injector

Figure 25: Shadowgraphy at 45 bar, from Mayer and Tamura, *Journal of Propulsion and Power* Vol 12, 1996

shown in Figure 25 for comparison.

An Abel inversion of the near-injector emission images at 60 bar is shown in Figure 26. This will not be valid in the central region where the jet partially shields the far side of the flame. The images show the proximity of the flame to the oxygen jet. The bright spot behind the oxygen injector lip is smaller and less intense than that observed by Mayer and Tamura on the 1mm diameter injector.

Important points can be made about the flame shape at 60 bar. The flame and the oxygen jet are extremely turbulent. The jet breaks up into packets, rather than droplets. The flame is stabilized on the oxygen injector lip in a recirculation zone and then grows in intensity. This is schematized in Figure 28.

6   Conclusion

Structure of subcritical and supercritical cryogenic flames are examined using imaging techniques. The flame is stabilized in the near vicinity of the oxygen tube and initially spreads around the oxygen core as a corrugated surface. The momentum ratio has a decisive effect in the subcritical cases. It has a less visible effect in the supercritical case but this aspect needs further study. Subcritical and supercritical flames differ notably in their structure and corresponding rate of expansion.

Figure 26: Abel inversion of the near-injector emission images

Figure 27: Abel transform of the averaged images at 60 bar

Figure 28: Schematic representation of the flame shape at 60 bar

References

[1]Herding, G., Snyder, R., Scouflaire, P., Rolon, C. and Candel, S., "Emission and laser induced fluorescence imaging of cryogenic propellant combustion," *Proceedings of the Conference on Propulsive Flows in Space Transportation Systems* (Bordeaux, France), CNES, 1995. pp. 1-14

[2]Snyder, R., Herding, G., Rolon, C. and Candel, S., "Analysis of flame patterns in cryogenic propellant combustion," *Combustion Science and Technology*, Vol. 124 , 1997, pp. 333-373.

[3]Herding, G., Snyder, R., Scouflaire, P., Rolon, C. and Candel, S., "Flame stabilization in cryogenic propellant combustion," *26th Symposium (International) on Combustion*, The Combustion Institute, Pittsburgh, 1996, pp. 2041-2047.

[4]Herding, G., Snyder, R., Rolon, C. and Candel, S., "Investigation of cryogenic propellant flames using computerized tomography of OH emission images," *Journal of Propulsion and Power*, Vol. 13, pp. 146-151 , 1998.

[5]Brummund, U., Cessou, A., Oschwald, M., Vogel, A., Grisch, F., Bouchardy, P., Pealat, M., Vingert, L., Habiballah, M., Snyder, R., Herding, G., Scouflaire, P., Rolon, C. and Candel, S., "Laser diagnostics for cryogenic propellant Combustion Studies," *Proceedings of the 2nd International Symposium on Liquid Rocket Propulsion* (Chatillon, France), 1995. pp. 19.1-19.22.

[6]Candel, S., Herding, G., Snyder, R., Scouflaire, P., Rolon, C., Vingert, L., Habiballah, M., Grisch, F., Pealat, M., Bouchardy, P., Stepowsky, D., Cessou, A. and Colin, P., Experimental investigation of shear coaxial cryogenic jet flames," *Journal of Propulsion and Power*, Vol. 14 , 1998, pp. 826-834.

[7]Kendrick, D., Herding, G., Scouflaire, P., Rolon, C. and Candel, S., Effects of recess on cryogenic flame stabilization," *In press, Combustion and Flame* 1999.

[8]Tripathi, A., Juniper, M., Scouflaire, P., Rolon, C., Durox, D. and Candel, S., LOX tube recess in cryogenic flames investigated using OH and H2O emission," AIAA paper 99-2490, 1999.

[9]Barbeau, B., Lacas, F., Rymer, G. and Candel, S., Cryogenic flame modeling in a coaxial flame configuration," AIAA paper 99-0207, 1999.

Coherent anti-Stokes Raman Scattering (CARS)
Measurements in a Shear-Coaxial Cryogenic Jet Flame

P. BOUCHARDY, F. GRISCH

ONERA - LAERTE
Département Mesures Physiques
Diagnostics optiques et plasmas
Fort de Palaiseau - 91120 PALAISEAU

W. CLAUSS

German Aerospace Research Establishment (DLR)
Germany

CNES01a

DLR

ONERA

Objective

- **Improve design and optimization of high performance LOX-GH2 Rocket Engines**

- **Development of optical Diagnostics for combustion studies at high pressure (10 MPa)**

  ⟶ **CARS technique**
    Instantaneous measurements of temperature - concentration

  ⟶ **Heat Release**
    Turbulence mixing of hot reaction products and Hydrogen

CNES02a

DLR

ONERA

MASCOTTE Combustion chamber

10 bar Facility

High Pressure Facility

ONERA

Multiplex CARS technique on MASCOTTE

- Detection of H_2 (fuel species)

- Single-shot measurements at 5 Hz frequency

⇨ 150 measurements during a run ($\Delta t = 30s$) at 1 bar
100 measurements (20 s) at higher pressure

- Temporal resolution: 10 ns

- Planar BOXCARS arrangement for H_2 with 200 mm focal lens

⇨ probe volume: 1.2 mm-long × 100 µm diameter

ONERA

346

The CARS technique
(coherent anti-Stokes Raman spectroscopy)

● Three laser beams are applied simultaneously
to the gas mixture
- two pump beams
- one probe beam

- A new laser beam is created

- Its amplitude is strong when the difference
$(\omega_p-\omega_s)$ matches a Raman frequency ω_v

● **Multiplex CARS spectroscopy**

- Use of a monochromatic laser for ω_p
and a broadband dye laser for ω_s

- Instantaneous Measurements

- Spatially Resolved Measurements

CNES03a

DLR

ONERA

Multiplex CARS technique on MASCOTTE

- Detection of H_2 (fuel species)

- Single-shot measurements at 5 Hz frequency

⇨ 150 measurements during a run (Δt=30s) at 1 bar
100 measurements (20 s) at higher pressure

- Temporal resolution: 10 ns

- Planar BOXCARS arrangement for H_2 with 200 mm focal lens

⇨ probe volume: 1.2 mm-long × 100 μm diameter

CNES05a

DLR

ONERA

Experimental CARS setup

ONERA

Two-Phase Flow Effect
on the single-shot H$_2$ CARS spectra

X= 80 mm, Y = 5 mm, P = 1 bar

ONERA

Temperature measurement on H_2 at atmospheric pressure

Single-shot spectrum of H_2

T= 1290 ± 30 K

slope $\propto 1/T$

Boltzmann diagram

$\gamma_{doppler} \gg \gamma_{collisional}$ for all rotational lines

CNES06a

DLR

ONERA

Single-shot temperature *versus* time at 1 bar

X=80 mm

X=215 mm

X=180 mm

X=250 mm

Position: Y=20 mm

X: axial position from the injector, Y: radial position from the flow axis

CNES12a

DLR

ONERA

349

P.D.F. of single-shot temperature at 1 bar
Position: Y=20 mm

mean temperature and standard deviation

P.D.F. of single-shot temperature at 1 bar
X=180 mm from the injector

mean temperature and standard deviation ?

Temperature Profile at Y=20 mm
P=1 bar

Condition A: 50 g/s LOX, 15 g/s H_2
Condition C: 50 g/s LOX, 10 g/s H_2

ONERA

High pressure condition

- CARS line depends on the linewidth γ (Doppler + collisional)

- Collisional broadening + Dicke effect become significant.

- Dependance on the rotational state J

- Influence of the collisional partners for H_2 (H_2, O_2, H_2O)

Single-shot spectrum at 10 bar

→ **Impossibility to use the Boltzmann Diagram Technique**

ONERA

Collisional Linewidths for H_2-H_2 and H_2-H_2O

H_2-H_2

Courtesy of X. Michaut and H. berger
(University of Dijon)

H_2-H_2O

$$\gamma = C_{H2}\,\gamma_{H2\text{-}H2} + C_{H2O}\,\gamma_{H2\text{-}H2O}$$

ONERA

CNES08a

DLR

Temperature measurement at high pressure

- Temperatures are deduced by fitting experimental spectra with the theoretical ones calculated for different temperatures and for different molar fractions of H_2 and H_2O

- Effects of O_2 are merged with those of H_2
  (same collisional behavior of H_2-H_2 and H_2-O_2)

- The fitting technique used is a simple least squares where the error function is given by

$$F = \sum \omega_j\,(I_j^{exp} - I_j^{theory}(T, x_{H2}, x_{H2O}))^2$$

$$x_{H2} = 1 - x_{H2O} \text{ by assumption}$$

CNES09a

DLR

ONERA

High Pressure H₂ CARS spectra

P= 30 bar

P= 65 bar

Temperature evolution *versus* pressure

Condition C

Radial position: 15 mm from the flow axis

Principle of measurement

- Simultaneous detection of two species: H_2 and H_2O

H₂ CARS spectrum   H₂O CARS spectrum

- Data processing

  - H_2O concentration estimated from the intensity of the H_2O CARS spectra
  - Species composition for the collisional linewidth can be estimated
  - Temperature deduced from the H_2 and H_2O spectral profiles

ONERA

DLR

Results

- Simultaneous detection of H_2 and H_2O using CARS have been performed for pressures up to 65 bar.

- H_2O CARS spectra

- Data processing still in progress (recent experiment)

ONERA

DLR

Conclusion

- Detection of H_2 (and H_2O) using CARS have been successfully performed for pressures up to 65 bar in a cryogenic combustor.

- Temperature and concentration can be deduced from the experimental CARS signals

- Data base for the validation of combution solvers

- Measurements will be performed on the P8 combustor (DLR) at 60 bar next year

DLR

ONERA

Statistical Investigation

of the Turbulent Flame Geometrical Structures

in a Liquid Oxygen / Gaseous Hydrogen

Shear-Coaxial Jet

Armelle CESSOU, Pascal COLIN, Denis STEPOWSKI

CORIA UMR 6614
CNRS - Université & INSA de Rouen
Place Emile Blondel
76821 Mont Saint Aignan, France

co⟋⟍ia
UMR 6614
CNRS - UNIVERSITE et INSA de ROUEN

Context

- rocket engine application

- cryogenic propellant combustion facility :

    MASCOTTE test bench of ONERA

- developed for better understanding of physical phenomona encountered in rocket engines :
    - *atomization*
    - *vaporization*
    - *turbulent mixing*
    - *two-phase combustion*

- Investigation by planar laser induced fluorescence

co⟋⟍ia
UMR 6614
CNRS - UNIVERSITE et INSA de ROUEN

Investigated Area

Flame Description

- **Flame always anchored at the lip of the injector**
- **Non-premixed character**
- **conserved scalar : mixture fraction**

$$Z = \frac{\nu Y_F - Y_O + Y_O^\infty}{\nu Y_F^\infty + Y_O^\infty}$$

• **Description : constant-property surface**

• **Hyp. : infinitely fast chemistry** $\Rightarrow$ flame at stoichiometric mixture

constant-property surface $Z = Z_s$ $\Rightarrow$ **Flame**

Flame Description

| • chemistry decoupled from turbulence |

mean reaction rate p.u.v. ← $\overline{\dot{\omega}}_k = V_k\overline{\Sigma}$

mean reaction rate p.u.a. ← → **flame surface p.u.v.**

- local geometry of constant-property surface
  - *presence probability*
  - *normal to the surface*
  - *curvature*
  - *flame surface production*

Operating Conditions

Point	m_l g/s	m_g g/s	P bar	T_{GH2} K	V_{lox} m/s	V_{GH2} m/s	Re_l $\times 10^3$	J	We $\times 10^3$	image number
C1	50	9.5	1	289	2.18	620	67	6	12.5	151
C1p	50	9.5	8	289	2.18	163	67	3.2	6.5	182
F1	50	9.5	1	94	2.18	419	67	8.1	16.9	274

Experimental Set-up

Fluorescence Scheme

- **broadband ArF laser, 193 nm**

- **predissociative fluorescence of O_2**

- **hot vibrational bands**
  (v'=0, v"=4)
  (v'=1, v"=7)
  (v'=2, v"=10)
  (v'=3, v"=15)

- **Effective absorption cross section**
- **Fluorescence efficiency**
} **strongly increase with temperature**

Instantaneous Image

hot O$_2$ vapor

liquid O$_2$

H$_2$

LO$_2$

H$_2$

0 19 53   87 121 155 189 218 255

bottom contourline

co**R**ia
UMR 6614
CNRS - UNIVERSITE et INSA de ROUEN

Flame Identification

- reverse configuration
  laser irradiance not altered
  before reaching the flame

- at adiabatic flame temperature
  detection limit : Z = 0.109
  while Z$_s$ = 0.11

- **Hyp. : infinitely fast chemistry for H$_2$/O$_2$**

bottom outline of fluorescence
called ⟹ **flame**

co**R**ia
UMR 6614
CNRS - UNIVERSITE et INSA de ROUEN

Contourline Determination

instantaneous image

- Binarization $S_f >$ threshold $\Rightarrow S = 100$
  $\qquad\qquad\qquad S_f <$ threshold $\Rightarrow S = 0$
- median filter (3 x 3)
- contourline detection

coRia
UMR 6614
CNRS-UNIVERSITE et INSA de ROUEN

High frequency filtering

unsmoothed

smoothed, 800 μm

- sampled at evenly spaced intervals

$$ds = \sqrt{dx^2 + dy^2}$$

- smoothed through a gaussian filtering (800 μm)

coRia
UMR 6614
CNRS-UNIVERSITE et INSA de ROUEN

High and Low Frequency Filterings

high freq.	low freq.
$800 \mu m$	profile length

Presence Probability

- **mesh 0.25 x 0.25 mm²**

- **$x < d_i$ sharp distribution**

- **$x < 2d_i$**

  flame bows

  large distribution

363

Length Increase

length increase / d_i

1.2

0.8

0.4

0.0

b

a

1   2   3   4   5

x/d_i

a : flapping
b : flapping + wrinkling
—— C1
—— C1p
—— F1

Curvature

F_1

pdf

0.6

0.4

0.2

0.0

$x = d_i$

$x = 3d_i$

$x = 5d_i$

0.6

0.4

0.2

0.0

pdf

-6 -4 -2 0 2 4 6

-4 -2 0 2 4 6

-4 -2 0 2 4 6 8

mm^{-1}

mm^{-1}

mm^{-1}

$$h_i = \frac{\dot{x}(s_i)\ddot{y}(s_i) - \dot{y}(s_i)\ddot{x}(s_i)}{\left(\dot{x}^2(s_i) + \dot{y}^2(s_i)\right)^{3/2}}$$

Flame Surface Density

$$\overline{\Sigma}(\underline{X}, Z_{st}) = f_Z(Z_{st}; \underline{X}) \cdot \langle \|\nabla Z\| \, Z_{st}; \underline{X} \rangle$$

$$dl(u, v, DX, DY, Z) = DX \cdot \sin(\vec{u}, \vec{x}) + DY \cdot \cos(\vec{u}, \vec{x})$$

$$\overline{\Sigma}(\underline{X}, Z_{st}) = P\left(Z_{st} < Z < Z_{st} + \langle dZ | Z_{st} \rangle; \underline{X}\right) \cdot \left\langle \frac{1}{dl} \middle| Z_{st}; \underline{X} \right\rangle$$

$$\Sigma$$

- $\Sigma = P \times \langle 1/dl \| Z_s \rangle$
- mesh 0.25 x 0.25 mm^2
- x < 2d$_i$

  Σ underestimated

from

$$\left\langle \frac{1}{dl} \middle| Z_{st}; \underline{X} \right\rangle = \left\langle \frac{1}{DX \times dy/ds + DY \times dx/ds} \right\rangle$$

0.02 0.47 0.92 1.37 1.82 2.2

Comparison

$$\overline{\Sigma}(\underline{X}, Z_{st}) = \langle dl | Z_{st}; X \rangle / (DX \cdot DY)$$

$$\overline{\Sigma}(\underline{X}, Z_{st}) = P(Z_{st} < Z < Z_{st} + \langle dZ | Z_{st} \rangle; \underline{X}) \cdot \left\langle \frac{1}{dl} \middle| Z_{st}; \underline{X} \right\rangle$$

0.02 0.32 0.62 0.92 1.22 1.52

Conclusion

- – **reverse configuration**
  (oxygen within the flame envelope) } **stoichiometric iso-surface**
  – **O_2 fluorescence**

- **statistical description of flame surface properties**

→ **validation tools for numerical modeling**

Acknowledgment

- **GDR «Combustion dans les moteurs fusées» (CNES, SEP, CNRS, ONERA)**

- **M. Habiballah, L. Vingert, A. Mouthon, R. Barraud of ONERA (MASCOTTE test bench)**

SOME POSSIBLE CONSEQUENCES OF BIFURCATIONS IN COMBUSTORS

F.E.C. Culick

California Institute of Technology

~ ~ ~

International Workshop on Research Status and Perspectives in Liquid Rocket Chamber Dynamics

~ ~ ~

Held at CNES, 1 Place Maurice Quentin,
Paris, France

27–28 May 1999

OUTLINE

I INTRODUCTION

HISTORICAL BACKGROUND

Bifurcation of Dynamical States of Combustion

- In the mid-1980's, hysteresis was discovered at the boundary between stable and unstable operation of the Caltech dump combustor (Smith, 1985; Sterling, 1987)

> These results suggest bifurcation of <u>dynamical</u> states of combustion (limit cycles?)

> The behavior has since been found by others [Cohen (UTRC); Richards (METC)]

HISTORICAL BACKGROUND (cont'd)

Bifurcation of Steady States of Combustion

- In the 1970's, Natanzon et al proposed and investigated the stability of bifurcated <u>steady</u> states of combustion as a possible mechanism for random occurrences of combustion instabilities.

  ➤ The reasoning rests on bifurcation of steady combustion in a recirculation zone (Natanzon et al, 1992)

HISTORICAL BACKGROUND (cont'd)

Bifurcation of Steady States of Combustion (cont'd)

> One state (cold recirculation zone) is more unstable and prone to produce combustion instabilities.

> Which state is reached depends on history (e.g. during ignition or shut-down); the final state depends on random 'accidents' of that history.

> Hence random occurrences of combustion instabilities may be observed.

> Analysis of the recirculation zone is an extension of that for a perfectly stirred (homogeneous) reactor

HISTORICAL BACKGROUND (cont'd)

- Doulatov et al (1998) (independently) proposed existence of 'multiple modes' of combustion, based on statistical analysis of pressure records

  > "…statistical error equaled almost 100% while the instrumentation error was no more than 15%…"

  > Observations of flame structure in a small NH_3/O_2 engine (Beliy et al, 1983; Abulkanov et al, 1974) showed correlation between presence of instabilities and spatial characteristics of the flame structure.

(1) Mono-top Stable Flame
(2) Bi-top flame with Spontaneous Instability

Mono-top Stable Flame

Migratory Flame

Dependence of radiation intensity (ICuH) on the chamber length; a) typical mono-top stable flame; b) an example of migratory flame; c) mono-top stable flame and bi-top flame created by the spontaneous instability in the combustion chamber from a single experiment.

HISTORICAL BACKGROUND (cont'd)

- Note the connection in the Russian reports between statistical analysis of pressure records (both multiple and single firings) and the conclusion that bifurcation of the combustion process exists [Ref. <u>1st International Symposium on Liquid Propellant Rocket Engines</u>, Pennsylvania State University (1993)]

- In numerical simulations it may be difficult to identify bifurcations except with special intentions (?)

- Presence of hysteresis constitutes a basis for control by injecting pulses to cause transitions between two stable states.

SOME REMARKS ON AFFECTING COMBUSTION INSTABILITIES

- The problem of linear stability of motions in a combustion chamber can be reduced to a general form of Rayleigh's Criterion.

- Rayleigh's <u>original</u> criterion was based on excitation of acoustic waves in a tube (e.g. a Rijke tube) by energy addition in the form of heat transfer or energy released in combustion porcessses.

- The criterion states (roughly) that energy addition tends to destabilize (i.e. encourage) a pressure disturbance if the rate of energy addition is increasing locally where the pressure distrubance is also increasing.

$\dot{Q}$: rate of energy addition/volume

$\dfrac{\partial \dot{Q}^{(r)}}{\partial t}$: component of rate of change of $\dot{Q}$ in phase

  with the pressure disturbance δp

Change of energy if the disturbance $\sim \dfrac{\partial \dot{Q}^{(r)'}}{\partial t} \delta p$

- Formally:

$$\nabla^2 p' - \frac{1}{\bar{a}^2}\frac{\partial^2 p'}{\partial t^2} = h \quad ; \quad h = \frac{1}{\bar{a}^2}\frac{R}{C_v}\frac{\partial \dot{Q}'}{\partial t} + h_2$$

$$\hat{n}\cdot\nabla p' = -f$$

SOME REMARKS ON AFFECTING COMBUSTION INSTABILITIES (cont'd)

Modal expansion and spatial averaging:

$$p'(\vec{r};t) = \overline{p}\sum \eta_i(t)\psi_i(t) \; : \; \frac{d^2\eta_n}{dt^2} + \omega_n^2\eta_n = F_n$$

$$F_n = -\frac{\overline{a}^2}{\overline{p}E_n^2}\left\{\int h\psi_n dV + \oiint f\psi_n dS\right\} \qquad E_n^2 = \int \psi_n^2 dV$$

Change of energy of an oscillator in one cycle

$$\Delta\mathscr{E}_n = \int_t^{t+\tau_n} \mathscr{R}e\{F_n\dot{\eta}_n\}dt = \frac{\overline{R}/\overline{C}_v}{\overline{p}E_n^2}\int\psi_n dV \int_t^{t+\tau_n}\dot{\eta}_n\frac{\partial\dot{Q}'}{\partial t}dt' + \cdots$$

"Rayleigh's Criterion"

$$\Delta\mathscr{E}_n = \frac{\overline{R}/C_v}{\overline{p}E_n^2}\int\psi_n dV\int_t^{t+\tau_n}\dot{\eta}_n\frac{\partial\dot{Q}'}{\partial t}dt' > 0 \quad\Rightarrow\quad \text{instability}$$

SOME REMARKS ON AFFECTING COMBUSTION INSTABILITIES (cont'd)

- The destabilizing tendency of energy addition depends on the local phase relation and spatial disturbance.

- Stabilizing or controlling combustion instabilities "according to Rayleigh's criterion" means altering the spatial distribution and phasing of the energy released by combustion.

  - e.g. modulate the primary or a secondary supply of fuel.

- Neither successes nor failures in treating combustion instabilities in liquid rockets are well-understood; notably the amplitudes of oscillations before and after application of a method to improve stability have not been predicted.

  - Why? Because the mechanisms are not well-understood: relying only on Rayleigh's criterion for interpreting problems of combustion instabilities produces no information about the mechanisms unless a theory for $\partial \dot{Q}/\partial t$ is given.

  - The situation is somewhat better for solid rockets because the overwhelming dominant mechanism is associated with the dynamics of combustion processes at a burning solid surface. A secondary cause of instabilities is vortex shedding, strongly dependent on details of the internal geometry.

- Consideration of bifurcations means paying attention to a special class of mechanisms.

II BIFURCATION OF DYNAMICAL STATES IN A DUMP COMBUSTOR

References:

D. Smith (1985) "An Experimental Study of Acoustically Excited, Vortex Driven, Combustion Instability Within a Rearward Facing Step Combustor," Ph.D. Dissertation, Jet propulsion Center, California Institute of Technology.

J. Sterling (1987) "Longitudinal Mode Instabilities in Air Breathing Engines," Ph.D. Dissertation, Jet Propusion Center California Institute of Technology.

P. Knoop, F.E.C. Culick, and E.E. Zukoski (1996) "Extension of the Stability of Motions in a Combustion Chamber by Nonlinear Active Control Based on Hysteresis," *Combustion Science and Technology V. 123, 1-6*, p. 363.

G. Isella, C. Seywert, F.E.C. Culick, and E.E. Zukoski (1997) "A Further Note on Active Control of Combustion Instabilities Based on Hysteresis," *Combustion Science and Technology V. 126*, pp. 381-388.

STABILITY AND HYSTERESIS IN A DUMP COMBUSTOR

Tests with a dump combustor have revealed hysteretic behaviour in the stability boundary (V_d, ϕ) *[Smith 1985, Sterling 1987]:*

STABILITY BOUNDARY

HYSTERESIS OF AMPLITUDE

Observations:

1) As ϕ is increased, keeping V_d constant, the system becomes unstable for $\phi \geq \phi_1$.

2) If ϕ is then decreased, oscillations persist until $\phi \approx \phi_2 < \phi_1$.

POTENTIAL SIGNIFICANCE OF HYSTERESIS

- **In combustors for which hysteresis exists, the range of stable operation (with active control) can be extended.**

  If a disturbance causes the system to be unstable in state A, active control of pulsing can produce transition to the stable state B.

- **Understanding hysteresis means understanding true nonlinear behavior and may lead to a method of nonlinear control in the regions of vigorous instabilities, possibly more efficient than methods of line or control.**

- **However, when it exists, hysteresis occurs in some lean range of mixture ratio, i.e. in the region including the lean blowout limit.**

  Hence a practical strategy for design of operational combustors may be

  - design the combustor for stable operation for moderate and high mixture ratios, by using 'passive' control (geometry, flow field ...)

  - use active control based on the presence of hysteresis in the range of low mixture ratios

IMPLICATIONS OF HYSTERESIS

◊ The existence of hysteresis means that the system possesses two types of dynamic behaviour - two dynamical states - corresponding to the upper and lower branches.

◊ Recent experiments confirm that discrete pulses of secondary fuel injected in the region of the dump plane can cause the transition from the upper branch, point A, to the lower branch, B. The third intermediate branch ------is unstable.

V_d constant

$|p'|$

A

B

Φ_2 Φ Φ_1

PULSED TRANSITION

V_d

Φ

Secondary fuel injection ports

PULSED INJECTION OF SECONDARY FUEL

QUESTIONS ON THE ROLE OF HYSTERESIS IN ACTIVE CONTROL OF COMBUSTORS

- How general is hysteresis in combustors?

- Under what conditions does hysteresis exist?

- What distinguishes the conditions under which:

  (i) a pulse causes no transition?; and

  (ii) a pulse generates transition to the lower branch?

MEASURED STABILITY BOUNDARY AND
HYSTERESIS LOOP

STABILITY DIAGRAM

Sterling (1987)

HYSTERESIS LOOP

Isella et al. (1996)

EXAMPLE OF A PULSED TRANSITION

LOW AMPLITUDE STABLE STATE

HIGH AMPLITUDE LIMIT CYCLE

III BIFURCATION OF STEADY STATE COMBUSTION WITH RECIRCULATION ZONES

References:

Dubinkin, B.N., Natanzon, M.S., and Cham'yan, A.E. (1978) "Two Regimes of Combustion in a Combustion chamber with a Recirculation Zone," *Physics of Combustion and Explosion, Vol. 14, No. 6*, (pp. 693-700).

Natanzon, M.S. and Men'shikova, O.M. (1992) "Bifurcation of Steady Combustion Regimes and Their Influence on the Onset of High-Frequency Oscillations in Combustion Chambers," *Physics of Combustion and Explosion, Vol. 28, No. 4*, (pp. 10-18).

Natanzon, M.S. (1999) Unsteady Combustion in Liquid Rocket Engines translated from the Russian edition (1984) with revised Chapter 8 on bifurcations. Translation editor, F.E.C. Culick.

3.1 BIFURCATION OF COMBUSTION IN A PERFECTLY-STIRRED REACTOR

References:

Bifurcations in Combustion:

Semenov, N. N. (1928) Russian Physico-Chemical Association Journal, V. 60, No. 3 (pp. 241-250).

Zel'dovich, Y. B. Barenblatt, G. I. And Librovich, V. B. (1985) Mathematical Theory of Combustion and Explosion.

Bifurcations in Perfectly-Stirred Reactors:

Vulis, L. A. (1960) Thermal Regimes of Combustion, McGraw-Hill Book Company, New York.

Longwell, J. P. and Weiss, M. A. (1955) "High Temperature Reaction Rates in Hydrocarbon Combustion," *Industrial and Engineering Chemistry*, Vol. 47, pp. 1634ff-1643.

Spalding, D. B. (1957) "Theoretical Relationships Between Combustion Intensity and Pressure Drop for One-Stream Combustion Chambers," A.R.C. 19,180 C.F. 393, Aeronautical Research Council, Great Britain.

3.1 BIFURCATION OF COMBUSTION IN A PERFECTLY-STIRRED REACTOR (cont'd)

References:

Bifurcations in Perfectly-Stirred Reactors (cont'd):

Hottel, H. C., Williams, G. C. and Bonnell, A. H.
(1958) "Application of Well-Stirred Reactor
Theory to the Prediction of Combustor
Performance."

- Spalding and Hottel et al treat a model of a combustor comprising a <u>perfectly stirred reactor</u> (mixing of reactants and recirculated products; no combustion) followed by a <u>plug flow reactor</u> (recirculation zone with combustion).

3.1 BIFURCATION OF COMBUSTION IN A PERFECTLY-STIRRED REACTOR (cont'd)

Reference: Vulis, L. A. Thermal Regimes of Combustion

$$T^\circ, c^\circ \xrightarrow{\dot{m}} \boxed{\quad T, c \quad} \xrightarrow{\dot{m}} T, c$$

Chemical Reactor

- Assumption: Instantaneous complete mixing of inlet flow, producing uniform conditions in the volume.

τ_r: residence time, $\tau_r = \dfrac{\text{mass of reactants in volume}}{\text{mass flow rate}} = \dfrac{\rho V}{\dot{m}}(s)$

w: reaction rate, $w = \dfrac{c_0 - c}{\tau_r}(s^{-1})$

Q: heat of combustion per unit mass (Energy/mass)

- Assumption: Ignore heat losses through the boundary condition for steady reaction (combustion).

c: mass concentration of reactant mixture

V: volume of reactor

ρ: density of products

3.1 BIFURCATION OF COMBUSTION IN A PERFECTLY-STIRRED REACTOR (cont'd)

Rate of Energy Release $=$ Net Rate of Energy
by Combustion   Loss with Flow

$$Q_I = Q_{II} \qquad \text{(per unit mass of reactants in the volume)}$$

$$Q_I = wQ = \frac{c_0 - c}{\tau_s} Q = \left[k_0 c e^{-E/RT} \right] Q \qquad \text{for a first order reaction}$$

$$Q_{II} = \frac{\dot{m} c_p (T - T_0)}{\rho V} = \frac{1}{\tau_s} c_p (T - T_0)$$

Rewrite the condition in terms of four dimensionless parameters

$$\theta = \frac{RT}{E} \qquad \text{(temperature)}$$

$$\theta_0 = \frac{RT_0}{E} \qquad \text{(inlet temperature)}$$

$$\xi = \frac{R}{c_p} \frac{c_0 Q}{E} \qquad \text{(heat of combustion)}$$

$$\tau_{rc} = \tau_r \dot{k}_0 = \frac{\tau_r}{\tau_c} \qquad \left(\frac{\text{residence time}}{\text{reaction time}} \right)$$

3.1 BIFURCATION OF COMBUSTION IN A PERFECTLY-STIRRED REACTOR (cont'd)

Define: $\varphi = 1 - \dfrac{c}{c_0}$ concentration of reacted mixture leaving the reactor.

Replot to show hysteresis loop:

Subcritical bifurcation with turning points occurs because:

1) Energy loss is a linear function of temperature
2) Energy gain is a nonlinear function of temperature having a 'special' form

3.2 BIFURCATION OF STEADY COMBUSTION WITH RECIRCULATION ZONES; Connections With Loss of Stability

Reference: Natanzon et al.

Motivation

* In general there are two classes of mechanisms for loss of stability:
    * linear instability: 'soft excitation', supercritical bifurcation
    * nonlinear instability: 'hard excitation', subcritical bifurcation

* Instabilities arising from subcritical bifurcations may be generated in two ways:

    1) sufficiently large disturbances applied to the system operating in the lower branch;

    2) during transient changes the system may be taken to the lower turning point, then making the transition to the upper branch:

Bifurcation Parameter

3.2 BIFURCATION OF STEADY COMBUSTION WITH RECIRCULATION ZONES; Connections With Loss of Stability (cont'd)

- If instabilities are found far from the linear stability boundary, a possible cause is subcritical bifurcation of combustion.
  - In the absence of large disturbances, path ② may be the cause, identified by connection with the history of the operating state.

Idea:

- - • Bifurcation of steady combustion is associated with behavior of recirculation zones treated as one-dimensional perfectly stirred (homogeneous) reactors.

- The length of the recirculation zone becomes the bifurcation parameter.

- An essential assumption is that local ignition of the injected reactants (gas/gas or liquid/gas) may occur in two ways.

    1) presence of hot combustion products from the recirculation zone;

    2) 'self-ignition' of the injected reactants due to high initial temperature at the injector outlet, or low activation energy.

3.2 BIFURCATION OF STEADY COMBUSTION WITH RECIRCULATION ZONES; Connections With Loss of Stability (cont'd)

- The two cases of ignition produce different spatial structures of the combustion field in the vicinity of the injector.

- If one of the fields is linearly unstable, then the bifurcation of steady combustion leads to an apparent bifurcation of stability.

Ignition by Recirculation Zone

DISTANCE FROM INJECTOR FACE (mm)

Self-Ignition in the Bulk Flow

DISTANCE FROM INJECTOR FACE (mm)

3.3 NATANZON'S ANALYSIS OF COMBUSTION WITH RECIRCULATION ZONES

- The analysis is based on a simplified physical model: the results should be regarded as suggestive of the behavior described above

Physical Model:

- The field is approximated as a one-dimensional steady flow:

- Recirculation zone is followed by the combustion region downstream.

3.3 NATANZON'S ANALYSIS OF COMBUSTION WITH RECIRCULATION ZONES (cont'd)

- A condition for steady combustion in the recirculation zone is set in analogy with the condition $Q_I = Q_{II}$ constructed for a perfectly stirred reactor, but flow enters due to entrainement and leaves at the upstream face, having the temperature T^* of the zone.

- For analysis of the recirculation zone, the external flow from the injection port is implicit, being the source of the entrained flow.

- As for the perfectly stirred reactor, there exist conditions under which steady states exist: one is stable, and two are unstable.

  i) Low temperature stable state with 'no' combustion in the recirculation zone. The main flow must 'self-ignite' at the end or downstream of the recirculation zone.

  ii) High temperature stable state representing combustion in the recirculation zone. The flow leaving the zone at the injector face ignites the main flow.

Condition for steady combustion:

$$Q_I(T^*) = Q_{II}(T^*)$$

$$\left(\rho u C_p \widetilde{T}\right)^* - \left(\rho u C_p T\right)^0 = w H_0 \ell - B \Delta \rho u$$

| Net Energy Flow out of Recirculation Zone | Energy Released by Combustion | Energy Absorbed by Liquid Fuel |

3.3 NATANZON'S ANALYSIS OF COMBUSTION WITH RECIRCULATION ZONES (cont'd)

Equations Solved for Recirculation Zone

Gas Flow:

$$\frac{d}{dx}(\rho u) = G_{\rho u}$$

$G_{\rho u}$: vaporization rate

ν_f, ν_0, ν_p : mass concentrations

$$\Rightarrow \boxed{\Delta(\rho u) = G_{\rho u}\ell}$$

$$\boxed{\nu_f + \nu_0 + \nu_p = 1}$$

Combustion Products:

$$\frac{d}{dx}(\rho u \nu_p) = w$$

$$\Rightarrow \boxed{\nu_p \Delta(\rho u) = w\ell}$$

$$\Delta(\rho u) = (\rho u)^* - (\rho u)^0$$

Fuel Vapor:

$$\frac{d}{dx}(\rho u \nu_f) = G_{\rho u} - \frac{1}{1+k_0}w$$

$G_{\rho u}$: vaporization rate of fuel drops

$$\Rightarrow \boxed{\nu_f \Delta(\rho u) = \Delta(\rho u) - \frac{1}{1+k_0}w\ell}$$

3.3 NATANZON'S ANALYSIS OF COMBUSTION WITH RECIRCULATION ZONES (cont'd)

Energy:

$$\frac{d}{dx}(\rho u h) = w H_0 - G_{\rho u}\left[C_f(T_s - T_s^0) + \xi(T_s)\right] + G_{\rho u} C_p T_s$$

T_s: surface temperature of fuel drops

C_f: heat capacity of fuel

ξ: heat of vaporization

$$\Rightarrow \boxed{\left(\rho u C_p \widetilde{T}\right)^* - \left(\rho u C_p \widetilde{T}\right)^0 = w H_0 \ell - B \Delta(\rho u)}$$

$$B := C_f(T_s - T_s^0) + \xi(T_s) - C_p T_s$$

$$\widetilde{T} := T + h_d / C_p$$

Motions of Fuel Drops:

$$\frac{d v}{dx} = G_v \quad ; \quad \frac{dm}{dx} = G_m$$

v: velocity

m: mass

3.3 NATANZON'S ANALYSIS OF COMBUSTION WITH RECIRCULATION ZONES (cont'd)

- The true meaning of the model and the calculations is NOT clear in the two references but it appears that the model is virtually identical to that for a PSR.

- Solution is obtained by iteration giving the results sketched above.

- The results of the calculations for the recirculation zone can be displayed in the bifurcation diagram, a replot of the results given above:

- This figure shows that for initial temperatures T^0 higher than about 830°K only the high temperature state of combustion exists in the recirculation zone.

3.3 NATANZON'S ANALYSIS OF COMBUSTION WITH RECIRCULATION ZONES (cont'd)

- For a range of $T^0 < 830°K$, say $T^0 = 775°K$, two stable states are possible for, in this case, $1.2cm < \ell < 2.0cm$.
  - For $T^0 = 775°K$, as ℓ increases, the temperature remains low in the recirculation zone until $\ell \approx 2cm$ when ignition occurs.
  - Then ℓ is reduced, combustion is sustained until $\ell \approx 1.2cm$ when extinction occurs.

- Multiple states can also be obtained if for a fixed length of recirculation zone the equivalence ratio α (i.e. the F/O mixture ratio) is changed, consequently changed the heat of combustion.

  The next figure shows the bifurcation diagram in the coordinates: temperature T^* in the recirculation zone versus ϕ, the equivalence ratio.

- Note that in this setting two hysteresis loops exist.

3.3 <u>NATANZON'S ANALYSIS OF COMBUSTION WITH RECIRCULATION ZONES</u> (cont'd)

<u>Combustion and The Temperature Field Outside the Recirculation Zone</u>

- Natanzon and Men'shikova (1992) have reported the following results for the temperature field outside the recirculation zone, obtained by solving one-dimensional equations with $T^0 = 775°K$ and $\phi = ?$

3.3 NATANZON'S ANALYSIS OF COMBUSTION WITH RECIRCULATION ZONES (cont'd)

- The sequence of these cases falls as shown in the bifurcation diagram:

Length of Recirculation Zone, ℓ (mm)

- Some of the detailed behavior of these curves depends on the model of droplet combustion, fragmentation,…

- Note that the overall steady combustion process in the chamber is hardly affected by the particular condition in the recirculation zone:
    - ~ if the chamber is sufficiently long, the combustion efficiency and exit temperature are essentially identical in all cases

- In respect to the excitation of combustion instabilities, when there are multiple steady states , the question is:

    Which of the steady states is less stable?

3.3 NATANZON'S ANALYSIS OF COMBUSTION WITH RECIRCULATION ZONES (cont'd)

- Because the current existence of a particular steady state depends on the history of the operating point of the chamber, the possibility for 'randomly' occurring instabilities is exposed.

A Two-Dimensional Model for Combustion with Bifurcations

- A model is constructed for gas/gas reactants.
- The recirculation zone is treated as a perfectly stirred reactor but flows in and out are included.
  - A condition for stationary combustion enforced.
- Details of the flow outside the recirculation zones are incomplete.
- Results show the existence of two states of steady combustion:

Ignition by Recirculation Zone

3.3 NATANZON'S ANALYSIS OF COMBUSTION WITH RECIRCULATION ZONES (cont'd)

DISTANCE FROM INJECTOR FACE (mm)

Self-Ignition in the Bulk Flow

Stability of the Two States of Steady Combustion

- Natanzon establishes the stability of the two steady states by applying his method based on the amplitude-phase-frequency characteristic (APFC) interpreted as a "hodograph."

- A recirculation zone is a passive capacitance, providing distributed sources along its boundary.

3.3 NATANZON'S ANALYSIS OF COMBUSTION WITH RECIRCULATION ZONES (cont'd)

- The method comes down to examining the behavior of the transfer function $R(i\omega)$ for the combustion zone:

$$R(i\omega) = \frac{\delta u}{\delta p}$$

δu: velocity fluctuation at the

δp: pressure fluctuation

- $\mathcal{R}e\left(\dfrac{\delta u}{\delta p}\right) > 0 \Rightarrow$ tendency to instability. (Natanzon)

- Consistent with Rayleigh: move Q where p is high

> HENCE the state with a hot (combusting) recirculation zone is more unstable.

3.3 NATANZON'S ANALYSIS OF COMBUSTION WITH RECIRCULATION ZONES (cont'd)

Experimental Results Confirming the Possible Influences of Recirculation Zones

- The figure shows laboratory apparatus specially constructed to demonstrate qualitative changes of stability when recirculation zones are present.
  - Tests were run with and without recirculation zones; recirculation zones were created by mounting a cascade of rods immediately downstream of the pylons through which fuel was injected in an air stream.

WITH RECIRCULATION ZONES
NO RECIRCULATION ZONES

- In all tests, the chief experimental variables were the temperature T^0 of the inlet air and the equivalent ratio.

- The reactants were liquid fuel and heated air.

3.3   NATANZON'S ANALYSIS OF COMBUSTION WITH RECIRCULATION ZONES (cont'd)

- Tests with no recirculation zones showing the conditions for combustion and no ignition or extinction.

> $---$ boundary of extinction
> $\triangle$ steady combustion
> $\blacktriangle$ no combustion

- The extinction boundary is essentially coincident with the boundary of self-ignition (apparently no ignition was used) and T^0 is minimum when $\phi = 1$.
- Tests with turbulence-inducing cascade (and recirculation zones)

> $-\!-\!-$ boundaries of extinction
> $\bigcirc$ steady combustion
> $\bullet$ no combustion
> ▰ region in which hysteresis is observed

3.3　NATANZON'S ANALYSIS OF COMBUSTION WITH RECIRCULATION ZONES (cont'd)

- Experimental results for hysteresis are shown in the figure below.

IV INCORPORATING BIFURCATION OF COMBUSTION IN ANALYSIS OF COMBUSTOR DYNAMICS

References:

Culick, F. E. C., Paparizos, L., Sterling, J., and Burnley, V. (1992) "Combustion Noise and combustion Instabilities in Propulsion Systems," AGARD CP 512.

Burnley, V. (1990) "Nonlinear Combustion Instabilities and Stochastic Sources," Ph.D. Dissertation, California Institute of Technology.

INCORPORATING A GLOBAL BIFURCATION OF COMBUSTION IN ANALYSIS OF COMBUSTOR DYNAMICS

- Two apparently different types of subcritical bifurcations have been described, both involving recirculation zones in essential ways.

   1) Bifurcation of dynamical states, showing the existence of two steady oscillatory states in a dump combustor:

   A: loss of linear stability and development
       of steady limit cycles for all $\phi \geq \phi_n$

   B: absolute linear stability for $\phi \geq \phi_B$

Lower branch: weak oscillations: stable linear modes
                driven by noise sources independent of
                the acoustic field.

Upper branch: strong oscillations in stable limit
                cycles characterized by the balance
                of energy (power) gains and losses;
                the behavior is intrinsically
                nonlinear (gains of losses or both).

412

INCORPORATING A GLOBAL BIFURCATION OF COMBUSTION IN ANALYSIS OF COMBUSTOR DYNAMICS (cont'd)

2) Bifurcation of steady states, one of which is linearly stable and one linearly unstable, developing stable limit cycles.

- The two types of bifurcation involve physical behavior differing in detail but which can be formally accommodated in the same theoretical framework.

  - Note that the scales of the recirculation zones differ in the two cases because the scales of the combustor differ.

  - In liquid rockets, many 'small' recirculation zones exist at the injector face. The problem of cooperative behavior to produce a bifurcation of dynamical behavior in the combustor remains unsolved: interactions among the zones is sufficient and probably necessary.

INCORPORATING A GLOBAL BIFURCATION OF COMBUSTION IN ANALYSIS OF COMBUSTOR DYNAMICS (cont'd)

- Analysis based on modal expansion and spatial averaging suggests the strategy to follow.

<u>Modal Expansion</u> $\qquad p'(\vec{r},t)=\bar{p}\sum\eta_i(t)\psi_i(\vec{r})$

<u>Spatial Averaging</u> $\qquad \dfrac{d^2\eta_n}{dt^2}+\omega_n^2\eta_n=F_n$

$$F_n=-\frac{\bar{a}^2}{\bar{p}E_n^2}\left\{\int h\psi_n dV+\oiint f\psi_n dV\right\}$$

where h, f represent volumetric and surface sources of pressure distrubances:

$$\nabla^2 p'-\frac{1}{\bar{a}^2}\frac{\partial^2 p'}{\partial t^2}=h \ ; \ \hat{n}\cdot\nabla p'=-f$$

- The functions h and f contain purely gasdynamical parts and sources of mass, momentum, and energy due, primarily, to combustion processes and interaction between gaseous and condensed phases.

  - Some of the sources may be due to actuation associated with some means of active control.

414

INCORPORATING A GLOBAL BIFURCATION OF COMBUSTION IN ANALYSIS OF COMBUSTOR DYNAMICS (cont'd)

- Gasdynamics alone cannot produce subcritical bifurcations. Hence the behavior sought must be associated with other sources, in particular the dynamics of the energy release accompanying combustion processes.

  - As a result of the spatial averaging, the dynamical consequences of volumetric and surface sources (h, f) are equivalent.

$$\nabla^2 p' - \frac{1}{\overline{a}^2}\frac{\partial^2 p'}{\partial t^2} = h \qquad \hat{n}\cdot\nabla p' = -f$$

Modal Expansion and Spatial Averaging:

$$\frac{d^2\eta_n}{dt^2} + \omega_n^2\eta_n = 0 \; ; \quad F_n = -\frac{\overline{a}^2}{\overline{p}E_n^2}\left\{\int h\psi_n dV + \oiint f\psi_n dS\right\}$$

With volumetric energy release Q_R and mass injection at the lateral boundary:

$$\left(F_n\right)_{\text{COMB}} = \frac{\overline{a}^2}{\overline{p}E_n^2}\left\{\frac{\gamma-1}{\overline{a}^2}\int\frac{\partial \dot{Q}_R'}{\partial t}\psi_n dV + \oiint\frac{\partial m_b'}{\partial t}\psi_n dS + \oiint\frac{\partial p'}{\partial t}\left[\overline{u}_b + (u_b')_{\text{linear}}\right]\psi_n dS\right\}$$

Accounting for volumetric energy addition only:

$$\left(F_n\right)_{\text{COMB}} = \frac{\gamma-1}{\overline{p}E_n^2}\int\frac{\partial \dot{Q}_R'}{\partial t}\psi_n dV$$

INCORPORATING A GLOBAL BIFURCATION OF COMBUSTION IN ANALYSIS OF COMBUSTOR DYNAMICS (cont'd)

QUESTION: What nonlinear behavior of $\dot{Q}'_R$ is necessary to produce a subcritical bifurcation in the chamber dynamics?

Two proposals:

A. Sterling (1993) "Nonlinear Analysis and Modeling of Combustion Instabilities in a Laboratory Combustor," Combustion Science and Technology, Vol. 89 (pp. 167-179)

- Modeling time-dependent heat release associated with combustion in periodically shed vortices to explain nonlinear behavior in the Caltech dump combustor.

- Rayleigh's Criterion is used to obtain an estimate for a Poincaré map:

$$\Delta \mathcal{E}_n = \frac{\gamma-1}{\overline{p}E_n^2} \omega_n^2 \int \psi_n \, dV \int_t^{t+\tau} \eta_n \dot{Q}' \, dt'$$

The map displays the cycle-to-cycle increments of the energy in a modal oscillator.

INCORPORATING A GLOBAL BIFURCATION OF COMBUSTION IN ANALYSIS OF COMBUSTOR DYNAMICS (cont'd)

- Two models of $\dot{Q}'_R$ proposed:

1) Periodic Delayed Combustion Response

Physical Basis: (observations)

(i) For small amplitudes, a small shed vortex is surrounded by hot combustion products from the previous cycle: shorter time delay and less energy released.

(ii) For large amplitudes, a large shed vortex interacts with the wall, creating a region of cold reactants: a longer time delay is associated with larger energy release.

Model: Energy released in the vortex shedding is proportional to the acoustic velocity, with a time delay (relative to the pressure oscillation) linear in the acoustic oscillator energy

INCORPORATING A GLOBAL BIFURCATION OF COMBUSTION IN ANALYSIS OF COMBUSTOR DYNAMICS (cont'd)

Realization:

$$\dot{Q}' = Q(\vec{r})\dot{\eta}(t-\tau)$$

$$\eta = \sqrt{\mathscr{E}}\,\sin\omega t \qquad \text{(Single Mode)}$$

$$\tau = c_1\mathscr{E}$$

Substitute in Rayleigh's Criterion

$$\boxed{\mathscr{E}_{j+1} = \mathscr{E}_j\left[1 + c_2\sin\mathscr{E}_j\right]}$$

A one-dimensional map with bifurcation parameter c_2.

2) "Twice-Kicked" Oscillator

Physical Basis: (observations)

(i)   A vortex is shed when the velocity at the dump plane is rising during each cycle.

(ii) For 'small' vortices, combustion occurs later in the cycle, nearly to completion, producing a broad 'pulse' of pressure.

(iii) For 'large' vortices, combustion is not complete in the first pulse and occasionally smaller secondary pulses of pressure occur.

INCORPORATING A GLOBAL BIFURCATION OF COMBUSTION IN ANALYSIS OF COMBUSTOR DYNAMICS (cont'd)

<u>Model:</u>   The energy released is modeled as two pulses (δ-functions) in time. A large amplitude pulse <u>always</u> occurs when the pressure is near maximum, and rising, causing growth. For 'large' amplitudes a pulse also occurs when the pressure is minimum, tending to alternate the oscillations.

<u>Realization:</u>

Use Rayleigh's Criterion to construct the relations for energies at maxima and minima of pressure:

Free Oscillation:

$$\mathcal{E}_{max+} = \mathcal{E}_{min-}$$

Pulse near p_{max}:

$$\mathcal{E}_{max+} = \mathcal{E}_{max-} + c_1 \mathcal{E}_{max-}$$

Pulse near p_{min}:

$$\mathcal{E}_{min+} = \mathcal{E}_{min-} - c_2 \mathcal{E}_{min-}$$

Combine and renormalize:

$$\boxed{\mathcal{E}_{j+1} = c_3 \left(\mathcal{E}_j - c_4 \mathcal{E}_j^2 \right)}$$

Bifurcation parameter c_3 for c_4 fixed

INCORPORATING A GLOBAL BIFURCATION OF COMBUSTION IN ANALYSIS OF COMBUSTOR DYNAMICS (cont'd)

The bifurcation diagrams for the two cases are shown in the following two figures. In each case, period-doubling bifurcations occur, leading to chaotic behavior not observed in the experimental results.

DELAYED COMBUSTION RESPONSE

Example 1 Bifurcation Parameter, C_2

"TWICE-KICKED" OSCILLATOR

Example 2 Bifurcation Parameter, C_3 with $C_4 = 1$

INCORPORATING A GLOBAL BIFURCATION OF COMBUSTION IN ANALYSIS OF COMBUSTOR DYNAMICS (cont'd)

- The question remains: can these ideas be adapted in such a fashion as to provide an explanation for the subcritical bifurcation and hysteresis shown by the experimental results?

  V. Burnley (1996) "Nonlinear Combustion Instabilities and Stochastic Sources," Ph.D. Thesis, California Institute of Technology.

- Modeling the time-dependent heat release for distributed combustion following the models of Levine and Baum(1983) and Greene (1990).

$$\dot{m}' = \overline{\dot{m}} R_{vc} F\left(\left|\vec{u}' - \vec{u}_t\right|\right) \quad or \quad \dot{Q}' = \overline{\dot{Q}} q_{vc} F\left(\left|\vec{u}' - \vec{u}_t\right|\right)$$

- The threshold velocity u_t is <u>necessary</u> to give a subcritical bifurcation.

INCORPORATING A GLOBAL BIFURCATION OF COMBUSTION IN ANALYSIS OF COMBUSTOR DYNAMICS (cont'd)

- With the above representation of $\dot{m}'$ or $\dot{Q}'$, application of a continuation method gives the following bifurcation diagram:

BIFURCATION DIAGRAM FOR THE DETERMINISTIC SYSTEM; THRESHOLD VELOCITY MODEL OF NONLINEAR COMBUSTION

- For reasons not known, the usual supercritical bifurcation occurs at α, = 0, followed by two turning points,, giving the possibility for hysteresis and nonlinear (pulsed) instabilities.

    Note: existence of a threshold velocity $\neq 0$
    is essential for this result: the reasons
    are not known.

V SOME CONSEQUENCES OF
SUBCRITICAL BIFURCATIONS WITH NOISE

5.1 REPRESENTING NOISE IN ANALYSIS OF THE GLOBAL DYNAMICS

- There are three sorts of problems:

  - Formal construction of noise (stochastic) sources in the framework of spatial averaging equations for the fluctuating motions (oscillator equations).

  - Modeling the noise sources

  - Solving the stochastic differential equations

A Construction of Noise Sources in the Oscillator Equations

- The first step is application of the principle of splitting small disturbances.

  Chu, B.T. and Kovazonay, L.S.G. (1958) "Nonlinear Interactions in a Viscous Heat-Conducting Compressible Gas," Journal of Fluid Mechanics, V. 3, No. 5 (pp. 494-514).

5.1 REPRESENTING NOISE IN ANALYSIS OF THE GLOBAL DYNAMICS (cont'd)

SPLITTING THE UNSTEADY FLOW FIELD

- Chu and Kovazsnay (1958)

  - In the limit of small amplitudes, disturbances in a compressible fluid may be synthesized of three types of waves: acoustic waves, vorticity waves, and entropy waves.

    - acoustic waves carry pressure and velocity
    - vorticity waves carry vorticity and velocity
    - entropy waves carry entropy and velocity

$$p' = p'_a$$
$$\vec{\Omega}' = \vec{\Omega}'_\Omega$$
$$s' = s'_s$$
$$\vec{u}' = \vec{u}'_a + \vec{u}'_\Omega + \vec{u}'_s$$

- To second order, acoustic waves remain free of entropy and vorticity.

- Apply the principle of additive splitting to problems of second-order acoustics and nonuniform mean flow.

5.1 REPRESENTING NOISE IN ANALYSIS OF THE GLOBAL DYNAMICS (cont'd)

- Apply the principle of additive splitting to problems of second-order acoustics and nonuniform mean flow. Write the flow variables as sums of the three contributions:

$$p' = p'_a + p'_\Omega + p'_s$$

$$\vec{\Omega}' = \vec{\Omega}_a + \Omega'_\Omega + \Omega'_s$$

$$s' = s'_a + s'_\Omega + s'_s$$

To first order;

Acoustic Waves: $p' = p'_a$ $p'_\Omega = p'_s = 0$

Vorticity Waves: $\Omega' = \Omega'_\Omega$ $\Omega'_a = \Omega'_s = 0$

Entropy Waves: $s' = s'_s$ $s'_a = s'_\Omega = 0$

The velocity field contains all three:

$$\vec{u}' = \vec{u}'_a + \vec{u}'_\Omega + \vec{u}'_s$$

Note: The vorticity field may contain, to first order, random contributions (noise) and terms arising, for example, from generation of vorticity at a lateral surface with mass injection.

426

5.1 REPRESENTING NOISE IN ANALYSIS OF THE GLOBAL DYNAMICS (cont'd)

A. Procedure:

(i) Write $p = \bar{p} + p'$, $\vec{u} = \bar{\vec{u}} + \vec{u}'$ etc. in the general conservation equations expanded to 3rd order in $(\ )'$

(ii) Form the nonlinear wave equation for the pressure

(iii) Assume $p' = \bar{p} \sum \eta_i \psi_i$ and spatial average to give the oscillator equations $\ddot{\eta}_n + \omega_n^2 \eta_n = F_n$:

$$-\frac{\bar{p} E_n^2}{\bar{a}^2} F_n = \bar{p} I_1 + \frac{1}{\bar{a}^2} I_2 + \bar{p} I_3 + \frac{1}{\bar{a}^2} I_4 + \bar{p} I_5$$

$$+ \oiint \bar{p} \frac{\partial \vec{u}'}{\partial t} \cdot \hat{n} \psi_n \, dS - \int \vec{\mathcal{F}} \cdot \nabla \psi_n \, dV + \frac{1}{\bar{a}^2} \int \frac{\partial p'}{\partial t} \psi_n \, dV$$

$$I_1 = \int \left[\bar{\vec{u}} \cdot \nabla \vec{u} + \vec{u}' \cdot \nabla \bar{\vec{u}} \right] \cdot \nabla \psi_n \, dV$$

$$\vdots$$

etc

(iv) Apply the splitting principle and rewrite I_1, ...

$$I_1 = I_1^a + I_1^\Omega + I_1^s$$

$$I_1^a = \int \left[\nabla \left(\bar{\vec{u}} \cdot \vec{u}_a' \right) - \vec{u}_a' \times \nabla \times \bar{\vec{u}} \right] \cdot \nabla \psi_n \, dV$$

$$\vdots$$

5.1 REPRESENTING NOISE IN ANALYSIS OF THE GLOBAL DYNAMICS (cont'd)

(v) The fluctuations appearing in I_1, ... must be modeled:

Assume to first order,

$$u'_a = \sum \frac{\dot{\eta}_j \cdot (t)}{\gamma k_j^2} \nabla \psi_j$$

and set $p'_\Omega = p'_s = 0$

To second order the oscillator equations have the form

$$\ddot{\eta}_n + \omega_n^2 \eta_n = 2\alpha_n \dot{\eta}_n + 2\omega_n \theta_n \eta_n - \sum_{i=1}^{\infty} \sum_{j=1}^{\infty} \left[A_{nij} \dot{\eta}_i \dot{\eta}_j + B_{nij} \eta_i \eta_j \right]$$
$$+ \sum \left[\xi_{ni}^v \dot{\eta}_i + \xi_{ni} \eta_i \right] + \Xi_n + \left(F_n \right)_{other}^{NL}$$

$\xi_{ni}^v, \xi_{ni}, \Xi_n$ are stochastic sources defined as integrals but they must be modeled.

B. Modeling the Noise Sources

- No modeling based on experimental, theoretical, or phenomenological results has been accomplished.

- Approximate the sources ξ_{ni}^v, ξ_{ni} and Ξ_n as white noise processes.

5.1 REPRESENTING NOISE IN ANALYSIS OF THE GLOBAL DYNAMICS (cont'd)

C. Solving the Stochastic Differential Equations

- The random character of the stochastic sources will appear as randomness imposed in the amplitudes $\eta_n(t)$ of the modes.

- Thus the Fourier synthesis of the pressure field serves in the first instance as an approximate representation of the deterministic (acoustics) part of the unsteady motions and good results can be obtained by retaining only a small number of terms in the modal expansion.

- Results have been obtained only for the simplest case of two modes, with noise sources only in the fundamental mode. Nonlinear gasdynamic coupling transfers stochastic behavior to the second mode.

5.1 REPRESENTING NOISE IN ANALYSIS OF THE GLOBAL DYNAMICS (cont'd)

C. <u>Solving the Stochastic Differential Equations</u> (cont'd)

- There are two types of stochastic influences included here:

    (i) ξ_{ni}, ξ_{ni}^{v} represent stochastic influences on the 'spring' of natural frequency and in the damping of growth rate of the n^{th} mode;

    (ii) Ξ_n represents a stochastic driving source causing excitation of the n^{th} mode even in the absence of driving by combustion processes [cf. Russian interpretation of test results and analysis by R. Hessler for solid rockets in the 1970's – 1980's.

- The equations to be solved are (Burnley, 1996)

$$\ddot{\eta}_1 + \omega_1^2 \eta_1 = 2\left(\alpha_1 + \frac{1}{2}\xi_1^v\right)\dot{\eta}_1 + 2\omega_1\left(\theta_1 + \frac{1}{2\omega_1}\xi_1\right)\eta_1 + \left(F_1\right)^{NL} + \Xi_1$$

$$\ddot{\eta}_2 + \omega_2^2 \eta_2 = 2\alpha_2\dot{\eta}_2 + 2\omega_2\theta_2\eta_2 + \left(F_2\right)^{NL}$$

5.1 <u>REPRESENTING NOISE IN ANALYSIS OF THE GLOBAL DYNAMICS</u> (cont'd)

- Results for probability density functions have been constructed using the Monte-Carlo method (Paparrizos, 1991; Burnley, 1996) applied to a Stratonovich form of the stochastic differential equations (Burnley, 1996).

- The following figures show a pressure trace and spectrum for one simulation.

- Many simulations with initial conditions varied, and constructing probability distributions after the initial transients have decayed.

C. Solving the Stochastic Differential Equations (cont'd)

- A series of simulations have been carried out with the nonlinear combustion model described above, and the growth (decay) constant α, of the fundamental mode varied. The probability density functions are shown in the following figures.


(a) $\alpha_1 = -35$ sec^{-1}

(b) $\alpha_1 = -25$ sec^{-1}

(c) $\alpha_1 = -20$ sec^{-1}

(d) $\alpha_1 = -10$ sec^{-1}

(e) $\alpha_1 = +10$ sec^{-1}

VI CONCLUDING REMARKS

- Indisputable theoretical and experimental evidence exists for the existence of various sorts of subcritical as well as supercritical bifurcations in combustors.

- A framework is available for investigating the consequences of global bifurcations in combustor dynamics.

- The consequences of many local subcritical bifurcations have not been examined.

- The proposal that hysteresis associated with recirculation zones and different stability of the associated steady combustion fields merits further investigation as a possible explanation for random occurrences of combustion instabilities.

- Numerical simulations of these problems remain in a primitive state.

433

Some Aspects of Nonreproducibility of Self-Oscillation Excitation

in Combustion Chamber of Liquid Rocket Engine

K.P. Denisov[*], V.N. Ivanov[**], V.P. Pikalov[***]

Research Institute of Chemical Machine Building (NIICHIMMASH),

Sergiev-Posad, Russia

Abstract

Some aspects of low reproducibility of high-frequency self-oscillation excitation in combustion chamber of liquid rocket engine.

In the investigation of model combustion chambers it is shown that the observed effects of unreproducibility arise from:

- possibility of realization of combustion zone ambiguous (bistable) stationary   states with invariant parameters of the propellant feeding system.;

- combustion zone nonline*ar sensitivity to chamber natural acoustic field that results in the occurrence of self-oscillation unstable limit cycle of one or other mode.

---

[*] Vice-General Director.

[**] Senior Reseach Engineer.

[***] Head, Reseach Division.

Nomenclature

A_{rms}=root mean square of total pulsating signal

F=frequency

H=potential barrier

P_c=static combustion chamber pressure

P'=pulsating pressure component

P'_{cms} = root mean square of pulsating pressure component

P_{st}=stationary probability density function

Q' = pulsating heat release component

$\dot{P}'$ = P' complex amplitude

$\dot{Q}'$ = Q' complex amplitude

$R(\tau)$=autocorrelation function

SLC=stable limit cycle

ULC= unstable limit cycle

T=oscillation period

V_0=Oxygen velocity stream

V_p=Propan velocity stream

α=equivalense ratio (oxygen excess relative to the stoichiometric ratio)

β=decay coefficient

$\overline{\beta T}$ =effective oscillation decrement

$\delta(\tau)$=Dirac delta function

λ=amplitude (envelope) of narrow-band signal

λ_{SLC}=SLC amplitude

λ_{ULC}=ULC amplitude

$\xi(t)$=normal delta-correlated (white) noise

τ=temporal interval

φ=oscillation phase

=potencial function

ω= oscillation angular frequency

ω_0= natural angular frequency

Introduction

Dynamic ambiguity of combustion regime in liquid rocket engine (LRE) chambers manifests itself in spontaneous transitions from a state of small random oscillation ("noises') to a state of regular self-oscillation of high amplitude with propellant supply condition and other monitored "external" factors being constant. A distinctive feature of those transitions is the fact that they occur occasionally, for no apparent reason. No observable disturbance (of pulse or explosive nature, for example) generally precedes the self-excitation event. Self-oscillation excitation is of "soft", smooth character. The self-oscillation termination occurs in a similar way. The random character of such spontaneous transitions causes us to speak of self-oscillation excitation nonreproducibility (such terms as "limited reproducibility", "random reproducibility' are also used).

At least two basic concepts exist of the nature of low reproducibility of acoustic self-oscillation excitation in combustion chambers.

One of the concepts is based on postulating a possibility of combustion zone space pattern bifurcations that are significant with respect to stability to small acoustic disturbance. This is equivalent to the stating that a stationary regime of propellant feeding to the chamber is not a factor that defines the flame pattern unambiguously.

Thus the given concept is based on the assumption that, in principle, generation of multiple combustion zone space patterns that differ in regimes of flame stabilization is possible at identical values of parameters defining the combustion chamber stationary mode. These combustion zone patterns may have different sensitivity to small acoustic disturbances.

In particular, the realization of one or other combustion zone space pattern may depend on a combination of random conditions that take place in the course of engine starting and operating in the specified regime. As a consequence

of the random character of one or other combustion zone space pattern realization, the self-oscillation excitation process acquires a statistic character also.

The second concept of nonreproducibility is based on the idea that a nonlinear ("hard') excitation of a potentially self-oscillating system occurs by the action of a stationary wide-band acoustic noise of turbulent combustion, or by the action of single random pressure disturbances of explosive nature that occur in combustion chamber sometimes. This model postulates the presence of unstable limit-cycle (ULC) self-oscillation that results from the fact that n, the effective index of interaction between oscillatory components Q' of heat release (or mass release) rate and oscillatory components P' of pressure is a nonlinear function of pressure oscillation amplitude λ[1]:

$$n = \frac{\dot{Q}'}{\dot{P}'} = n(\lambda),$$

where $\dot{Q}'$ and $\dot{P}'$ are complex amplitude of Q' and P' , respectively.

The considered concepts of nonreproducibility are alternate in a sense because they lead to different scenarios of random beginning of self-oscillations. The adequacy of used diagnostic model is very important for successful application of methods and tools of diagnostics of combustion stability in LRE. In this connection the study of the nature of self-oscillation excitation low reproducibility, as well as the search of diagnostics methods and ways of predicting this phenomenon are of critical importance. Some results of the study of self-oscillation excitation low reproducibility in combustion chamber are presented. The data are based on experimental research work carried out at NIICHIMMASH's set-ups modeling oscillatory combustion.

1. External Symptoms of Spontaneous Combustion

Instability

A wide variety of external symptoms of spontaneous combustion instability are observed in engine tests of which the following two are most common:

a) instability is observed in a series of *m* identical tests of engines of the same type in *n>m* cases immediately or in some random time *t* after the engine reaches the specified stationary operation regime (Fig.1a)

b) instability occurs in some time t_i after a certain engine reaches the specified operation regime and manifests itself as a single "spike" of self-oscillation (Fig. 1b) or as alternating 'noise' and self-oscillatory combustion regimes. (Fig.1c)

2. Model Combustion Chamber with a Single

Injection Element

Investigation was carried out in a model combustion chamber with a single coaxial injection element (Fg.2). Gaseous propane and gaseous oxygen were used as propellants. The combustion chamber is equipped with instruments for flame photographing and reaction zone oscillatory pressure measurement.

The following result was obtained. In the course of tests a distinct ambiguity of flame space pattern was recorded in a certain range of operating governing parameters: fuel flow rate and oxidizer flow rate. Depending on the ignition condition, flame stabilization regime (and flame space pattern, accordingly) could be in one of two stable stationary state (Fig.3). First of them corresponded to the flame stabilization inside the injection element in the vicinity of the fuel post edge (Scheme 1). The flame had an elongated form and radiated a relatively low level of noise (1...30 Pa in the 0...10 kHz range). The second stationary state corresponded to flame stabilization outside of the injection element at some distance from the oxidizer tube exit (Scheme 2). This state is characterized by a shorter smeared flame and a relatively high integral noise level (26... 90 Pa). The noise frequency contents were different in both cases. The mentioned ambiguity of stabilization mode (bistability) was observed in a wide range of the governing parameters (fuel flow velocity and oxidizer flow velocity).

A principally important effect was found in the tests: an acoustically stable 'noise' combustion corresponded to the flame stabilization Scheme 1

439

throughout the investigated range of the governing parameters (Fig 4a). In the case of flame stabilization according to Scheme 2, in the same range of the governing parameters there was a boundary beyond which strong self-oscillation of the first radial mode (of 2620 Hz , 320 Pa) excited. (Fig.4b).

This series of experiments showed that the bistability of combustion zone pattern could really give rise to dynamic ambiguity that manifests itself in the presence or absence of self-oscillation. With unmonitored ignition process (if it is unknown what particular flame stabilization regime is realized), the excitation of self-oscillation in an ensemble of similar tests becomes of a random, statistical nature. Thus it can be stated that the ambiguity of dynamic state of combustion may a consequence of a stochastic process of initial ignition and subsequent generation of one or another flame self-consistent spatial pattern.

It should be noted that in the given experiments, once the mixture was ignited and flame stabilization regime was established as per Scheme 1, an artificial transition from Scheme 1 to Scheme 2 was achieved by disturbing oxygen concentration in the reaction zone. Some air was injected in the oxygen feeding line for a short time for this purpose. (Fig.5). After the air injection was terminated, the system retained stabilization Scheme 2. In this case, after the system transition to the region of potential instability, self-oscillation excitation became a completely deterministic, reproducible phenomenon.

Thus in this example the self-oscillation excitation nonreproducibility is only apparent and is a result of the absence of information on flame stabilization regime on ignition. However the mere fact of recognizing a possibility of bifurcation of flame spatial pattern with subsequent self-oscillation excitation deserves attention.

3. Model Combustion Chamber with Gas-Liquid

Injection Elements

A combustion chamber of 104 mm in diameter was investigated (Fig.6). Propellants, liquid kerosene and gaseous (cold) oxygen were supplied from

cylinders. The chamber was equipped with an independent igniter, using methane and oxygen. A device for applying artificial pulse disturbances to the reaction zone and fuel feed cavity is mounted on the chamber.

The injection head includes four injection elements with radial input of liquid fuel into the flow of gaseous oxidizer.

The range of test regimes on coordinates: chamber static pressure, P_c, – equivalence ratio (oxygen excess relative to the stoichiometric ratio), α, is shown in Fig. 7.

In the course of testing this injection head type the following dynamic state of combustion process were recorded;

- **noise stable state**, $(P_c \leq 0.4$ MPa$)$, Fig.8;

- **chaotic alternation of noise and self-oscillatory states.** Each dynamic state occurrence instants and duration are random in the ensemble of realizations similar by P_c, and α, $(P_c = 0.4$ MPa$)$, Fig.9;

- **self-oscillatory combustion** $(f_{101} = 6300$ Hz, $P_c = 0.6...0.7$ MPa$)$, Fig.10.

Thus it can be stated that in the $P = 0.4...0.6$ MPa, $\alpha = 0.65...0.75$ range the dynamic state of the combustion process is characterized by stochastic ambiguity and the ambiguity symptoms differ from those described in the previous section.

To understand the observed transition nature, let us consider a model of potentially self-oscillatory system being in the mode of hard excitation.

3.1. Model of potentially self-oscillatory system in the mode of hard excitation.

It should be noted that in the case under consideration the self-oscillation is excited at a frequency of combined first longitudinal mode –first tangential mode $(f_{101} = 6300$ Hz,$)$. Therefore a simple one-mode approximation will be used in devising a model of dynamic transitions. In such approximation the combustion

chamber stochastic dynamics can be described by the following model of potentially self-oscillatory system [1,2]:

$$\frac{d^2 P'}{dt^2} + 2\beta(\lambda)\frac{dP'}{dt} + \omega_0^2 P' = \xi(t)\omega_0^2,$$ (1)

where: P' is oscillatory pressure;

t is time;

ω_0 is a circular frequency ;

$\beta(\lambda)$ is an effective coefficient of decay or generation, a nonlinear function of amplitude λ;

$\xi(t)$ is a stationary normal delta-correlated (white) noise of turbulent combustion.

With the proviso that $\dfrac{\omega_0}{\beta(\lambda)} \gg 1$, the following evolutionary equation for pressure oscillation amplitude λ corresponds to equation (1)[3]:

$$\frac{d\lambda}{dt} = -\beta(\lambda)\cdot\lambda + \omega_0 N_0 / 8\lambda + \zeta(t).$$ (2).

Here: N_0 is the spectral intensity of random noise $\xi(t)$;

$\zeta(t)$ is normal delta-correlated random function:

$$R(\tau) = \langle \zeta(t)\cdot\zeta(t+\tau)\rangle = \omega_0^2 \cdot N_0 \cdot \delta(\tau)/4.$$

Within the framework of the self-oscillatory system with hard excitation a particular $\beta(\lambda)$ relationship is postulated which provides the existence of self-oscillation unstable limit cycle and stable limit cycle.

Evolutionary equation (2) describes one-dimension Markov process with coefficients of "drift" and "diffusion", equations (3) and (4), respectively:

$$a(\lambda) = -\beta(\lambda)\cdot\lambda + \omega_0^2 N_0 / 8\lambda,$$ (3)

$$b(\lambda) = \omega_0^2 N_0 / 4.$$ (4)

Equation (2) has the potential function in the following form:

442

$$\hat{O}(\lambda) = -\frac{1}{2}\int_0^\lambda \left(-\frac{\beta(\lambda)\cdot\lambda}{\beta_0} + \frac{\sigma^2}{\lambda}\right)d\lambda, \qquad (5)$$

where:

$$\sigma^2 = \omega_0^2 \cdot N_0/8\beta_0, \qquad (6)$$

$$\beta_0 = \beta(\lambda) \quad \text{at} \quad \lambda \to 0, \qquad (7)$$

and a stationary state probability density [3,4]:

$$P_{st}(\lambda) = C_1 \exp[-2\hat{O}(\lambda)/\sigma^2] = C_1\lambda \exp\left[-\frac{1}{\beta_0\sigma^2}\int_0^\lambda \lambda\beta(\lambda)d\lambda\right]. \qquad (8).$$

The C_1 constant is determined from the norming condition $\int_0^\infty P_{st}(\lambda)d\lambda = 1$.

The calculated relations $\Phi(x)$ and P_{st} are shown in Fig 11 ($x = \lambda/\sigma$).

As can be seen, $\Phi(x)$ potential has two minima that correspond to locally stable state of dynamic equilibrium: the left minimum corresponds to the noise state while the right one corresponds to the self-oscillatory state. Unstable dynamic equilibrium corresponds to the unstable limit cycle.

The distribution of state probability density $P(x)$ for a specific form of function $\beta = \beta(x)$ is bimodal and the maxima of probability density correspond to the minima of potential $\Phi(x)$. The probability density minimum corresponds to the maximum of potential $\Phi(x)$, i.e. to the unstable limit cycle.

The self-excitation of the dynamic system described by Eq. (1) is stochastic in principle, in the sense that it is impossible to know a priori the exact time instant when excitation will occur i. e. the time of system transition from noise to self-oscillatory state.

The mean expectation time of self-excitation event depends on the noise intensity N_0 and the potential barrier height h_1. If the potential barrier is sufficiently high (which corresponds to a high amplitude of the unstable limit cycle compared to σ, Eq. (6)), and the noise intensity N_0 is small, the expectation

time can be very large, and self-oscillation excitation will be a very rare event, accordingly. And vice versa, with low potential barrier and high noise intensity, random transitions of "noise <—>self-oscillation" will occur. In this case pressure oscillogram for i-realization will look like alternating noise and self-oscillation regions, similar to those shown in Fig.9.

Thus within the limits of Model 1, the nonreproducibility of self-oscillation excitation, with 'external' conditions being constant, is attributed to the presence of unstable limit cycle and random wide-band noise $\xi(t)$.

3.2 System Identification

The task of identification of a potentially self-oscillatory system is stated in this case as follows: to what extent the initial uncertainty of the statistic model of the observed dynamic transitions can be reduced.

The model of potentially self-oscillatory system with hard excitation (Model 1) is taken as a base model. The following relationship connecting $\beta(\lambda)$ with the narrow-band noise amplitude probability density is obtained:

$$\frac{\beta(\lambda)}{\beta_0} = \sigma^2 \left\{ \frac{1}{\lambda^2} - \frac{\Psi(\lambda)}{\lambda} \right\}, \tag{9}$$

where

$$\Psi(\lambda) = \frac{d\{\ln P_{st}(\lambda)\}}{d\lambda}, \tag{10}$$

and $P_{st}(\lambda)$ is a function of amplitude probability density, estimated experimentally based on the realization of the random process $\lambda(t)$.

The realization of oscillatory process $P' = P'(t)$ filtered in the band $f=1000\ldots10000$ Hz and the corresponding noise spectrogram for the region that precedes oscillation self-excitation (t =4...5 s) are shown in Fig.12 (a compressed oscillogram is presented). The narrow-band peak with decrement $\overline{\beta T} \approx 0.04$ observed in the vicinity of $f_{101} \approx 6150$ Hz corresponds to combined first tangential mode-first longitudinal mode of the chamber volume natural acoustical oscillations.

The estimate of probability density of envelope (amplitude) $\lambda(t)$ of narrow-band noise $P'(t) = \lambda(t) \cdot \cos\ (2\pi f_0 t + \varphi(t))$ in the region that precedes oscillation self-excitation is shown in Fig.13. The corresponding estimate of the decay coefficient [β] - amplitude [λ] relation. As can be seen in Fig.13, the reconstructed relation $\beta = \beta(\lambda)$ is of a falling character and predicts the existence of unstable limit cycle with amplitude $\lambda_{ULC} \approx 8\sigma$. The found fact of unstable limit cycle existence allows identifying the system being studied within the base model of a potentially self-oscillatory system with hard excitation of self-oscillation (Model 1).

It should be noted that for the case of dissipative system of the second order, $\beta(\lambda) = \beta_0 = const$, the distribution (8) changes to the known Rayleigh distribution for the amplitude (envelope) of linear narrow-band noise:

$$P_{st}(\lambda) = \frac{\lambda}{\sigma^2} e^{\frac{-\lambda^2}{2\sigma^2}} .$$

In the framework of Model 1, actually deterministic transition from a locally stable noise state into a self- oscillatory one can be performed by applying a pulse to the system (combustion zone). The pulse should be high sufficiently to overcome the potential barrier, (hard pulse excitation of the system). In this case oscillation with an amplitude of $\lambda > \lambda_{ULC}$ should develop in the system after the disturbance application.

In the same time, Model 1 assumes a possibility of a reverse transition from a self-oscillatory state to noise in case the pulse is applied as antiphase to the existent self-oscillation.

Such situation is shown in Fig 14 for the chamber under investigation. The pulse disturbance was applied to the chamber reaction zone by exploding an explosive charge.

It should be mentioned however that treatment of effects of self-oscillation excitation and termination under the action of artificial disturbance in the framework of Model 1 is not quite correct. There is reason to believe that, under the conditions of the described experiments, the artificial pulse disturbance,

apart from acoustic effect, produce a parametric effect on combustion (it changes the combustion zone pattern, possibly including change in the flame stabilization regime). This is suggested, in particular, by a specific character of the dynamic transition of "noise to self-oscillation": the decay of oscillatory response actually to the initial noise level, with a subsequent smooth transition to the stable limit cycle, Fig.15. A possibility of self-oscillation termination on application of a pulse to the fuel feed cavity is another evidence of parametric effects (Fig.16). The establishment of a new 'noise' stationary state on pulse application is also shown in Fig.16. This state differs in noise spectrum and level from the state that preceds oscillation self-excitation.

Thus the given series of experiments reveals a possibility of realization of combustion zone multiple stationary patterns, which is beyond the frames of the base Model 1.

The treatment presented shows that while devising diagnostic models of oscillatory combustion in LRE chambers it is necessary to consider, along with 'hard excitation' effects, a possibility of bifurcation of combustion stationary modes and dynamic state ambiguity resulted from the bifurcation..

Conclusion

From the conducted studies it is concluded that at least two aspects should be taken into consideration for devising adequate models of unstable combustion in LRE:

- possibility of realization of combustion zone ambiguous (bistable) stationary states with invariant parameters of the propellant feeding system.;

- combustion zone nonlinear sensitivity to chamber natural acoustic field that results in the occurrence of self-oscillation unstable limit cycle of one or other mode.

Both aspects of realization of flame self-consistent pattern may lead to the nonreproducibility of self-oscillation excitation in LRE combustion chamber.

References

1. Artamonov K.I. Thermodynamic Instability. M. Mashinistroenie, 1982. (Rus.)

2. Ilchenko M. A. and others. Operating Process Stability in Spacecraft. M. Mashinistroenie, 1995. (Rus.)

3. Stratonovich R. L., Landa P.S. Noise Action on a Hard-Excited Generator. IVUZ . Radiophysics, v.2, 1, 1959. (Rus.)

4. Horsthemke W., Lefever R. Noise-Induced Transitions. Berlin, Heidelberg, New-York, Tokyo: Spriger Verlag, 1984 (Transl. to Rus.).

Fig. 1. Symptoms of spontaneus combustion instability
(compressed displays of oscillatory processes).

Fig. 2. Model combustion chamber with
single coaxial injection element.

Fig. 3. Photograph of the diffusion flame.
1. Flame stabilization inside the injection element
in the vicinity of the fuel post edge.
2. Flame stabilization outside of the injection element
above the oxidizer tube.

Fig. 4. Dynamic states and path of the system movement in the domain of governing parameters:
a) flame stabilization as per Scheme 1;
b) flame stabilization as per Scheme 2;
(propellaut feeding parameters, V_o and V_p, marked with similar figures are completely identical).

Fig. 5. Air injection induced transition from stabilization as per Scheme 1 to Scheme 2.

Fig. 6. Schematic of combustion instability study (all dimensions are in millimeters)

Fig. 7. Combustion chamber operation regimes.

Fig. 8. Noise state of combustion process.

Fig. 9. Chaotic alternation of noise and self-oscillatory states.

Fig. 10. Self-oscillatory combustion.

Fig. 11. Decay coefficient β, probability density P_{st} and potential Φ versus oscillation relative amplitude.

h_{1-2} – Potential barrier of the transition from state 1 to state 2

h_{2-1} – Potential barrier of the transition from state 2 to state 1

Fig. 12. Spontaneous dynamic transition "noise → self-oscillation":
   a) compressed oscillogram;
   b) noise spectrum in the region preceding oscillation self excitation.

Fig. 13. Estimate of probability density of noise amplitude (a) and reconstructed relation "decay coefficient-amplitude" (b).

Fig. 14. Self-oscillation excitation (a) and termination (b) artificial
disturbance (disturbance applied to the chamber reaction zone).

461

Fig. 15. Character of self-oscillation excitation artificial disturbance (disturbance applied to the chamber reaction zone).

Fig. 16. Self-oscillation termination (disturbance applied to fied cavity).

Fundamental Combustion Instability Research at Glenn Research Center in the 90's

by

Kevin Breisacher

May 27-28 1999
Paris, France

GRC=LeRC

40K LOX/CH4 Stability testing

ROCCID

ROCCID LOX/RP-1 stability testing

HICCIP

PacAstro

FASTRAC

"Unique Combustion Stability Validation Database"

for "same" co-ax element

- air/H2O simulants

- liquid/ gaseous nitrogen simulants

- hot fire Lox/H2 PDPA data

- single element instability data

"Coaxial Injector Spray Characterization Using Water/Air as Simulants", Michelle Zaller, Mark klem, 28Th JANNAF Combustion Meeting, Volume 2, pp151-160, 1993.

"LOX/Hydrogen Coaxial Injector Atomization Test Program", Michelle Zaller, 27th JANNAF Combustion Subcommittee Meeting, Volume 3, pp 229-237, 1990.

"Coaxial Injector Reacting and Non-Reacting Cyrogenic Spray Characterization", Mark Klem, 32nd JANNAF Combustion Subcommittee Meeting and Propulsion Engineering Research Center 7th Annual Symposium, Vol 2, 1995.

"Axisymmetric Single Shear Element Combustion Instability Experiment", Kevin Breisacher, 29th Joint Propulsion Conference, AIAA 93-1953.

Cylindrical Chamber Design

Throat section
(for hot firing)

Gas purge for cooling window

Fused silica window

Pr = 1.2
Gaseous and Liquid Nitrogen
No swirl
Gaseous Nitrogen: T = 55°F, .006 lb/s
Liquid Nitrogen: T = -260°F, .024 lb/s

Pr = 0.3
Gaseous and Liquid Nitrogen
No swirl
Gaseous Nitrogen: T = 55°F, .006 lb/s
Liquid Nitrogen: T = -270°F, .024 lb/s

Vaporizing Liquid Nitrogen Spray Data for Varying Chamber Pressures

Liquid nitrogen flow rate .024 lb/s; gaseous nitrogen flow rate .012-.015 lb/s.

Mean Drop Size and Velocity Measurements in

Liquid Oxygen/Gaseous Hydrogen Sprays

CHAMBER PRESSURE 160 PSIA ($P_r = 0.2$)

$Re_L = 60,000$

TEST PARAMETERS

FOR PHASE/DOPPLER DROP SIZE MEASUREMENTS

	Liquid/Gaseous Nitrogen	LOX/Gaseous Hydrogen
Pr	0.3	0.2
Tr	0.7	0.6
Re(L)	71,000	60,000
$\dot{m}(L)/\dot{m}(g)$	2,3	6,10
V(g) (ft/s)	78, 120	650, 820
Ma(g)	.07, .10	.15, .19

Figure 4.—Pressure transducer locations.

Figure 5.—Schematics of LOX post configurations.

Figure 8.—Cascade plot of pressure for unstable test 292.

Figure 9.—Power spectral density plot for unstable test 292.

Figure 10.—Expanded digitized pressure trace for unstable test 286.

Figure 11.—Power spectral density plot for unstable test 286.

Figure 12.—Variation of oscillation amplitude with mixture ratio (configuration 3, Df - .235").

High Energy Laser as a Stability Rating Device

Disclaimer: results presented are by no means
   a thorough evaluation of the concept

Piggybacked at tail end of laser ignition test program

"High Energy Lasers as a Stability Rating Device"
Kevin Breisacher, Pennsylvania State Propulsion
Engineering Research Center,Volume 2, pp 148-152, 1995.

Bombs

ADVANTAGES

- may simulate "natural" engine disturbance
- database from experience
- can be positioned throughout the chamber

DISADVANTAGES

- may not create a resonance of sufficient amplitude
  to incite an instability
- chamber damage possible
- shrapnel damage possible
- thermal initiation: fizzling
- several bombs per test sometimes possible
- danger: unexploded bomb
  ejecting a bomb

Laser Pulsing

ADVANTAGES

- clearer determination of stability margin
- multiple tests
  (setup-oscillation, turn-off, etc.)
- no shrapnel
- aid in tuning stability aids
- potential HM device ("enhanced noise")

DISADVANTAGES

- optical access
  ZnSe
  Pcb
  laser ignition
- sensitivity to location

Energy

1 grain RDX ———————▶ 386 J

100 W CO2 ——————▶ 3.68 s

(of course want to couple to combustion process)

Power

100 W   vs. $\dfrac{386 \text{ J}}{50 \text{ microseconds}}$ = 7.36 MW

Why CO2 ?

– cheap, reliable
$15K / 100 W

– RP1 fairly absorbent at 10.6
(optics too big and costly to create a laser spark at 10.6)

PERCENT ABSORBED

WAVELENGTH IN MICRONS

WAVENUMBER CM⁻¹

485

Test Engine

Length	8.88"
Diameter	2.06"
Pc	70 psi
MR	1.7 – 2.5

4 GOX/RP1 triplets

nominal 1L 2622 Hz

1. CO2 Laser
2. Periscope
3. 45 – degree mirror
4. Focusing lens
5. Test combustor

CO2 Laser

Synrad 57–1 sealed gas, RF excitation

Power	100W
beam diameter	4 mm
wavelength	10.6 microns
pulse rate	2 – 10 kHz (at 50% duty cycle)
pulse energy	32 mJ – 17 mJ
	2 kHz 5 kHz

Attempts to drive at
    2600 Hz, 3000 Hz, 5000 Hz, 5200 Hz

  – no oscillations observed except when driving at 5000 Hz

Driving at 5000 Hz
    oscillations ~ 3% of Pc
    at 2380 Hz
    beat frequency ~ 125 Hz

  – power at 5000 Hz 35% > that at 2600 Hz or 5200 Hz

  – closer to 1L frequency at half 5000 Hz

Figure 3a. - Pressure Trace

Figure 3b. - Expanded Pressure Trace

SUMMARY

Despite far from optimal conditions (unsteady combustion, inability to move the focal point) we were consistently able to drive very small amplitude oscillations with laser pulsing.

GENCORP
AEROJET
TechSystems

Atomization of an Impinging
Jet Fan is Periodic?

M16/D8/Lq flckt:3.8

(a) Flow apparatus.

(b) Photographic apparatus.

(c) Frequency measurement apparatus.

Figure 1. - Schematic diagram of impinging-jet apparatus and instrumentation.

v = 2.5 m/s
$Re_D = 4,800$

v = 3.1 m/s
$Re_D = 6,000$

v = 4.9 m/s
$Re_D = 6,900$

v = 12.2 m/s
$Re_D = 6,900$

v = 21.1 m/s
$Re_D = 41,500$

Figure 4 Comparison of multiple-exposure (time-averaged) with instantaneous photographs.

500

Ultrafast Imaging of Sprays

"Picosecond Imaging of Sparys", L. Wabg (CCNY), Kevin Breisacher, et al, Pennsylvania State University Propulsion Engineering Research Center, Volume 2, pp 221-225, 1995.

Optical Imaging

Input Laser

Object

Diffuse

Ballistic

Snake

Time

Diffuse

Snake

Ballistic

502

Time-Resolved Kerr-Fourier Imaging System

Results

T = 2 sec   T = 5 sec   T = 10 sec

Early time two-dimensional shadowgram image of water phantom droplet in a highly scattering host 50 mm thick of 2% diluted intralipid stok solution.

Probe beam : 1054 nm; Pump beam : 527 nm

Experimental Setup

JET DROP

505

Results

Time-Resolved Image of Jet-Fuel Spray

Area of
integration
~ 6 pixels
per channel

(20 μm/pixel)

3D Jet Droplets Imaging

90° Transmitted
2D image

0° Transmitted
2D image

(A) = a$_{ij}$

Jet Sprays

(B) = b$_{jk}$

Laser Beam
0° illumination

(A)

(B)

Laser Beam
90° illumination

Computer reconstruction

Reconstructed 3D image

Summary

- Time-resolved imaging technique has been applied to jet stream: a simulated rocket engine injection element.

- Refinements to these techniques may enable drop size measurements in the highly scattering, optically dense region of multi-element rocket injectors.

- These types of measurements should greatly enhance the design of stable and higher performing rocket and automobile engines.

ISTANBUL TECHNICAL UNIVERSITY

FACULTY OF MECHANICAL ENGINEERING

Prof. Dr. A. Nilufer EGRICAN

Dean

URL: www.mkn.itu.edu.tr

E-Mail: egrican@mkn.itu.edu.tr

DIVISIONS

- Fluid Mechanics and Hydraulic Machinery

- Thermodynamics, Heat Transfer and Energy

- Design

- Materials and Manufacturing

- Theory of Machinery, System Dynamics and Control

- Mechanics

- Automotive

Faculty
43 Professors

18 Associate Professors

26 Assistant Professors

7 Lecturers

Student Profile
1600 Undergrauate Students

350 Graduate Students

ABOUT ITS PAST

At ECOS' 95 July – 1995 Istanbul, closing session recommends establishing International Centre for Applied Thermodynamics.

In December 1997 official establishment started.

In July 1998 at ECOS' 98 in Nancy – France, first General Assembly met.

Approval of Statutes & By-Laws.

ELECTION:

Prof. Elias GYFTOPOULOS – U.S.A. as President, Prof. Richard GAGGIOLI – U.S.A. and Prof. Bjorn QVALE – Denmark as Vice Presidents, Prof. George TSATSARONİS as Chairman of the Executive Committee and Prof. A.Nilüfer EGRICAN as Secretary General of the Centre.

International Centre for Applied Thermodynamics (ICAT)

founded in 1997

To promote and foster international cooperation in the field of

Applied Thermodynamics and its applications

OBJECTIVES

The general objective of the Centre is to promote and foster international cooperation in the field of Applied Thermodynamics and its applications.

MAIN ACTIVITIES

9.1 Organizing conferences, symposia, seminars, forums, schools and courses on   topics in the Field;

9.2. Publishing material in the Field, such as proceedings, journals, reference books, directories, reports and data sheets;

9.3. Collecting, evaluating and disseminating technical information in the Field;

9.4. Promoting and assisting in the conduct of research in the Field;

9.5. Promoting the exchange of personnel between organizations working in the ield;

9.6. Undertaking activities conducive to the general objectives of the Centre;

9.7. Co-operating with international and national organizations having an interest   in the Field.

MEMBERSHIP

The membership of the Centre is composed of national, regional and international scientific and professional Institutions active in the Field.

ORGANIZATION

```
                    PRESIDENT
                        |
        +---------------+---------------+
        |                               |
 SCIENTIFIC COUNCIL              VICE - PRESIDENTS
        |
 EXECUTIVE COMMITTEE
        |
        +---------------+---------------+
        |                               |
 CHAIRMAN AND                   SECRETARY GENERAL
 VICE-CHAIRMAN                          |
                        +---------------+---------------+
                        |                               |
                   ASSOCIATE                       OFFICE OF
                   SECRETARY                        I.C.A.T.
                    GENERAL
```

MEMBERS OF THE EXECUTIVE COMMITTEE

Prof. A. Özer Arnas

Prof. Adrian Bejan

Prof. Michel Feidt

Prof. Erich Hahne

Prof. G. Hirs

Prof. G. Manfrida

Prof. Phillip Mathieu

Prof. Björn Qvale

Prof. Gunnar Svedberg

Prof. Stanislaw Sieniutycz

Prof. Antonio Valero

Prof. George Tsatsaronis (Chairman)

Prof. Chiristos A. Frangopoulos

Prof. Michael J. Moran

MANAGING OFFICERS

Vice-Chairman of the Executive Committee: Prof. Yalcin Gogus, O.D.T.U. – Turkey

Secretary General: Prof. A. Nilufer Egrican, I.T.U. – Turkey
Assistant Secretary General: Prof. Aksel Ozturk, I.T.U. – Turkey
Prof. Ediz Paykoc, O.D.T.U. – Turkey

PAST ACTIVITY

A Short Course on Thermoeconomics And Cogeneration

One of the goals of sustainable development is higher fuel efficiency at lower product cost for systems that use or produce power and heat. The course introduced a methodology that aims at this goal under the name *Thermoeconomics*. The methodology allows the intensive analysis of design concepts in order to reveal opportunities of fuel and cost savings.

The course was held at the Mechanical Engineering Faculty of Istanbul Technical University between 13-15 April 1999. Prior to lectures of Prof. El-Sayed, Prof. A.Yalcin Gogus and Prof. Taner Derbentli of Istanbul Technical University reviewed prerequisite thermal design models, economic calculations and basics of optimization. Yehia El-Sayed, emeritus Profesor of Massachusetts Institute of Technology, is President of Advanced Energy Systems Analysis Inc..

PUBLICATIONS OF THE CENTRE

1-Proceedings of ECOS '95 (3 Volumes)

2- Proceedings of a work shop on Education of Applied Thermodynamics

3 -International Journal of Applied Thermodynamics

VOLUME 1 NO.1-4

International Journal of

Applied Thermodynamics

PROJECTS

- **Analysis of Reactive Flow in Solid Rocket Motors (NATO-CRG , Univ. of Colorado at Boulder,USA)**

- **Unsteady Flow in Centrifugal Compressors (NATO-CRG, von Karman Institute, Belgium)**

- **Experimental Analysis of Louvered Fin Heat Exchangers(Univ. of Illinois at Urbana,USA)**

- **Experimental and Numerical Analysis of Falling Film Behavior(Univ. of Illinois at Urbana,USA)**

- **Thermoacoustic Refrigeration (Johns Hopkins Univ.,USA)**

ANALYSIS OF REACTIVE FLOW IN SOLID ROCKET MOTORS

This study is concerned with modeling transient flow dynamics when there is interaction between propellant burning and the fluid dynamics in a solid propellant rocket motor chamber. The results will provide new perspectives about the physical processes occuring in the system. The application to the design processes should foster the development of more reliable motors with predictable performance.

E-mail:kadir@mkn.itu.edu.tr

FLOW IN A SOLID ROCKET MOTOR

GRID STRUCTURE

VELOCITY PROFILES

Axial Velocity Profiles at Different Times

$t = 15$

$t = 3$

$t = 30$

ANALYSIS OF THE FULL 3D FLOW IN CENTRIFUGAL IMPELLER

A flow solver, that allows the evaluation of the effects of different design parameters on the impeller performance, has been developed. Full 3D Navier - Stokes equations, including artificial compressibility approach for incompressible flows, are written in quasi-conservative form and are solved by using a finite volume method that employs Runge-Kutta time stepping. The solver is used to analyze the flow field inside different pump impellers for which experimental data is available. The comparison of the calculated and measured results reveals that the flow solver is capable of predicting impeller performances.

E-mail:erkan@mkn.itu.edu.tr

FLOW INSIDE IMPELLER BLADES

Grid Structure for Centrifugal Impeller Blades

Velocity Field

Pressure Distribution

Comparison of Numerical and Experimental Velocity Distributions between Blades

EXPERIMENTAL AND NUMERICAL ANALYSIS OF FALLING FILM BEHAVIOR

The scope of the present study may be summarized as to analyse the inline-staggered jet modes and the jet instability and to simulate the jet. The new data will allow the effects of tube diameter and spacing to be ascertained. Tube diameter effects will be captured using the dimensionless Ohnesorge (Oh) number, and tube spacing effects are captured with s/D..

The mentioned effects are being analysed numerically. The jet pattern are being simulated in three domains of the computation: the jet, the liquid film surrounding the tubes and the liquid bridge. The results will be compared to the experimental ones.

E-mail : seyhan@mkn.itu.edu.tr

EXPERIMENTAL ANALYSIS OF LOUVERED FIN HEAT EXCHANGERS PERFORMANCE

The main objective of this work is to provide a better understanding of the flow and the heat transfer phenomena in a louvered geometry. Therefore, previous to the experiments, an analytical work will be done for predicting the critical values of the geometric parameters such as , fin pitch, louver pitch, louver angel and fin thickness. Then , the manufactured specimens will be tested and the quantitative and qualitative data will be evaluated. The results will be a new input for a better design of higher performance.

E-mail: honbasi @ mkn.itu.edu.tr

SMOLDERING COMBUSTION OF HORIZONTAL DUST LAYERS IN A FORCED AIR FLOW

E-mail: erhan @ mkn.itu.edu.tr

SMOLDERING COMBUSTION OF HORIZONTAL DUST LAYERS IN A FORCED AIR FLOW

In order to define the effects of these properties on the smoldering combustion propagation and on the flaming or extinguish, smoldering combustion of horizontal dust layers in a forced air flow was experimentally investigated. The experiments were carried out i... . combustion box lined with ceramic fibrous and refractors with a thickness of 70 mm. The inside of this combustion box measured 150 x 200 x 500 mm. Wood dust and tobacco were used as experiment material. The air velocity supplied over the fuel bed was in the range of 1-4 m/s. The experiments were carried out for both forward and reverse smoldering combustion. The combustion wave propagation velocity parallel to the air supply direction was higher than the velocity of the wave perpendicular to the fuel bed. The resultant velocity increased with the increasing air velocity for both forward and reverse smoldering combustion. In the following pictures, the top view and the cross section of the combustion wave are seen.

E-mail: erhan @ mkn.itu.edu.tr

secondary air

primary air

Domestic Downdraft Coal Burner

EFFICIENCY ENHANCEMENT OF THE COAL FIRED DOMESTIC HEATERS AND STOVES

The main objectives of this work were to obtain smokeless combustion and continuously coal feeding. The first group of experiments were carried out on the original hand fired furnace and later the furnace was reconstructed. The experiments were repeated on this new developed furnace. The results of the experiments were showed that the burning was taken under control, the excess air and CO emission were decreased and the efficiency raised to the value of %80.

E-mail: uralcan @ mkn.itu.edu.tr

UNDERFEED FIXED BED COAL COMBUSTION

E-mail : erhan @ mkn.itu.edu.tr

Figure 1. Combustion ...

UNDERFEED FIXED BED COAL COMBUSTION

The object of this work is to develop a mathematical model of steady-state underfeed fixed bed coal combustion. In this combustion system the coal is fed from underneath the bed so that the reaction front is traveling down and the volatiles are carried up into the bed. Air is supplied through the tuyeres. The fixed bed coal combustion is described mathematically for a thin coal bed layer by means of energy, mass and species conservation equations. The model is supported with the computer codes obtaining reaction rates, physical properties and thermal conductivity. Using this computer simulation, combustion product concentrations, temperature and fixed carbon gradients can be predicted.

E-mail: erhan @ mkn.itu.edu.tr

FORWARD AND BACKWARD SMOLDERING COMBUSTION

E-mail : erhan @ mkn.itu.edu.tr

FORWARD AND BACKWARD SMOLDERING COMBUSTION

E-mail : erhan @ mkn.itu.edu.tr

The main object this work is to investigate one dimensional smoldering combustion in dust layers. The experiments are carried out in a cylindrical combustion chamber with wood dust. The forward and backward smoldering combustion are investigated for various air supply velocities. The forward combustion are appeared to be more steady.

- **FLUIDIZED BED COMBUSTION OF LIGNITES AND COAL-BIOMASS MIXTURE**

- **COAL AND GAS DESULFURIZATION**

- **KINETICS OF COAL COMBUSTION AND CARBONIZATION**

- **BIOMASS AND ALTERNATIVE FUELS**

- **COAL-WATER SLURRY PREPARATION AND COMBUSTION**

- **PYROLYSIS OF COAL AND PRODUCT CHARACTERIZATION**

INFLUENCE OF HORIZONTAL FINS WITH LOW THERMAL CONDUCTIVITY ON NATURAL CONVECTIVE HEAT TRANSFER FROM VERTICAL SURFACES

E- mail : turkmen @ mkn.itu.edu.tr

INFLUENCE OF HORIZONTAL FINS WITH LOW THERMAL CONDUCTIVITY ON NATURAL CONVECTIVE HEAT TRANSFER FROM VERTICAL SURFACES

Natural convective heat transfer from a vertical plate with uniform base temperature and having transverse rectangular fins of low thermal conductivity has been investigated for a wide range of the spacing-to-fin height ratio. A holographic interferometer was employed as well, to visualise the temperature distribution in the boundary layer. Holographic images of thermal field were recorded using a video camera. These records were loaded on a PC using a frame grabber. A software for digital processing of these images has been developed and used for the analysis.

E-mail: turkmen @ mkn.itu.edu.tr

FORCED CONVECTIVE HEAT TRANSFER IN POROUS MEDIUM OF WIRE SCREEN MESHES

The hydrodynamic and heat transfer characteristics of a porous medium consisting of 20 wire screen meshes are examined theoretically and experimentally. The hydrodynamic experiments are conducted for the range of Reynolds number based on mean velocity and wire diameter from 1.5 to 12. The Ergun's constants and thermal dispersion coefficients are calculated in this range. Nusselt number variation is determined in both thermally developing and fully developed flows by the help of forced convection heat transfer experiments conducted for the uniform heat flux boundary condition. Correlation functions of Nusselt number in the range of fully developed and thermally developing, and of thermal entrance length are obtained from experimental data. Solutions of momentum and energy equations simulating the experimental model are obtained numerically with variable porosity and the anticipated thermal dispersion coefficients. The thermal dispersion coefficients well-adjusted to the experimental data are determined by numerical solution of the energy equation.

E- mail : mozdemir @ mkn.itu.edu.tr

Experimental Apparatus

1)Upstream reservoir, 2)Dividers, 3)Test section, 4)Porous medium, 5)Downstream reservoir, 6)Valve, 7)Pressure taps, 8)Manometer, 9)Direct current source, 10)Temperature props, 11)Milivoltmeter, 12)Scanner, 13)Ice bath, 14)Water filter, 15)Pump

Test section and upper portion

3)Test section, 4)Porous medium, 7)Pressure taps, 10)Temperature probes, 16)Copper plate, 17)heaters

Variation of non-dimensional pressure gradient with respect to Reynolds Number.

Nu_x-x/L variation calculated by considering $\gamma=0.08$ and $\omega=1.5$ for the first medium.

Nu_x-x/L variation calculated by considering $\gamma=0.27$ and $\omega=1.5$ for the second medium.

LOW-SPEED WIND TUNNEL
800 x 800 mm, 10 m/s < Velocity < 30 m/s

# HIGH-SPEED WIND TUNNEL

Cone Flow and Mach Waves
M = 2.804

150 x 150 mm

0.6 < Mach < 2.2 and 2.3 < Mach < 4.0

HIGH-SPEED WIND TUNNEL

Rocket Exp. - M=2.655

30 X 60 mm , 0.3 < Mach < 2.2
Continuous Working

552

İSTANBUL TECHNICAL UNIVERSITY

Faculty of Mechanical Engineering
Mechanics Division

FLUIDS LABORATORIES

www.akis.itu.edu.tr

Dr. İ. Bedii Özdemir, Assoc. Professor

ÜNİVERSİTESİ
İSTANBUL TEKNİK
1773

FLUIDS LABORATORIES

Subsonic Flows Laboratory

"ANKA" Wind Tunnel

Supersonic Flows Laboratory

"TURNA" Lateral Jet Facility

"ISLIK" Supersonic Jet Facility

Combustion Facility

Research on Aerodynamic Flows

- Problems related to missile dispersion in ground proximity due to instabilities associated with dynamic loading on nearby surfaces by the impingement and deflection of rocket exhausts

- High angle of attack and unsteady rocket aerodynamics

- Side-jet technology

DESIGN
of
LAUNCHERS

IMPROVEMENT
OF
FLIGHT STABILITY
and CONTROL

● Supersonic jet-wall/tube interactions
● Supersonic two-phase free jets

● Forebody geometry and spinning effects in supersonic flows
● Side-jet effects on rocket aerodynamics
● High angle of attack rocket aerodynamics
● Vortex effects
● Effects of exhaust jets on rocket aerodynamics

Research on Combustion

- **Combustion without flame**

- **Low-NO$_x$, high IFGR Combustor Design**

- **Applications on gas turbine technology**

CURRENT PROJECTS

- **Reduction of Missile Dispersion (Approved for grant)**

  Sponsored by: Ministry of Defense (MSB, Türkiye)

- **High Pressure Low-NO$_x$ Flameless Combustion System for Gas Turbines (Approved for grant)**

  Sponsored by: State Planning Organization (DPT, Türkiye)

- **Unsteady Flow and Vorticity Interactions at High Angle of Attack (In progress)**

  Sponsored by: Defense Industries Research and Development Institute (SAGE, Türkiye)

- **Vorticity Generated by Side Jets (In progress)**

  Sponsored by: Defense Industries Research and Development Institute (SAGE, Türkiye)

COMPLETED PROJECTS

Reduction of Missile Dispersion (1996-98)

Sponsored by: *State Planning Organization (DPT, Türkiye)*

Study on Rocket Aerodynamics and Jet Effects on Model Geometries (1997-98)

Sponsored by: *Scientific and Technical Research Council of Turkey (TÜBİTAK, Türkiye)*

Reduction of Missile Dispersion and Improvement of Flight Stability (1996-98)

Sponsored by: *University Research Funds (İTÜ, Türkiye)*

Supersonic Jet/Wall Interactions (1995-97)

Sponsored by: *Defense Industries Research and Development Institute (SAGE, Türkiye)*

Aerodynamics of Crossflow with Side Jets (1995-97)

Sponsored by: *Defense Ids. Resch. and Dev. Ins. (SAGE, Türkiye)*

SUBSONIC FLOWS LABORATORY

"ANKA" Wind Tunnel

Type   : Positive-pressured
Driver   : 45 kW AC motor
Fan Type   : Radial
Test Sec.   : 0.5x0.5 m² square
Test Length : 2.5 m
Max Spd.   : 55 m/s
Turbulence : 0.4%

"TURNA" Lateral Jet Facility

Type   : Radial fan with settling chamber.
Driver   : 2.5 kW AC motor
Jet Speed   : 120 m/s
Properties : Eqp. with nozzles of 30 and 52mm diameters

SUPERSONIC FLOWS LABORATORY

"ISLK" Supersonic Jet Facility

• **Type:** Blow down (to ambient atmosphere)
• **Mach number:** 2.5
• **Eqp. with:**
  • Stagnation chamber of d=0.29 m with nozzles d=20 mm, and 35 mm
  • High pressure facility :
    - Screw-type comp (5.5 m³/min - 8 bar)
    - Receiver tank (1 m³)
    - Piston-type comp (0.4 m³/min - 50 bar)
    - High pressure air tanks (2.5 m³ -250 bar)

Instrumentation and Measurement Techniques

- **Hot-Wire Anemometry**

  3-D velocity measurements of subsonic turbulent flows; velocity measurements with X-wire and miniature probes, 1-D measurements of supersonic flows with film probes, surface friction force and temperature measurements

- **Thermocouples**

- **Fast Response Pressure Transducers**

- **Shadowgraph and Optical Systems**

- **Flow Visualization Set-up**

- **Pitot-tube and Pressure-based Instrumentations**

# A short view of experiments

Supersonic flow over a bluff body

$\xi = 1.63$

$\xi = 1.66$

$\xi = 1.70$

Photographs of supersonic free jets

563

Pressure measurements on a tangent ogive forebody at 30 degree angle of attack

Pressure tapped body

Wall pressure fluctuations
dowstream
of a side jet in crossflow

Shadowgraphs of a supersonic
jet impingement with
10 degrees inclination

Rayleigh measurement of temperature in the reaction zone of a combustion flow without flame

LIF measurement of OH concentration in the reaction zone of a combustion flow without flame

OH Concentration (a.u)

LDV measurements of U and V velocity components in the reaction zone of a combustion flow without flame

AUTOMOTIVE LABORATORIES

E-mail : sorusbay @ mkn.itu.edu.tr

Combustion Modelling

1. Modelling of combustion in Spark Ignition (SI) Engines

* multi-dimensional gas flow in cylinder

* single step reaction for fuel

$$2 \, C_8H_{18} + 25 \, O_2 \rightarrow 16 \, CO_2 + 18 \, H_2O$$

* 3 kinetic reactions and 6 equilibrium reactions

* effect of cylinder geometry, equivalence ratio etc has been investigated

* effect of cylinder pressure on reaction rate is also investigated

Combustion Modelling

Kinetic reactions

$$O_2 + 2\,N_2 \Leftrightarrow 2\,N + 2\,NO$$
$$2\,O_2 + N_2 \Leftrightarrow 2\,O + 2\,NO$$
$$N_2 + 2\,OH \rightarrow 2\,H + 2\,NO$$

Equilibrium reactions

$$H_2 \Leftrightarrow 2\,H$$
$$O_2 \Leftrightarrow 2\,O$$
$$N_2 \Leftrightarrow 2\,N$$
$$O_2 + H_2 \Leftrightarrow 2\,OH$$
$$O_2 + 2\,H_2O \Leftrightarrow 4\,OH$$
$$O_2 + 2\,CO \Leftrightarrow 2\,CO_2$$

Combustion Modeling

Comparison of numerical predictions with experimental data

Combustion Modelling

2. Modelling of combustion in Spark Ignition (SI) Engines

* Multi-dimensional gas flow in cylinder

* Reduced mechanism for combustion

* Prediction of CO, NOx, HC emissions

Combustion Modelling

3. Investigation of Knock in SI Engines (in progress)

* Development of reduced mechanism for combustion of HC fuels

* Low temperature reactions

Combustion Modelling

4. Chemical Kinetics of Methane Combustion
(in progress)

* Development of reduced mechanism for methane

* Control of NOx emissions in methane combustion
systems - internal recirculation of combustion products
(CFD application)

AUTOMATION TECHNOLOGIES DEVELOPMENT AND EDUCATION CENTER

E-mail : guvenc @ mkn.itu.edu.tr

- Undergraduate and Graduate Level Education

- Research on Automation Technologies

- Projects through University - Industry Collaboration

AUTOMATION TECHNOLOGIES

- **Engineering Calculations, Planning** *(Engineering Software)*
- **Supervisory Control, SCADA systems**
- **Communication** *(Fieldbus, CAN)*
- **PC Based Data Acquisition and Control**
- **Control and Automation Using PLC's**
- **Sensor Technology**
- **Electromechanical Systems and Electronics**
- **Hydraulics/Electrohydraulics**
- **Pnaumatics/Electropneumatics**

OUR CURRENT FACILITIES

- PC Based Computer System in a LAN Configuration

- PC Based Data Acquisition and Control Systems (5) and Graphical Programming Language

- PLC Systems

- Engineering Software (Simulation of Pneumatic Systems, Control, Analysis of Mechanical System Dynamics, Finite Element Analysis, Data Acquisition and Control)

- Pneumatic/Electropneumatic Education Sets

- Sensor Education Set

- Servopneumatic Positioning Systems

- AS-I Education Set

- Electronics Education Set

- Rapid Controller Prototyping/Hardware in the Loop Simulation Systems (2)

- Self Erecting Inverted Pendulum

- Various Measurement Devices etc. (Oscilloscopes, Multimeters, Digital Tachometers, Power Supplies, etc.)

The END